

C.C.Rider Seat

Installation Instruction

Part Number: S07

WARNING

Rider and passenger safety depend upon the correct installation of this kit. Improper installation of this kit could result in death or serious injury.

Do not install these seat kits on motorcycles that are not equipped with an appropriate grab strap and passenger footpegs. If footpegs and grab strap are not installed, passengers could fall from a moving motorcycle or grab onto the operator, causing loss of control and death or serious injury.

NOTE

When performing the following installation procedures, avoid scratching painted surfaces (fender, tank, etc.) with tools or metal seat tabs.

Do not allow the seat to contact painted surfaces when sliding it through the grab strap or damage to paint can occur.

INSTALLATION

1. Remove the seat following the steps in the owner's manual. Save seat mounting screw.

2. Carefully remove the protective tape from the rear fender.

3. *Reuse grab strap from the motorcycle.

Remove and discard the existing grab strap. Save fastening hardware from the motorcycle.

4. Remove and discard the studded seat bracket, if equipped.

5. Install retention nut and retention washer in the appropriate fender holes.

6. Mark and apply protective tape to the fender.

a. Mark the bottom of isolators (5) that contact the fender with chalk.

b. Set the seat in place with front and rear mounting locations on the seat aligned with the mounting locations on the motorcycle.

c. Press down on the seat to transfer the marks from the isolators to the fender.

d. Place protective tape (9) on the rear fender over the marks transferred to the fender.

7. Install the grab strap (4) from the kit using the screw (6) and washer (7). Tighten.

8. Slide the back of the seat through grab strap and hook the front tab of seat (12) into the frame (11).

9. Secure seat bracket to fender with a screw from step 1. Tighten.

10. Pull up on the seat to check that it is secure.

