

# C.C.Rider Seat

## Installation Instruction

### Part Number: SC231-R (Rear Seat)

#### WARNING

Rider and passenger safety depend upon the correct installation of this kit. Improper installation of this kit could result in death or serious injury.

Do not install these seat kits on motorcycles that are not equipped with an appropriate grab strap and passenger footpegs. If footpegs and grab straps are not installed, passengers could fall from moving the motorcycle or grab onto the operator, causing loss of control and death or serious injury.

#### NOTE

If original equipment seat mounting hardware is unavailable, a Detachable Seat Hardware Kit is available for separate purchase.

#### INSTALLATION

1. If installed, remove seat mounting nuts (B) and solo seat (A).
2. Install grab strap (2) onto the studs where seat mounting nuts were removed.
3. Install solo seat (A) and seat mounting nuts (B) over the grab straps.
4. Install touring pillion, through the grab strap (2), to the seat mounting nuts:
  - a. Slide two slots in a pillion base into grooves on the seat mounting nuts.
  - b. Verify that tab at front of the seat engages the slot.
5. Secure rear of pillion to the fender using the seat mounting hardware (C) from the OE two-up seat. Lift up on the seat to ensure it is secure

#### Remove Pillion:

1. Remove seat mounting hardware (C) at the rear of the pillion.
2. Pull pillion (1) to the rear to disengage from seat mounting nuts.
3. If necessary, remove seat mounting nuts (B) and solo seat (A). Remove grab strap (2).
4. Install the solo seat and seat mounting nuts over studs. Verify that tab at front of the seat engages a slot in the frame. Lift up on the seat to ensure it is secure.
5. Cover seat mounting nuts with leather flap at the rear of the seat.
6. Remove chrome cap (4) from the bottom of the pillion. Install cap into pillion mounting hole in the fender.

