

SeeStation

4 in 1 Hybrid Camera Specs (AHD/TVI/CVI/CVBS)



Features:

4 In 1 Hybrid Camera

Adopts high definition CMOS Sensor, 25/30fps real time.

It's convenient for user to work with different recorder.

It's easy to operate and change video signal (AHD/TVI/CVI/CVBS) via OSD button.

Specification:

| | | | |
|-----------------------|--|-----------------|-----------------|
| TV System | NTSC/PAL are optional | | |
| Video Signal | AHD/CVI/TVI/CVBS signal are optional | | |
| Image sensor | 1/4" HD CMOS | 1/3" HD CMOS | 1/3" HD CMOS |
| Resolution | 1.0 Mega Pixel | 1.3 Mega Pixel | 2.0 Mega Pixel |
| Pixel | 1280*720P | 1280*960P | 1920*1080P |
| Frame | 25/30 fps | | |
| Illumination | 0.1Lux(F2.0,AGC ON), 0 Lux with IR | | |
| Shutter Electronic | 1/50s~1/100,000s(PAL), 1/60s~1/100,000s (NTSC) | | |
| IR Led | All types are available and optional | | |
| Lens | Fixed and varifocal HD lens are available and optional | | |
| Scanning system | 2:1 interface | | |
| Sync. System | Internal System | | |
| S/N Ratio | >48dB (AGC off) | >58dB (AGC off) | >58dB (AGC off) |
| Day/Night Mode | IR Cut Supported | | |
| White Balance | Auto | | |
| AGC | Auto | Auto/Manual | Auto/Manual |
| OSD | YES, it's available to change the mode for AHD/CVI/TVI/CVBS via pressing Up and down, left and right. Left: CVI; Right: TVI; UP: AHD; Down: CVBS | | |
| Power Supply | DC 12V | | |
| Operation Environment | -20°C~+60°C / 10%~90%RH | | |
| Working Humidity | ≤90% | | |

SeeStation products available at PAM Distributing & other select distributors

800-888-8101

www.seestation.com

www.pamdist.com