

# SC628

## Sonalert Buzzer



# PA100

## Piezo Buzzer



Sonalert buzzer can be mounted in 1-1/8" hole on a single gang wall plate

### Features

#### Standard Features

- Sound level 68 to 80dB
- Medium sound level; Continuous tone
- Buzzer mounts in 1-1/8" hole on single gang wall plate

#### Options

- Available pre-mounted on a single gang wall plate (**TS-41**)
- Single gang wall plate available for self-mounting (**RP-22**)
- **SCVC** Sonalert volume control

### Specifications

#### Dimensions

- Required mounting hole: 1-1/8"

#### Electrical

- Operates on 6 to 28 VDC
- Screw terminals

Piezo buzzer can be mounted in 3/4" hole on a single gang wall plate

### Features

#### Standard Features

- Sound level 90 dB
- Continuous tone
- Buzzer flange mounts in 3/4" hole on single gang wall plate

#### Options

- Available pre-mounted on a narrow stile (**TS-34N**) or standard single gang wall plate (**TS-34**)
- Wall plates available for self-mounting: slimline (**RP-23SLIMLINE**), narrow stile (**TS-34NPO**), or standard single gang (**RP-23**)

### Specifications

#### Dimensions

- Required mounting hole: 3/4"

#### Electrical

- Operates on 3 - 24 VDC
- 12" red and black leads