


PT724A

Single Channel Annual Event Timer

Altronix PT724A extremely versatile 24 Hour 365 Day Event Timers is designed to support a wide range of applications: Home and Building Automation, Security, Access Control, Lighting Control, etc. PT724A is equipped with an independently controlled form "C" relay contact that provides many latching and/or momentary operations during a program schedule of your choice. Events may be set for single or multiple operations on a daily and/or weekly schedule.



PT724A

Specifications

Input

Voltage 12 or 24VAC or VDC operation

Relay

Contact Rating Form "C" 10A/120VAC or 28VDC contacts

Standby Current 10mA (relay off) or 50mA (relay on)

Timer

EE Prom memory protects against loss of programming due to power failure

Accurate crystal controlled clock

Momentary and/or Latching Events

50 individually programmed daily/weekly events

Block programming capacity can accommodate a total of 350 events per week

10 programmable Holiday dates

"First man in" option

Standard or Daylight Savings Time settings

Automatic compensation for leap year

Indicators (LCD)

Alphanumeric LCD display simplifies programming

Back-up Battery (not included)

Type Sealed lead acid or gel type

Failover Upon AC loss, instantaneous

Optional lithium battery (Altronix LB2032) backup maintains clock

Physical and Environmental

Dimensions (L x W x H)

5.25" x 3" x 1" (133.35mm x 76.2mm x 25.4mm)

Product Weight 0.48 lb. (0.22 kg)

Shipping Weight 0.5 lb. (0.23 kg)

Temperature


Operating -20°C to 49°C (-4°F to 120°F)

Storage -25°C to 70°C (-13°F to 158°F)

Relative Humidity 85% +/-5%

Board Dimensions (L x W x H) and Drawing

5.25" x 3" x 1" (133.35mm x 76.2mm x 25.4mm)



Lifetime Warranty