

Features:

High power handling 6.5" in-ceiling speaker system
New magnetic trim-less grille
Smooth-wide frequency response
6.5 inch polypropylene woofer cone
Rubber woofer surround
20 oz Ferrite woofer magnet
1 inch aim-able silk dome tweeter
Neodymium tweeter magnet
High quality crossover with air core inductor
Pure white acoustically lined magnetic grille
4 heavy duty mounting clamps.
Gold plated 12awg binding posts
Complete rough in brackets included (RI-675)
Available in three 25/70V transformer options
10 watt / 20 watt / 30 watt
Sold as pairs
Master carton 2pcs
10 year warranty



Specifications:

Diameter Woofer 6.5" (165.1mm) polypropylene
Diameter Tweeter 1" (25.4mm) silk dome aim-able
Power Handling 125 watts (peak)
Impedance 8 ohms (speaker) 5000 ohms @ 1 watt transformer
Frequency Response 40Hz - 20kHz (± 10 dB)
Dispersion 110°
Sensitivity 92dB (1W 1M) Average

Transformers:

Wattage 10/20/30 watts 25 /70 volts

Primary taps:

E-675-TL-X 10, 5, 2.5, 1.25 watts

E-675-TL-X20 20, 10, 5, 2.5 watts

E-675-TL-X30 30, 15, 8, 4 watts

Secondary tap 8 ohms

Frequency response 40Hz – 17kHz (+/-5dB)

Insertion loss 1.0dB

Included:

2 x RI-675 rough-in brackets

Cutout template

Paint shield

Dimensions:

Dimensions Overall 10.125" (250mm)

Cutout Dimensions Speaker 8.25" (210mm)

Cutout Dimensions RI Bracket 8.5" (216mm)

Depth 3.5" (90mm)

Shipping Weight 13lbs (5.9kg)

Shipping dimensions 14x12x13"



New "Tough-Cam" Mounting System

