



Field Selectable TVI/AHD/CVI/Analog with Dip Switch on Camera

## PAR-TURRET28A

2 Megapixel TVI/AHD/CVI/Analog, Outdoor Turret Housing, 65' IR Range, DWDR, 12VDC, White Housing, with Dip Switch

### Features

- 2 Megapixel (1920 x 1080) Resolution
- Field Selectable TVI/AHD/CVI/Analog with Dip Switch on Camera
- True Day/Night
- Digital WDR
- 65' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- 12VDC Only Operation
- Through InVid Tech DVR: Free App, CMS & MAC Client
- NDAA Compliant

Camera	PAR-TURRET28A
Image Sensor	1/2.9" CMOS
Resolution	1920 x 1080
Image System	PAL / NTSC
Auto Iris	Fixed Iris
Min Illumination	0 Lux (IR ON)
Lens	2.8mm
Field of View	Horizontal: 89.6 Vertical: 58.4
Lens Mount	M123
IR Distance	65 ft
Environmental	IP66
Video Output	TVI/AHD/CVI/Analog
Image Size	1080P (1920 x 1080)
Frame Rate	30fps (60Hz), 25fps (50Hz)
Angle Adjustment	Any angle
Functions	
Screen Display	2 languages supported, Chinese/English
Function Control	OSD
Day & Night	Yes (ICR)
BLC & HLC	Yes
WDR	Digital WDR
Digital NR	Yes
Defect Correction	Live defective pixel correction
S/N Ratio	> 52dB (AGC off)
Electronic Shutter	1/50s ~ 1/100000s (PAL); 1/60 ~ 1/100000s (NTSC)
AGC	Yes
White Balance	ATW, AWC→SET, Manual
Advanced Image	Sharpness, saturation, brightness, etc. are adjustable
Other	
Power Supply	DC12V (±10%)
Working Environment	-4°~122°F (-20°C~50°C) 10% ~90% humidity
Dimensions	Φ3.42" x 4.25" (Φ87x108)

### Ordering Information

**PAR-TURRET28A:** 2 Megapixel Turret, 2.8mm

**PAR-TURRET28BA:** 2 Megapixel Turret, 2.8mm, Black Housing