



# ruggedreaders

## Sleek Design. Vandal Resistant.

Upgrade to something sleeker and more durable with the rugged touch keypad readers. The mullion style reader is just the right width, making it ideal for door frame applications. Or, use the single gang reader, which is a bit wider, making it perfect for wall mounting applications.

### Model

Single Gang PN: RDRGR

Mullion PN: RDRMR



## Specifications:

### Inputs

125 KHZ

### Output

Wiegand protocol

### Environmental

Temperature: -20° ~ +60° C or -4° ~ +140° F

Humidity: 0 - 95% relative humidity non condensing

### Enclosures

Single Gang Dimensions (W x H x D) 3.25" x 4.875" x .875"

Mullion Dimensions (W x H x D) 1.625" x 6.25" x .75"

Metal Enclosure

### Weight

Single Gang: 0.44 lbs (7 oz)

Mullion: 0.5 lbs (8 oz)

### Power

5V DC from included power supply

### Manufacturer's Limited Warranty

One to three-year warranty against defects in materials and workmanship.

For full details, visit [www.prodatakey.com/warranty](http://www.prodatakey.com/warranty)

Visit [www.prodatakey.com/resources](http://www.prodatakey.com/resources) to access marketing, installation, and support resources.

For questions about the PDK rugged readers, please contact [support@prodatakey.com](mailto:support@prodatakey.com).