Revi	ade name : sion date : : date :	30.01.2019 13.02.2019	F Cement Residue Remover Version (Revision) :	4.0.2 (4.0.1)
SEC	TION 1: Identific	cation of the subs	stance/mixture and of the company/ und	ertaking
1.1	Product identifie	er		
	Lithofin KF Cement R			
1.2	Relevant identi		ubstance or mixture and uses advised aga	ainst
1.3	-		r/only representative/downstream user/	distributor)
	Distributor :	• •	Casdron Enterprises Ltd.	-
	Street :		Wood End, Prospect Road	
	Postal code/city :		GB- New Alresford, Hants SO 24 9QF	
	Telephone :		+44 1962 732126	
	Telefax :		+44 1962 735373	
	Contact :		Technical Department E-mail: sales@lithofin.co.uk	
			Emergency telephone number: 0196 2732126 (Only available during office hours)	
	Supplier :		Lithofin AG	
	Street :		Heinrich-Otto-Str. 36	
	Postal code/city :		73240 Wendlingen	
	Telephone :		+49 (0)7024 9403-0	
	Telefax :		+49 (0)7024 9403-40	
	Contact :		Technical Department E-mail: info@lithofin.de	
			Emergency telephone number: +49 (0)7024 9403-0 (Only available during office hours)	
1.4	Emergency tele	phone number		
	366 3661011 1.5			
SEC	TION 2: Hazards	identification		
2.1	Classification of	the substance or	r mixture	
	Eye Dam. 1 ; H318 Skin Corr. 1B ; H314 Met. Corr. 1 ; H290	- Serious eye damage/ey 4 - Skin corrosion/irritation - Corrosive to metals : C	Ilation (EC) No 1272/2008 [CLP] ye irritation : Category 1 ; Causes serious eye damage. on : Category 1B ; Causes severe skin burns and eye dama Category 1 ; May be corrosive to metals.	age.
	Additional info			
		ified as hazardous accor ancy: Skin Corr. 1B (OEC	rding to regulation (EC) No 1272/2008 [CLP]. Results from CD 435)	in vitro test for

Remark

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Full text of H- and EUH-phrases: see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms (EN/D)

Safety Data Sheet (EN / D) according to Regulation (EC) No. 1907/2006 (REACH)			
Trade name : Revision date : Print date :	Lithofin KF Cemer 30.01.2019 13.02.2019	nt Residue Remover Version (Revision) :	4.0.2 (4.0.1)
Corrosion (GHS05)			
Signal word			
Danger Hazard component	s for labelling		
-	CACID ; CAS No. : 75-75-2		
Hazard statements			
H290	May be corrosive to metals.		
H314	Causes severe skin burns and eye	damage.	
Precautionary state	ements	-	
P102	Keep out of reach of children.		
P234	Keep only in original packaging.		
P280	Wear protective gloves/protective	clothing/eye protection/face protection.	
P301+P330+P331	IF SWALLOWED: rinse mouth. Do	NOT induce vomiting.	
P305+P351+P338	IF IN EYES: Rinse cautiously with and easy to do. Continue rinsing.	water for several minutes. Remove contact	lenses, if present
P405	Store locked up.		
Other labelling			

2.3 Other hazards

Adverse human health effects and symptoms

Due to its pH value (see section 9), irritation of the skin and eyes cannot be ruled out.

2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

METHANESULPHONIC ACID ; REACH r	egistration No. : 01-2119491166-34-xxxx ; EC No. : 200-898-6; CAS No. : 75-75-2
Weight fraction :	≥ 15 - < 20 %
Classification 1272/2008 [CLP] :	Met. Corr. 1 ; H290 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 STOT SE 3 ; H335
FORMIC ACID ; REACH registration No	. : 01-2119491174-37-xxxx ; EC No. : 200-579-1; CAS No. : 64-18-6
Weight fraction :	≥ 0,5 - < 1 %
Classification 1272/2008 [CLP] :	Flam. Liq. 3 ; H226 Skin Corr. 1A ; H314 Eye Dam. 1 ; H318

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation. Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : Lithofin KF Cement Residue Remover

Revision date : Print date : 30.01.2019 13.02.2019 Version (Revision) :

4.0.2 (4.0.1)

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

After ingestion

Call a physician immediately. Keep at rest. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed No information available.

4.3 Indication of any immediate medical attention and special treatment needed Notes for the doctor

Treat symptomatically.
Special treatment

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray ABC-powder Foam

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture Hazardous combustion products

Carbon monoxide Carbon dioxide (CO2)

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases. The product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder

Clean contaminated articles and floor according to the environmental legislation. Retain contaminated washing water and dispose it. Dispose of waste according to applicable legislation.

Other information

Clear spills immediately.

	ade name :			sidue Remover	407 (404)
	sion date : : date :	30.01.2019 13.02.2019		Version (Revision) :	4.0.2 (4.0.1)
5.4	Reference to oth Safe handling: see se				
	Personal protection ed Disposal: see section	quipment: see section 8 13			
SEC	TION 7: Handling	and storage			
7.1	Precautions for	safe handling			
	When using do not ea	it, drink, smoke, sniff.			
	Protective mea	sures			
	Skin contact Eye cor the removal of produ- ventilation is not pos	atact Wear personal prot uct. Do not breathe gas/ soible or not sufficient, th oplication of suitable wo	ection equipment (refer /fumes/vapour/spray. Us he entire working area m	excluded: Inhalation of vapours to section 8). Always close cont e only in well-ventilated areas. hust be ventilated by technical n y over personal protection equi	tainers tightly afte If local exhaust neans. Technical
	•		ures for fire prevention.		
	Fire class :	-			
	Shake well befor	r e use nein			
	Advices on gen	eral occupational	l hygiene		
	P362+P364 - Take c	off contaminated clothing	g and wash it before reus	se.	
7.2	Conditions for sa	afe storage, inclu	ding any incompa	atibilities	
	Requirements f	or storage rooms	s and vessels		
	absorbent. Ensure a	dequate ventilation of th		The floor should be leak tight, jo	pintless and not
	Hints on joint s	-			
	Storage class (TR	•			
	Protect from frost		F 2F 0C		
		orage temperature	5 - 25 °C		
		ation on storage of children		losed in a cool, well-ventilated	nlaca
7.3					place.
	Recommendati				
		on ata sheet. Observe instru	ictions for use		
5EC	TION 8: Exposure		nal protection		
8.1	Control paramet				
		xposure limit valu			
		ACID ; CAS No. : 75-75-			
	<i>/</i> /	untry of origin) : TRGS 9	. ,		
	Limit value : Peak limitation :	0,7 mg/ 1(I)	111-		
		1(1)			

Remark :	Y
Version :	01.03.2018
FORMIC ACID ; CAS No. : 64-18-6	
Limit value type (country of origin) :	TRGS 900 (D)
Limit value :	5 ppm / 9,5 mg/m ³
Peak limitation :	2(I)
Remark :	Y
Version :	17.10.2017
Limit value type (country of origin) :	TWA (EC)
Limit value :	5 ppm / 9 mg/m ³

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name :

Lithofin KF Cement Residue Remover

30 01 2019 13.02.2019 Version (Revision) :

4.0.2 (4.0.1)

Revision date : Print date :

07.02.2006

8.2 Exposure controls

Version :

Appropriate engineering controls

Ensure adequate ventilation of the storage area. Technical measures and the application of suitable work processes have priority over personal protection equipment.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection goggles

Required properties

DIN EN 166

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : Data apply to the main component. Butyl caoutchouc, 0,5mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

Recommended glove articles : Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures : Check leak tightness/impermeability prior to use.

Remark : Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams are not substitutes for body protection.

Body protection

Protective clothing.

Suitable protective clothing : Chemical protection clothing Chemical resistant safety shoes

Required properties : acid-resistant.

Protective clothing. : DIN EN ISO 20345 DIN EN 13034 DIN EN 14605

footwear : DIN EN 14404

Remark : Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to reuse. Wash hands before breaks and after work. Apply skin care products after work. Do not breathe gas/fumes/vapour/spray.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance :	Liquid		
Colour :	pink		
Odour :	fruity		
Safety relevant basis data			
Melting point/melting range : (1013 hPa)			

-12 °C

Trade name :

Revision date : Print date : 30.01.2019 13.02.2019

Lithofin KF Cement Residue Remover

Version (Revision) :

4.0.2 (4.0.1)

Initial boiling point and boiling range :	(1013 hPa)	approx.	100	°C	
Decomposition temperature :	(1013 hPa)		not determined		
Flash point :			not applicable		closed cup (EN ISO 3679)
Ignition temperature :			not determined		
Sustaining combustion			No		UN Test L2:Sustained combustibility test
Lower explosion limit : Upper explosion limit :			not determined not determined		
Vapour pressure :	(50 °C)	<	3000	hPa	
Density :	(20 °C)		1,08	g/cm ³	Pyknometer (DIN EN ISO 2811-1)
Solvent separation test :	(20 °C)	<	3	%	Test L1: Solvent separation test (UN)
Water solubility	(20 °C)		miscible		
рН :		approx.	0		DIN 19268
log P O/W :			not determined		(Mixture)
Flow time :	(23 °C)	<	15	S	ISO cup 4 mm (DIN EN ISO 2431)
Odour threshold :			not determined		
Vapourisation rate :			not determined		
VOC content-EC		approx.	0,9	Wt %	*
VOC-France			not applicable		Décret no 2011-321 du 23 mars 2011

(* VOC-EC = "Volatile organic compound (VOC)" means any organic compound having an initial boiling point less than or equal to 250° C measured at a standard pressure of 101,3 kPa; VOC-value in g/L)

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Stable under recommended storage and handling conditions.

10.5 Incompatible materials

The product develops hydrogen in an aqueous solution in contact with metals.

10.6 Hazardous decomposition products Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

There are no data available on the preparation/mixture itself. Data apply to the main component.

Acute oral toxicity

Parameter :LD50 (FORMIC ACID ; CAS No. : 64-18-6)Exposure route :OralSpecies :RatEffective dose :730 mg/kg

Safety Data Sheet	
according to Regulation (EC) No. 1907/2006 (REACH)	

Trade name : Lithofin KF Cement Residue Remover

Revision date : Print date : 30.01.2019 13.02.2019 Version (Revision) :

4.0.2 (4.0.1)

	Method :	
	Parameter :	LD50 (METHANESULPHONIC ACID ; CAS No. : 75-75-2)
	Exposure route :	Oral
	Species : Effective dose :	Rat 649 mg/kg
	Acute dermal toxicity	0+3 mg/kg
	Parameter :	LD50 (METHANESULPHONIC ACID ; CAS No. : 75-75-2)
	Exposure route :	Dermal
	Species :	Rabbit
	Effective dose :	> 1000 - 2000 mg/kg
	Acute inhalation toxicity	2000 2000 mg/kg
	Parameter :	LC50 (FORMIC ACID ; CAS No. : 64-18-6)
	Exposure route :	Inhalation
	Species :	Rat
	Effective dose :	7,85 mg/l
	Exposure time :	4 h
	Specific symptoms in ani	mal studies
	There are no data available on the	
	Irritant and corrosive eff	• •
	Assessment/classification	
	•	uses source huma. Desults from in vitre test for alin correctivity/invitancy/ Chin Corr
	1B (OECD 435)	uses severe burns. Results from in vitro test for skin corrosivity/irritancy: Skin Corr.
	Sensitisation	
	There are no data available on the	
		subacute, subchronic, chronic)
	There are no data available on the	e preparation/mixture itself.
	CMR effects (carcinogen	icity, mutagenicity and toxicity for reproduction)
	Carcinogenicity	
	There are no data available on the	he preparation/mixture itself.
	Other information	
	No indication of human carcino	genicity.
	Germ cell mutagenicity	
	There are no data available on t	
	No indications of human germ ce	ell mutagenicity exist.
	Reproductive toxicity	
	There are no data available on t	he preparation/mixture itself.
	Other information	
	No indications of human reproc	
	Overall Assessment on CMR p	
	The ingredients in this mixture d	o not meet the criteria for classification as CMR category 1A or 1B according to CLP.
	STOT-single exposure	
	See SECTION 2.1 (classification).	
	STOT-repeated exposure	
	See SECTION 2.1 (classification).	
	Aspiration hazard	
	-	
	See SECTION 2.1 (classification).	
ECT	ION 12: Ecological inform	nation
	Toxicity	
		. There are no data available on the preparation/mixture itself.
	Aquatic toxicity	
	Acute (short-term) algae toxi	city

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name :

Parameter :

Species : Effective dose :

Method :

Parameter : Species :

Method :

Exposure time :

Effective dose :

Exposure time :

Revision date : Print date :

Lithofin KF Cement Residue Remover

30.01.2019 13.02.2019 Version (Revision) :

4.0.2 (4.0.1)

EC50 (METHANESULPHONIC ACID ; CAS No. : 75-75-2) Daphnia 70 mg/l 48 h OECD 202 EC50 (FORMIC ACID ; CAS No. : 64-18-6) Daphnia 356 mg/l 48 h OECD 202

Effects in sewage plants

Observe local regulations concerning effluent treatment. Before discharge into sewage plants the product normally needs to be neutralised.

12.2 Persistence and degradability

There are no data available on the preparation/mixture itself.

Biodegradation

The surfactant contained in this mixture complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3 Bioaccumulative potential

There are no data available on the preparation/mixture itself.

12.4 Mobility in soil

There are no data available on the preparation/mixture itself.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

There are no data available on the preparation/mixture itself.

12.7 Additional ecotoxicological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

Waste code (EWC/AVV): 06 01 06*

Waste code packaging

Waste code packaging: 15 01 10*

Waste treatment options

29/35 - Do not empty into drains; dispose of this material and its container in a safe way. Delivery to an approved waste disposal company.

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

	it in the second s	(EN / D
Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)		
Trade name : Revision date : Print date :	Lithofin KF Cement Resid	Iue RemoverVersion (Revision) :4.0.2 (4.0.1)
14.1 UN number		
UN 1760 L4.2 UN proper shippin Land transport (ADR	-	
	O.S. (METHANESULPHONIC ACID · FORMIC ACID)	
CORROSIVE LIQUID, N Air transport (ICAO-	O.S. (METHANESULPHONIC ACID · FORMIC ACID)	
14.3 Transport hazard	O.S. (METHANESULPHONIC ACID · FORMIC ACID) class(es)	
Land transport (ADR	/RID)	
Class(es) : Classification code :	8 C9	
Hazard identification		
No.):	80	
Tunnel restriction co Special provisions :	de: E LQ 1 · E 2	
Hazard label(s) :	8	
Sea transport (IMDO)	
Class(es) :	8	
EmS-No. :	F-A / S-B	ation group 1 Acida
Special provisions : Hazard label(s) :	LQ 1 · E 2 · IMDG-Code segrega 8	ation group 1 - Acids
Air transport (ICAO-		
Class(es) :	8	
Special provisions :	E 2	
Hazard label(s) :	8	
14.4 Packing group		
II	_	
14.5 Environmental ha		
Land transport (ADR		
Sea transport (IMDO Air transport (ICAO-	TI/IATA-DGR): No	
14.6 Special precautio	-	
None		
	according to Annex II of Marpol and	d the IBC Code
not required.		
SECTION 15: Regulate	ory information	
Cofety, bealth an	l an incomental nametica (la siele)	tion on alfie for the substance of
15.1 mixture	d environmental regulations/legislat	tion specific for the substance of
EU legislation		
-	1907/2006 concerning the Registration, Evaluation	n, Authorisation and Restriction of Chemicals
(REACH)	1272/2008 on classification, labelling and packagin of the European Parliament and of the Council on w	
REGULÁTION (EC) No Directive 2008/98/EC		
REGULÁTION (EC) No Directive 2008/98/EC EN 2:1992 (DIN EN 2	2005-01)	
REGULÁTION (EC) No Directive 2008/98/EC EN 2:1992 (DIN EN 2 Authorisations and	2005-01) for restrictions on use	
REGULÁTION (EC) No Directive 2008/98/EC EN 2:1992 (DIN EN 2 Authorisations and Restrictions on us	2005-01) /or restrictions on use e	according to order
REGULÁTION (EC) No Directive 2008/98/EC EN 2:1992 (DIN EN 2 Authorisations and Restrictions on us	2005-01) for restrictions on use a rding to REACH annex XVII, no. : None, if handled	according to order.

Trade name : Lithofin KF Cement Residue Remover 30.01.2019 Revision date : Version (Revision) : 4.0.2 (4.0.1) Print date : 13.02.2019 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Other regulations (EU) Regulation (EC) No. 648/2004 (Detergents regulation) Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work. (Directive 2000/39/EC, Directive 2006/15/EC, Directive 2009/161/EC) REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the export and import of hazardous chemicals [PIC-Regulation] REGULATION (EU) No 98/2013 on the marketing and use of explosives precursors: Not applicable. Regulation (EC) No. 1005/2009 on substances that lead to the depletion of the ozone layer Not applicable. Contains the following substances that deplete the ozone layer: -Regulation (EC) No 850/2004 [POP-Regulation] Not applicable. Name of the persistent organic pollutant (POP): -**National regulations** Observe in addition any national regulations! Germany: TRGS 400 (Risk assessment for activities involving hazardous substances) TRGS 500 (Protective measures) TRGS 510 (Storage of hazardous substances in non-stationary containers) TRGS 555 (Working instruction and information for workers) Water hazard class (WGK) Class: 1 (Slightly hazardous to water) Classification according to AwSV Other regulations, restrictions and prohibition regulations

Switzerland

VOCV-Regulation

Maximum VOC content (Switzerland) : < 3 Wt % according to VOCV

15.2 Chemical safety assessment

For this substance/mixture a chemical safety assessment has not been carried out.

15.3 Additional information

SECTION 16: Other information

16.1 Indication of changes

07. Hints on joint storage - Storage class

16.2 Abbreviations and acronyms

ABC-Pulver	Extinguishing powder for fire class A, B and C
ABEK-P1	combination filter
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AVV	Abfallverzeichnis-Verordnung (Waste Regulation)
AWSV	Ordinance on facilities for the handling of substances hazardous to water
BGR	BG rules and regulations
ca.	circa
CAS	Chemical Abstract Service
CLP	classification, labelling and packaging
CMR	Carcinogen, mutagen or toxic for reproduction
DIN	German Institute for Standardization
DNEL	Derived No-Effect Level
EAK/EWC/EAC/CWR/CER	European Waste Catalogue
EC50 / CE50	Effective Concentration 50%
EG / EC / CE	European Community

13.02.2019

Lithofin KF Cement Residue Remover Trade name : 30.01.2019 Version (Revision) :

Revision date : Print date :

4.0.2 (4.0.1)

EN	European Standard
EUH	supplemental hazard statement of the european union
GefStoffV	Gefahrstoffverordnung (Hazardous Substances Ordinance)
GHS / SGH	Globally Harmonised System
H-Sätze	hazard statements
IATA-DGR	International Air Transport Association-Dangerous Goods Regulations
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization-Technical Instructions
IMDG-Code	International Maritime Dangerous Goods Code
ISO	International Organization for Standardization
LC50 / CL50	Lethal Concentration 50%
LD50 / DL50	Lethal Dose 50%
log P O/W	Partition coefficient n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (marine pollution)
NOAEL (DSET)	No observed adverse effect level
NOEC (CSEO)	No observed effect concentration
Nr.	Number
OECD	Organisation for Economic Co-operation and Development
PBT	persistent, bioaccumulative and toxic
pН	Potentia hydrogenii
PIC	prior informed consent
PNEC	Predicted No-Effect Concentration
POP	Persistent organic pollutants
P-Sätze	precautionary statements
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	International Carriage of Dangerous Goods by Rail
STEL / LECT	short-term exposure limit
TRGS	Technische Regeln für Gefahrstoffe (Technical Rules for Hazardous Substances)
TWA / MPT	time-weighted average
UN/ONU	United Nations
VOC/COV/VOS/LZO	Volatile Organic Compound
VOCV	Ordinance on the Incentive Tax on Volatile Organic Compounds (SR 814.018)
vPvB	very persistent and very bioaccumulative
WGK	Wassergefährdungsklasse (Water hazard class)

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu. For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3 Key literature references and sources for data

Regulation (EC) No 1272/2008 (GHS) ECHA: Registered substances (https://echa.europa.eu/information-on-chemicals/registered-substances) REACH Art. 59: -Candidate List of substances of very high concern for Authorisation (https://www.echa.europa.eu/candidate-list-table)

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard statements for physical hazards : On basis of test data. Hazard statements for health hazards : Calculation method. Hazard statements for environmental hazards : Calculation method.

16.5 Relevant H- and EUH-phrases (Number and full text)

Safety Data Sheet (EN / D) according to Regulation (EC) No. 1907/2006 (REACH)			
Trade name :	Lithofin KF Cement Residue Remover		
Revision date : Print date :	30.01.2019 13.02.2019	Version (Revision) :	4.0.2 (4.0.1)
H226	Flammable liquid and vapour.		
H290	May be corrosive to metals.		
H302	Harmful if swallowed.		
H312	Harmful in contact with skin.		
H314	Causes severe skin burns and eye damage.		
H318	Causes serious eye damage.		
H335	May cause respiratory irritation.		
16.6 Training advice			
None			
16.7 Additional information None			

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.