


Connected Wireless System Guide

Module 1 – System Overview, SG888ZB & SALUS Smart Home Application



SMC-GM-CWSG-M1-2019.11v1(2020-02-19)

Module 1

SALUS Connected Wireless System Guide Contents

Section		Page
1	Introduction Why SALUS? Using this Manual System Overview	1-1
2	SG888ZB Gateway Installation & SALUS Smart Home Application S SG888ZB Gateway Installation. Smart Device Application Download Online Application Access. SALUS Smart Home Application Setup. SG888ZB Gateway – wifi Setup	2-1 2-3 2-3
3	SALUS Smart Home Dashboard Dashboard Overview. Using the Dashboard	
4	Profile Settings My Profile Logout	
5	SALUS Smart Home Main Menu Devices. Gateway. All Devices. Add New Group Edit Group. Add New Device Edit Device Device Alert Management Automation Users and Permissions Status.	5-1 5-2 5-3 5-4 5-5 5-6 5-7
6	Message Window & Status Bar Message Window	
7	Icons & Device Settings Icons (Device, Group, Automation) Device Settings	
8	About this App/FAQ/Contact Support About this App FAQ (Frequently Asked Questions). Contact Support	8-2

Introduction

Why SALUS?

Salus designs and manufactures industry-leading hydronics, HVAC, and fan coil products for heating engineers and contractors who need to drive profitability and deliver customer satisfaction. Through our proven, innovative products, we enable contractors to provide homeowners and building managers with the comfort and control they need, while reducing installation times and minimizing costly call-backs. Our easy-to-install wireless hydronic controls, and patented, industry-first auto-balancing actuators are advancing the industry.

Salus also offers a broad ecosystem of smart home products, including connected thermostats, a smart home hub, smart plugs, water valve shutoff, and door and window sensors. A proven leader in the European market since 2003, Salus is currently expanding across North America.

Using this Manual

For the latest Instructions go to: <u>WWW.SALUSINC.COM</u>

Special Attention Boxes

This manual uses special attention icons to alert the reader of important safety concerns, information important to reliable operation of the controls or helpful installation/setup information.



Safety:

Indicates a condition which may cause severe personal injury, death or major property damage



Important Information:

Indicates information which requires special attention for correct operation of the control



Your Benefit:

Indicates helpful installation or setup information

Introduction

System Overview

The SALUS Wireless System uses Zigbee communications protocol to provide a universal language for smart components to work together seamlessly and securely, with or without an internet connection.

SALUS Wireless System Components with SG888ZB Gateway












SG888ZB Gateway Installation




To operate wirelessly with an internet connection, SALUS wireless devices must use the SG888ZB Gateway. This section provides guidance for installation, joining the Zigbee network with or without an internet connection and connection to the SALUS Smart Home application.


Install the SG888ZB Gateway in a central location close to a 120 VAC electrical receptical and free from radio frequency interference. If the SG888ZB Gateway is intended to be connected to the internet, it must be close to an internet router for setup. Once the Gateway is connected to the internet, a wifi connection can be established and the Gateway can be moved to another location.

STEP 1. Confirm that all required parts are present in the Gateway package: Gateway with port cover, Ethernet Cable, USB Power Cable, USB Power Adapter and Installation/Quick Start Guide.




- STEP 2. Remove the port cover from the bottom of the Gateway by twisting it ¼ turn counterclockwise
- STEP 3. If connecting the Gateway to the internet, attach the ethernet cable and the power cable to the gateway only, making sure it is within easy reach of a router or ethernet connection
 - a) For best results, DO NOT CONNECT the power cable to electrical power outlet until after ethernet cable is attached to the router
 - b) If no internet connection is intended, it is not necessary to attach the ethernet cable to the Gateway
- STEP 4. Reattach the port cover on the Gateway
- STEP 5. Connect the ethernet cable to the Router if desired





STEP 7. When the SG888ZB Gateway is powered, the LED ring around the multi button will be solid green. The LED will then turn red. Once an internet connection is available (if plugged in to a router) the LED will turn green. Using the internet connection, the SG888ZB Gateway will attempt connection to SALUS Smart Home services. If successful, the LED will turn blue. If no interent connection is detected, the LED will be red.



LED Indications

Smart Device Application Download




Download the SALUS Smart Home application on your IOS or Android device for remote access to your home comfort system. After downloading the application, follow the steps in section 4.1.1 to create a user profile and set up an SG888ZB Gateway.













Online Application Access

To access your SALUS Smart Home features without a smart phone application, simply log on to: https://us.salusconnect.io

SALUS Smart Home Account Setup

Whether using a smart device or online application, the user will be prompted to set up a user account.



Choose "Set up an account" at the bottom of the screen. After creating a profile and logging in, the user is prompted to activate a gateway.



See the installation instructions for the SG888ZB Gateway for internet and power connections.



The LED on the Gateway will be blue when the device is connected to the internet. Read through the following activation steps before proceeding to prevent a timeout during activation.



Step 1.
Press the multibutton on top
of the SG888ZB
Gateway to begin the
activation process.
After 2 minutes, the
activation sequence
will time out, so make
sure all required
information is
available.




The gateway serial number will appear once the connection is initiated.

Step 2. Choose the correct country, Hour format and LED Mode. Then scroll down.



Step 3. Enter the street address, city, sate and zip code for the gateway and choose a Gateway name. This information can be updated after activation.



After the SG888ZB gateway is activated, a first-time welcome message is displayed, and a Gateway icon is automatically pinned to the dashboard.



Click the "x" in the upper right-hand corner to remove the welcome message.

SG888ZB Gateway – wifi setup



Step 1. Select the Gateway Icon from the SALUS Smart Home Dashboard.



Step 2. When the tile flips on the display, select the icon title to access gateway settings.

ARRIS-1A49

NETGEAR31


NETGEAR32

NETGEAR91


Connect to your wifi network

Select the strongest signal strength if you have multiple

ş



Step 3. Scroll to the bottom of the gateway setting screen and choose "Scan for wifi".



Step 4. After the application finds available wifinetworks, choose the applicable network.



Step 5. Disconnect the SG888ZB Gateway from the ethernet connection. Be sure that the LED on the Gateway is blue, indicating it is connected to the internet.


Step 6. Move the Gateway to the desired location.

Section 3

SALUS Smart Home Dashboard


With your SALUS Smart Home dashboard, you can effortlessly manage your equipment and connected home from one screen. Here you can pin equipment to the dashboard, automate frequent tasks, and monitor your gateway connection status and equipment states from a computer or smart device.

Dashboard Overview



SALUS Smart Home Dashboard


Using the Dashboard Home Screen



Choosing the gateway tile icon flips the tile on the screen.



Click the "x" in the upper right corner to flip the tile back. Choosing in will unpin the icon from the dashboard. Choosing the gateway name in the upper left provides access to options.



Edit the Gateway name by selecting . Clicking will cause the SG888ZB LED to flash green, identifying the Gateway. Use to access status and setup information for the device. Choose to toggle the pin-to-dashboard status.


Section 4

Profile Settings

Choose the icon in the top header for the Profile menu.



My Profile





The name, email address and phone number can be updated under, "My Profile" at any time. Scrolling down, the user can choose the country, language, clock format, date format and temperature units. Once the desired changes are made to the profile, press the user profile is also available.

Logout




Choosing the Logout option will return the user to the Sign in screen.

Section 5

Main Menu

With your SALUS Smart Home dashboard, you can effortlessly manage your equipment and connected home from one screen. Here you can pin equipment to the dashboard, automate frequent tasks, and monitor your gateway connection status and equipment states from a computer or smart device.



Devices

Update and organize SALUS Smart Home Devices

≻Gateway




Update any of the settings entered during SG888ZB Gateway activation.

≻All Devices

Add, manage or group equipment.


ADD NEW GROUP

Groups are typically used in larger automation systems for keeping track of related equipment. For smaller systems, it may not be desirable to group devices.



Choosing add new group prompts the user to name the group and choose devices to include from the list of ungrouped equipment.

Clicking the $\frac{1}{4}$ icon toggles between pinned $\frac{1}{4}$ and not pinned $\frac{1}{4}$ to the dashboard.




EDIT GROUP



Clicking on an existing device group allows the user to edit or delete the group. Use to edit the group or select "Delete Group" at the bottom of the screen.


Clicking a device tile icon enables access to the device status, serial number, and firmware version. In addition, the user can make changes to the display name of the device and, if applicable, change configuration and/or schedules.




ADD NEW DEVICE




Before adding a new devices to your SALUS Smart Home application, review the installation instructions for the device to be sure it is ready for connection. In many cases, several devices may be added at the same time. When all equipment is ready for pairing, press "Scan for devices".









AWRT10RF Wireless T...

Automations

Automations lets you automatically operate and/or create alerts for one or more device(s) with a single tap. We've pre-selected options that might if your needs. If you don't like them, simply uncheck the Automation or choose a different one. You can always make changes to any Automation later.

Party Mode
Set thermostat to 21°C for 2 hours

Run Comfort Temperature
Set thermostat to 21°C
Run Frost Mode
Set thermostat to 70°C
Set thermostat to 70°C

Pin

Would you like to pin this device to your dashboard?
A pin sticks your most important items to the dashboard for fast, easy access.

The SALUS Smart Home application will list of all devices ready for connection. For each component to be connected, click .

Give each device a unique name for easy identification on the dashboard then press

Choose the to setup any devices where required.

Press Connect Devices .

Change parameters as desired and then press Complete set up

Follow installation, pairing and setup instructions included with each device to finalize the pairing process.


EDIT A DEVICE




To edit a device pinned to the Dashboard, simply click the green tile icon that represents the device. The tile flips on the screen showing limited options.




For example, on a thermostat, available options are changing the operation mode (Heat/Cool/Off) or adjusting the target setpoint. Note that the actual temperature is on the below the bar, the target setpoint is on the top.



Clicking the device name in the upper left of the tile allows the user more setting options.



At the bottom of the option screen is a choice to remove the device. If this option is chosen, the device will not be accessible via the SALUS Smart Home application.








Choosing a tile from Ungrouped Devices or Categories works in the same way.


≻Device Alert Management

Configure Device Alerts and Notifications










Choosing Device Alert Management from the Main Menu provides access to preset alerts and allows users to create custom alerts.

Click the + symbol expands the alert description providing details, the current status and alerting criteria.


Click "Add an alert" to create a custom alert.

Enter a name for the alert and create an alert by pressing the + symbol after the desired criteria.



Set the condition, notification method and priority for the alert.

Press Save .



SALUS SMATHOME GALEWAY
Radiant Thermostats / AWRT10RF Wireless Thermostat
06/20/19 & 04-26 PM

AWRT10RF Wireless Thermostat - No Heat
SALUS SmartHome Gateway
Radiant Thermostats / AWRT10RF Wireless Thermostat
06/24/19 & 02-32 PM

Details

06/24/19 02-32 PM


AWRT10RF Wireless Thermostat
temperature is 82°F.

06/24/19 11:39 AM
AWRT10RF Wireless Thermostat
temperature is 84°F.

06/24/19 10-53 AM
AWRT10RF Wireless Thermostat
temperature is 88°F.

06/24/19 09-30 AM
AWRT10RF Wireless Thermostat
temperature is 88°F.

Press \oplus to review the alert details, current status and alerting criteria.



Click to edit the alert or to delete it.

Automations

Configure Automated Commands




To set up an automation, choose "Add a new Automation" or choose a shortcut to one from the list of available automations.




from list): Check the desired action and scroll down to press

Add Automation . A tile for this automation will be pinned to your dashboard.



Example (Add a new Automation): Choose add a new Automation.




Name the Automation and choose conditions and criteria for the automation.




Additional criteria and timers may be added depending on the device chosen. Press Save.



If desired, choose the Status in which the automation is to be applied. Press Next.




Select preference for pinning the automation to the dashboard. Press Save





Review and test the automation using the Run now button.


Users and Permissions

Add users and set permission levels









Click to add a new user to your SALUS Smart Home System.

Enter an email address and choose access level for new user.


Press Send invitation .


The new user and their access level are displayed. Select ••• to Edit, Resend Invitation or Remove Access for Users.


Update user level and press Save .


Status

For each Status (HOME, AWAY, SLEEPING, VACATION) choose the temperature setpoint and other parameters of the connected devices and equipment.









Message Window & Status Bar

Message Window

The message window can incorporate a custom photo if desired. In addition, prompts to address issues can be displayed here.






Message Window & Status Bar


Status Bar




The status bar shows the current status of the system. By choosing Home, Sleeping, Vacation or Away, the user can change multiple settings at once.




Clicking the bar showing "My Status is XXXX" allows the user to change the current status. Depending on the status settings, choosing a different status can make changes to temperature setpoints and other settings. For installations that don't follow a set schedule, this is an easy way to change many settings at once, based on the current status.



For thermostats, choose between Status and Schedule. Each thermostat allows options for Heat/Cool Temperature, Hold, Off or No Preference.



Window and door monitors set to "Close" will show an issue when open.




Clicking the Issues 3 message will provide details about the issues.

Icons and Device Settings


Icons (Device, Groups, Automations)





 $oldsymbol{\Lambda}$ Current Error – Indicates a low battery on the HVAC Thermostat


Device Settings



Icons and Device Settings

About this App

Choosing About This App displays version and release date information about the software application.



Icons and Device Settings

FAQ (Frequently Asked Questions)

Clicking FAQ provides the latest information about topics that customers have asked about.

Your Dashboard

What Does The Dashboard Do?

Using Tiles

Pinning Tiles

Unpinning Tiles

Changing Banner Picture

Connecting Gateways and Equipment

Managing Equipment

Managing Equipment

How Do I Remove a Piece of Equipment?

What Are Equipment Categories?

What Are Equipment Groups?

How Do I Create a New Group?

How Do I Review or Edit a Group?

See all 27 articles

Profiles

Passwords

Resetting a Forgotten Password

How Do I Change My Password?

How Do I Log In To My Account?

How Do I Log Out?

Login Troubleshooting Tips

Contact Support

Choosing Contact Support from any screen will open your email application initiating direct communication with support@us.salusconnect.io