

3H/2C Wi-Fi Thermostat

ST920WF



The SALUS SOLO Wi-Fi Thermostat is an economical, full featured, connected thermostat which is simple to install, configure and operate.

- Connects easily to 2.4GHz Wi-Fi networks
- Control from your phone, tablet or Alexa and Google Home devices
- Large LCD Display with Touch keys
- 5 powered relay outputs accommodate a wide variety HVAC and hydronic systems
 - 2 Heating & 2 Cooling outputs for conventional HVAC and hydronic systems
 - 3 Heating & 1 Cooling outputs for heat pump applications

Description and Features

- Works with SALUS SOLO application
- Convenient commissioning with Bluetooth
- Alexa and Google Home Support
- Compact Size: 3.94" x 4.17" x 0.92" (100 mm x 106 mm x 22.5 mm)
- Large LCD Display 2.2" x 2.9" (57mm x 73mm)
- Weekday/weekend or daily schedules with 6 intervals per day
- 5 powered relay outputs for fan, heating & cooling
- Configure for conventional boiler/furnace, heat pump, or dual-fuel systems
- Optional Wire Extender (SA918) provides an easy alternative to replacing the thermostat connection wires

Application Overview



Order Details

3H/2C Wi-Fi Thermostat					
Model	Single Unit UPC	Carton GTIN			
ST920WF	817989021687	10817989021684			
Wire Extender Module					
Model	Single Unit UPC	Carton GTIN			
SA918	817989024862	10817989024860			

Specifications

Wi-Fi Network Connected

Controls	
Mode touch button	Fan touch button
	V Down touch button
Indicators	
Temperature	Temperature Set Point
Heat Mode Icon	Cool Mode Icon
Heat/Cool/Auto	Emergency Heating
Fan Status	Keypad Locked
Time of Day	Day of Week
Schedule Icon	Hold Set Point

Electrical

18-30VAC, 60Hz with, or without C-wire (switch selectable) 5 Relay outputs rated 1A @ 18-30VAC

_				٠			п
П	е	r	m	П	n	а	K

	Conventional AC/ Fu	ırnace Heat Pump			
RC	Power – Cool				
RH	Power – Heat				
С	Common				
G	Fan				
Y1	1st Stage Cooling	1st Stage Compressor			
Y2	2nd Stage Cooling	2nd Stage Compressor			
W1/OB	1st Stage Heating	Reversing Valve			
W2/AUX	2st Stage Heating	Aux/ Emergency Heat			
L	Not Used	Check/Fault input			
Note: Use SA918 Wire Extender if C-wire is not available.					

Mechanical

Weight: 0.6lb (297g)

Dimensions: 3.94"H x 4.17"W x 0.92"D (100mm x 106mm x 22.5mm)

Communications

802.11 b/g/n, 2.4GHz band

Bluetooth v4.2 BR/EDR and BLE (for commissioning only)

Environmental

Operating: 32° - 122°F (0° - 50°C), <90% RH, non-condensing Storage: 14° - 140°F (-10° - 60°C), <90% RH, non-condensing

Agency Compliance

FCC, Industry Canada RoHS Compliant

Warranty

5 year limited warranty

Compatible Devices

SA918 Wire Extender Module

Note: Specifications are subject to change without notice

