

General Description

The McBride 8229/11/7025-10 is a pre-assembled ceiling speaker designed for public address and background music systems.

The 8229/11/7025-10 consists of our 8LS822-19 dual cone 6 oz. magnet loudspeaker, our round MC11 one piece baffle and our MCT7025-10 dual 70 and 25 volt 10 watt line matching transformer.

All McBride assemblies are manufactured in-house using our standard, in-stock, high quality components.

As a contractor you can be assured of top notch assembly workmanship, immediate delivery and service, and access to original replacement parts.



Architectural Specifications

McBride 8229/11/7025-10 Ceiling Speaker Assembly

The speaker, baffle, transformer assembly shall be a McBride model 8229/11/7025-10. The 8229/11/7025-10 shall consist of the McBride model 8LS822-19 loudspeaker, the McBride model MC11 round ceiling baffle and the McBride model MCT7025-10 line matching transformer. The McBride 8LS822-19 loudspeaker shall be an 8 inch dual cone type employing a 6 oz. magnet and shall be mounted to the McBride MC11 baffle with concealed studs. The McBride MC11 baffle shall measure 12-3/4 inches in diameter and be 3/16 inches deep. The baffle shall be constructed of heavy gauge steel and finished in a satin white baked epoxy. The McBride MCT7025-10 line matching transformer shall be a 10 watt, dual 70 and 25 volt design and shall have an insertion loss no greater than 1.0 db. The 9 primary tap fly leads shall be colour coded and shall provide 0.625, 1.25, 2.5, 5.0 and 10.0 watt taps for both 25 volt or 70 volt operating modes. The 8229/11/7025-10 shall be supplied completely assembled with the transformer secondary taps connected to the loudspeaker. The 8229/11/7025-10 shall be supplied with four colour matching baffle mounting screws.

Technical Specifications

Model Number:	8229/11/7025-10
Baffle Type:	Circular ceiling baffle with circular perforated sound area.
Loudspeaker:	McBride model: 8LS822-19 8 inch dual cone type with 6 oz. isotropic ceramic magnet. Freq. response: 50 Hz to 15 KHz. Dispersion angle: 90 degrees
Speaker Mounting:	Concealed studs, 4 places.
Baffle:	McBride model: MC11 Screw mounted, 4 places. (uses MC10E back box and/or MC100 mounting channels).
Baffle Finish:	Satin white baked epoxy.
Transformer:	McBride model: MCT7025-10 dual 70 & 25 volt design. Taps: Colour coded leads at 0.625, 1.25, 2.5, 5.0 & 10.0 watts
Overall Dimensions:	Diameter: 12-3/4 inches. Depth: 2-7/8 inches.
Weight:	Approx. 2.6 lbs.
Standard Packaging:	6 to a carton.



Distributed in Canada by:

Tel: (519) 884-3500
Fax: (519) 884-0193

LOUDSPEAKER SOURCE LTD.

638 COLBY DRIVE, WATERLOO, ONTARIO, CANADA • N2V 1A2