

Quality attenuators for stepped attenuation of high level audio signals. Each is mounted on a brushed stainless steel or white plastic designer style wall plate for easy installation. All mount to standard single or double gang electrical boxes (see below).

Available for 70 volt, 25 volt and 8 ohm systems in mono or stereo configurations. Up to 100 watts of speaker load. Low insertion loss (0.65 db typical, 1.0 db max). Stripped and tinned fly leads or terminal block connections for quick installation.



**Part No.
MCATT-10**

Power: 10 watts

Type: 70/25 volt mono

Mounting: 3-9/32" SG

Description:

10 step with zero off position on stainless steel wall plate.



**Part No.
TSLA10S/8**

Power: 10 watts

Type: 8 ohm stereo

Mounting: 3-9/32" SG

Description:

10 step with zero off position on stainless steel wall plate.



**Part No.
TSLA35/70**

Power: 35 watts

Type: 70/25 volt mono

Mounting: 3-9/32" DG

Description:

9 step with zero off position on stainless steel wall plate.



**Part No.
TSLA35/8S**

Power: 35 watts

Type: 8 ohm stereo

Mounting: 3-9/32" DG

Description:

9 step with zero off position on stainless steel wall plate.



**Part No.
MGT7050W**

Power: 50 watts

Type: 70/25 volt mono

Mounting: 3-9/32" SG

Description:

10 step with zero off position on white plastic designer style wall plate.



**Part No.
MGT7010W**

Power: 10 watts

Type: 70/25 volt mono

Mounting: 3-9/32" SG

Description:

10 step with zero off position on white plastic designer style wall plate.

Note: SG = single gang box; DG = double gang box.