



Tel: (519) 884-3500  
Fax: (519) 884-0193

# LOUDSPEAKER SOURCE LTD.

638 COLBY DRIVE, WATERLOO, ONTARIO, CANADA • N2V 1A2

## Millennium Series SB700 Systems

# NEW!

## SB700 MILLENNIUM SERIES

### 2-WAY WEATHERPROOF INDOOR/OUTDOOR CORNER COMPATIBLE SPEAKER SYSTEMS

The MG SB700 Millennium Series loudspeakers are designed to provide excellent sound quality in high performance commercial foreground and background music installations where construction and the acoustic environment require a surface mounted loudspeaker system. The SB700 has an appealing high tech, yet unobtrusive look that suits virtually any installation.

Millennium Series loudspeakers feature an air-tight hermetically sealed trapazoidal enclosure constructed of glass reinforced polypropylene with perforated color matched aluminum grills. The loudspeaker system is comprised of a 5" reinforced polypropylene cone woofer employing a 10 ounce magnet with vented pole piece and 14 mm polycarbonate dome tweeter with neodymium magnet.

The MG SB700 features a high quality low loss 12 db/octave crossover that ensures excellent sonic clarity and high output while providing maximum protection against tweeter burn-out. An indoor/outdoor equalization switch provides an added bass boost when the SB700 is used outdoors or in large rooms.

SB700T systems feature a very large 70/25 volt line matching transformer that provides excellent response characteristics even at low frequencies.

All SB700 systems include gold plated binding post terminations and color matched aluminum mounting brackets. Hook-up wire and mounting hardware included. The SB700 system is available in black or white in both 70V/25V/8 ohm selectable and 8 ohm only versions.



### **Features:**

- Indoor/Outdoor equalization switch (See photo at right).
- Available in 70V/25V/8 ohm selectable and 8 ohm only versions.
- Ultra violet and saltwater proof.
- Rustproof aluminum grills and aluminum mounting brackets included.

### **Specifications:**

Cabinet Dimensions: 9-7/8" high x 7-1/8" wide x 5-3/4" deep.  
Cabinet Finish: High impact glass reinforced polypropylene composite.  
Speaker System: 5" reinforced poly cone woofer, 14 mm poly dome tweeter.  
Sensitivity: 90 db (1 watt / 1 meter)  
Power Handling: 75 watts  
Frequency Response: 45 Hz to 22 KHz  
Transformer Taps: 5W, 10W, 15W, 20W and 30W (applies to "T" versions only).



***SB700TB rear view.***