

## PRODUCT DESCRIPTION

BF SUBLISTOP80 was developed to be applied on sublimated polyester garments. With a thickness of just 80 microns, we added a built-in blocker to the polyurethane film to stop the dye migration process. This product can withstand multiple wash cycles.

Thanks to the highly visible cutting lines and the ease of use, you can rest assured that this product will increase your productivity. BF SUBLISTOP80 features a thickness of only 80 microns.

It can also be layered and can withstand wash cycles up to 40° C.

## APPLICATION INSTRUCTIONS

- Mirror cut BF SUBLISTOP80 with a 45° blade.
- Weed BF SUBLISTOP80 and remove all excess material
- Pre-heat your press to 140°C.
- Sistemare il tessuto sul piatto piano della pressa.
- Place the garment on the lower platen of your heat press.
- Press at 140°C for 8 seconds.
- Remove the carrier

## STANDARD SIZES

- H 150 cm => available lengths:  
25 mt (upon request)
- H 100 cm => available lengths:  
25 mt (upon request)
- H 75 cm => available lengths:  
25 mt (upon request)
- H 50 cm => available lengths:  
25 mt / 12,5 mt / 5 mt / 1 mt (standard)

## APPLICATION TIPS

- Recommended Fibers: organic, synthetic, mixed
- Can be used for layering.
- Can be applied with other B-FLEX films (ex. FATTY, GLITTER, FLOCK, etc.)
- Ability to cut designs as small as 0.25 cm
- Doesn't require a Teflon sheet during the pressing phase.

## TECHNICAL DATA

Film:	PU/ Polyurethane
Thickness:	80 μ (±5%)
Carrier:	Adhesive PET

## APPLICATION

Temperature:	140°C - 285° F
Time:	8"
Pressure:	medium – 3,5 bar – 50 PSI

## LINER REMOVAL

Hot

## WASH RESISTANCE

First Wash:	12 hours after application
Max. Wash temperature:	40° C
Dry Clean:	NO
Softener:	NO
Bleach:	NO
Dryer:	NO

## SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page.

Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

This spec sheet is valid for the following products:  
BF SUBLISTOP80. Rev\_2020/10.