

PRODUCT DESCRIPTION

GIMME5 FLUO is made of Polyurethane and has a brilliant neon finish. It can be heat applied on organic or synthetic fibers in just four seconds. This product is easy to work with; the sticky polyester carrier allows for fast weeding and easy repositioning of details that might have accidentally been removed. It is also soft and comfortable to wear, even with bulky designs. Its thickness (90 micron) and its elasticity make GIMME5 FLUO pleasant and soft on any garment, and ideal for multi-layer applications. GIMME5 FLUO can withstand wash cycles up to 60°C.

APPLICATION TECHNIQUES

- Knockout
- Multi-layer, suggested up to 5 layers
- Layering with other products

APPLICATION STEPS

- Cut - 45° blade
- Weed excess material
- Turn on your heat press - heat to 140°C/285°F
- Place your graphic on the garment
- Press it - 140°C/285°F for 4 seconds
- Remove the liner - hot

SIZES

H 50 cm L 25 mt / 12,5mt / 5 mt / 1 mt

H 75 cm L 25 mt (upon request)

H 100 cm L 25 mt (upon request)





H 150 cm L 25 mt (upon request)

Oeko-Tex
Standard 100
Class I






Comply with
regulation REACH
n°1907/2006/EU






TECHNICAL DATA

-  Film: PU/polyurethane
-  Thickness: 90μ (±5%)
-  Liner: adhesive PET
-  Finish: matte

PLOTTER SETTING

-  Cut settings: mirror
-  Blade: 45°
-  Minimum cut: 0,1 cm

APPLICATION

-  Temperature: 140°C - 285°F
-  Time: 4''
-  Liner removal: hot
-  Pressure: medium - 3,5 bar - 50 PSI
-  Textile: organic, synthetic, mixed

WASH RESISTANCE

First wash after application	wait 12 hours
Max wash temperature	60°C - 140°F
Dry clean	✗
Dryer	✓

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information abovementioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications.

Rev_2021/03

follow us

HEADQUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com | www.b-flexamerica.com

ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com | www.b-flexpacific.com



GIMME5 FLUO

COLOUR GUIDE



- Neon effect withstand more than 100 wash cycles
- Application in only 4 seconds
- Easy to weed

GIMME5



FIVE FLU020A
NEON YELLOW



FIVE FLU030A
NEON ORANGE



FIVE FLU040A
NEON PINK



FIVE FLU050A
NEON GREEN



FIVE FLU06A
NEON BLUE

