

EASI PLANK CLICK FLOORING FOR FLOATING INSTALL

Easi-Plank SPC Hybrid flooring is a robust and highly durable choice for modern interiors. Due to its unique stone polymer composite (SPC) construction Easi-Plank delivers 100% waterproof attributes providing ultimate peace of mind for everyday residential living.

The visual décors feature realistic timber textures and colours in both classic Australian Timber and a contemporary colour palette. The planks also display an attached acoustic IXPE foam layer that delivers excellent noise reduction capabilities. Easi-Plank is anti-static and will resist common household stains & spillage.

EASI PLANK FLOORING SPC Click 1520 x 228 x 6.5mm & *1520 x 180 x 6.5mm						
Colour	Scotia	Trim	Sqm/Ctn	Planks/Ctn	Ctns/Pallet	Micro Bevel
Antique	Homestead	Teak	2.080	6	48	Yes 4 sides
Brown Stone	Tempest	Brown	2.080	6	48	Yes 4 sides
Ironwood	Tumbleweed	Champagne	2.080	6	48	Yes 4 sides
Maize	Coastal Blackbutt	Zermatt	2.080	6	48	Yes 4 sides
Pewter	Silvermoon	Snow	2.080	6	48	Yes 4 sides
Porcelain	Barn Oak	Lugarno	2.080	6	48	Yes 4 sides
Red Stone	Warm Springs	Lugarno	2.080	6	48	Yes 4 sides
Silver Grey	Crystal Lake	Snow	2.080	6	48	Yes 4 sides
Washed Coral	Pale Gorge	Moon	2.080	6	48	Yes 4 sides
Wheat	Buckskin	Moon	2.080	6	48	Yes 4 sides
*Blackbutt	Coastal Blackbutt	Blackbutt	2.189	8	45	Yes 4 sides
*Jarrah	Jarrah	Jarrah	2.189	8	45	Yes 4 sides
*Smoked Spotted Gum	Qld Spotted Gum	Spotted Gum	2.189	8	45	Yes 4 sides
*Spotted Gum	NSW Spotted Gum	Spotted Gum	2.189	8	45	Yes 4 sides

Key Features; Interior waterproof, can be installed in wet areas including bathrooms and laundry. SPC flooring provides a hard wearing surface with good dimensional stability. Excellent for renovations over existing ceramic tiles, minimal telegraphing. High impact surface resistance, 0.5mm décor vinyl wear layer. Super Width planks & easy click profile for install.

Attached IXPE 1.5mm acoustic underlay to enhance walking comfort, warmth and minimise sound transmission. Approx. impact sound reduction of 21dB.

Description & Profile; Stone Polymer Composite (SPC) construction. Unilin click profile. Micro Bevel edges, V4.

Surface features; Realistic timber visuals, on-trend colours and textures. Water based Matte coating.

Slip Rating; AS 4586:2013 Appendix A, slider 96 Wet Pendulum P4.

Fire Test; CHF Value 11.1 kWm². Smoke Value 226% min. VOC Emissions ;< E1, FloorScore Certified SCS-EC10.3-2014 v4.0.



Preference Floors (NSW)

ABN 40 117 801 037
32 Britton Street,
Smithfield NSW 2164
t +61 2 9738 1188
f +61 2 9738 1199
sales@preferencefloors.com.au

Preference Floors (VIC)

ABN 34 151 422 927
27-29 Zilla Court
Dandenong South VIC 3175
t +61 3 9794 5111
f +61 3 9794 5133
vic@preferencefloors.com.au

Preference Floors (QLD)

ABN 81 169 158 990
6/268 Evans Road,
Salisbury QLD 4107
t +61 7 3875 1688
f +61 7 3875 1788
qld@preferencefloors.com.au

Preference Floors (SA)

ABN 63 600 454 215
47 Research Road,
Pooraka SA 5095
t +61 8 8262 2774
f +61 8 8359 4189
sa@preferencefloors.com.au

Preference Floors (WA)

ABN 25 625 850 455
30 King Street,
Bayswater WA 6053
t +61 8 9471 7785
f +61 8 9272 4906
wa@preferencefloors.com.au