EASYGROUND®

TECHNICAL DATA SHEET

EASYGROUND® FLOOR COATING

PRODUCT DESCRIPTION

Material:

EASYGROUND® Floor Coating is a gray colored, 2-component, water-based epoxy floor coating designed for finishing concrete that is in structurally sound condition.

Benefits:

- Easy-to-Use
- Water-Based Epoxy
- Damp Substrate Friendly
- Low VOC & Solvent Free
- Salt Resistant
- Good Chemical Resistance

Area of Application:

EASYGROUND® Floor Coating is a low odor epoxy for concrete floor areas with light to medium traffic, e.g. garage floors, basement floors, mechanical rooms, warehouses, industrial workshops, etc.

Suitable Substrates:

Concrete Substrates Cured for at Least 28 Days

Material Coverage Rate:

Approx. 190 ft^2 (per coat, coverage may vary depending on the chosen system, condition and roughness of the substrate)

Color & Level of Gloss:

Silver Gray (approx. Pantone 444) / matte

Container Size:

1.21 gallon (7 kg) combined container:
Component A: 0.98 gal (6 kg) + Component B: 0.23 gal (1 kg)

Storage:

Store at room temperatures of between 41°F and 77°F and use within 12 months. Protect against frost and direct sunlight.

PRODUCT DATA

Shore D Hardness: Approx. 80

Wear: Approx. 100 mg, CS10, 1000U

Application Time: Approx. 60 minutes

Can be Recoated After: 12 hours

VOC Emission: 30.9% (water - no VOC)

Can be Driven on After: 72 hours

Important: Once fully cured, the coating is nonhazardous. For additional product safety information, please refer to our safety data sheet (SDS).

INSTRUCTIONS

Tools:

Goggles, Gloves, Nylon Naps, Telescopic Painter's Pole, Mixing Tools, & Water

Mixing Products:

Add all of Component B to Component A and mix them carefully and evenly.

Primer & Coating Application:

Primer: EASYGROUND® Floor Coating does not require a separate primer! The first step is to thin EASYGROUND® Floor Coating with up to 24 ounces of water and use as a primer to seal the pores of the concrete. EASYGROUND® Floor Coating can be used on slightly damp substrates (maximum 18% residual moisture). However, there should be no standing or ponding water on the surface of the substrate.

Coating: EASYGROUND® Foor Coating can be applied as a smooth coating, coating + colored chips, or coating + non-slip sand.

Please refer to the appropriate application guidelines for proper installation.

CUSTOMER SUPPORT: (866) 999-9011 | info@easyground.com

EMERGENCY ADVICE: (800) 424-9300

A brand of Kemper System America, Inc.
1200 North America Drive, West Seneca, NY 14224