



BLACK RTV SILICONE

HIGH PERFORMANCE SEALANT

MODEL

SN10300

100% Silicone (Acetoxy)

Permanent Flexibility

Fish Safe

NET WT. 10.3 OZ. (305 ml)

MADE IN USA

ATLANTIC WATER GARDENS

1.330.274.8317

www.ATLANTICWATERGARDENS.com

INSTRUCTIONS: Remove dirt, grease or moisture from surfaces to be bonded. Cut nozzle at angle to desired bead size. Apply silicone in a consistent bead approx 1/4" thick. Dries tack free in about 30 min. Total curing time 24 hrs. Apply at temperatures above 40°F.

WARNING

CONTENTS: 7631-86-9 silica, amorphous, fumed, 4253-34-3 methyltriacetoxysilane, 17689-77-9 ethyltriacetoxysilane, 70131-67-8 polydimethylsiloxane, hydroxy terminated polydimethylsiloxane 63148-62-9
Volatile Organic Content (VOC): 29 grams/liter



HAZARD & PRECAUTIONARY STATEMENTS

- Keep out of reach of children.
 - Suspect of damaging fertility. May cause eye / skin / respiratory irritation
 - Wear eye protection. In case of contact with eyes, immediately flush with water for 15 minutes. If irritation persists, get medical attention. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleared from the fingertips, nails, and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation.
 - Uncured product contact may irritate the skin and lungs. To clean from skin, wipe very thoroughly with dry cloth or paper towel before washing with detergent and water. Avoid breathing vapor. Use in well ventilated area. Get medical advice/attention if you feel unwell or if skin irritation or rash occurs. Wear protective gloves. Dispose of contents/ container to an approved waste disposal plant. Fully cured sealant is non-hazardous.
 - Refer to Safety Data Sheet for detailed information and NFPA listings.
 - Conforms to California Prop. 65 Listed Chemicals (See SDS).
- CAUTION:** Do not exceed 45 psig. when used in air powered caulking guns. Not intended for continuous underwater use. Not for structural glazing.
- STORAGE:** Store in dry area at temperature below 27°C(80°F).
- SHELF LIFE:** 24 months

**FOR EMERGENCY CONTACT:
1-800-424-9300**