

# Single Phase Fountain, Aerator, & Circulator Control Panels



C-25, 120V Single Phase Control Box for 120V Kasco Fountain, Aerator, and/or Circulator Models

> C-85 & C-95, 240V, Single Phase Control Panel for 240V Kasco Fountain, Aerator, and/or Circulator Models



#### **Quick Facts**

- ⇒ U.L. Listed per National Electric Code (NEC) Standards
- ⇒ Class A Human Rated GFCI
- ⇒ 24 Hour Built In Mechanical Timer, Each with 2 ON and 2 OFF Trippers
- ⇒ Built In Photo Cell for Optional Low Voltage Lighting Kits
- ⇒ 120V GFI Receptacle for Optional Lighting
- ⇒ NEMA Type 3R Weatherproof Enclosure
- ⇒ 2 Year Warranty
- ⇒ UPS Shippable
- ⇒ Industrial Strength Design
- ⇒ Built In Mounting Fixtures

#### **C-25**

- ⇒ 120V, Single Phase
- ⇒ Plug & Go 120V Hook Up
- ⇒ 15 Amp Single Pole Class A Human Rated GFCI
- ⇒ 24 Hour Mechanical Timer with Two Each ON and OFF Trippers
- ⇒ Photo Cell for Optional Light Kit
- ⇒ UV Resistant NEMA Type 3R Weatherproof Plastic Enclosure with Two Cord Entry Bottom Openings
- ⇒ Wired 120V "UNIT" Outlet
- ⇒ Wired 120V "LIGHT" Outlet
- ⇒ Door Mounted Instructions
- ⇒ Lockable Enclosure

## C-85

- ⇒ 240V, Single Phase
- ⇒ 20 Amp Class A Human Rated GFCB
- ⇒ Built In Surge Protector

Power Control Panels

- ⇒ 24 Hour Mechanical Timer for Unit
- ⇒ 24 Hour Mechanical Timer for Optional Lights
- ⇒ Terminal Block for Hardwiring
- ⇒ Requires 4 Wire Power (L1, L2, Ground, and Neutral)
- ⇒ Thermoplastic NEMA 3r/4x Enclosure
- ⇒ Door Mounted Wiring Schematic
- ⇒ Lockable Enclosure

### <u>C-95</u>

- ⇒ 240V, Single Phase
- ⇒ 30 Amp Double Pole Square D<sup>®</sup> Class A Human Rated GFCB
- ⇒ Built In Surge Protector
- ⇒ 24 Hour Mechanical Timer for Unit
- ⇒ 24 Hour Mechanical Timer for Optional Lights
- ⇒ Terminal Block for Hardwiring
- ⇒ Requires 4 Wire Power (L1, L2, Ground, and Neutral)
- ⇒ Thermoplastic NEMA 3r/4x Enclosure
- ⇒ Door Mounted Wiring Schematic
- ⇒ Lockable Enclosure

## **Control Panel Specifications**

Model #	Voltage/ Phase/Hz	Breaker Size	Shipping Weight	Number of Boxes
C25	120/1/60	15 Amp	5 Lbs.	1
C85	240/1/60	20 Amp	18 Lbs.	1
C95	240/1/60	30 Amp	18 Lbs.	1

Kasco Marine, Inc. 800 Deere Rd. Prescott, WI 54021



