



Where Performance Meets Prevention.

BUSTAPART™ ALUMINUM

BustApart™ Aluminum is a general purpose, economical, industrial anti-seize and lubricating paste containing micro-sized aluminum particles and graphite in a special no-melt petroleum base grease.

BustApart™ Aluminum adheres well to metal surfaces and offers exceptional wear resistance. Therefore it can provide outstanding protection against galling, seizing and corrosion on metal surfaces even under the most extreme of heat, pressure, steam and water exposure.

BustApart™ Aluminum was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures to 2000°F.

As it is free of copper, it can be safely used on stainless steel or other sensitive alloys. It was formulated to fit a wide variety of metal working, automotive, oilfield, construction and farm equipment applications.



BustApart™ Aluminum is unlike conventional products on the market because the maximum blend of metallic solids, proprietary dry-film lubricants and anti-galling agents have been homogenized into a specially designed petroleum base grease which does not contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. In addition, this stable blend is unaffected by severe temperatures, vibration, expansion and contraction.

HEALTH AND SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment. As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted into a collection vessel and not allowed to soak into the ground or enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, wipe up or scrape up product and deposit in a sealable container. Thoroughly clean area with detergent solutions and rinse well with water.

⚠ WARNING!

Prolonged or repeated skin contact may cause irritation. Use protective wear to avoid eye and skin contact. Wash thoroughly after use. For skin contact, wash with soap and water. If swallowed, seek medical attention immediately. For eye contact, flush with water for 15 minutes and contact a physician. For additional information read the Safety Data Sheet for this product. **KEEP OUT OF REACH OF CHILDREN.**

TECHNICAL DATA

TEST	METHOD	BUSTAPART™ ALUMINUM
NLGI	DATA	1
COLOR	DATA	GREY/SILVER
THICKENER	DATA	SYNTHETIC
TEXTURE	DATA	BUTTERY
VISCOSITY @ 40 cSt	ASTM D-445	221
POUR POINT, F	ASTM D-92	15
FLASH POINT, F	ASTM D-97	420
DROPPING POINT	ASTM D-566	NONE
PENETRATION WORKED 60 STROKES	DATA	290-315

AVAILABLE PACKAGING SIZES



GreaseCo
1101 Cumberland Dr.
Valparaiso, IN 46383
www.GreaseCo.com