



Where Performance Meets Prevention.

BUSTAPART™ ALUMINUM AEROSOL

BustApart™ Aluminum Aerosol contains molybdenum disulfide, graphite and aluminum in a thick grease base. Helps eliminate seizing of threaded parts. Temperature service ranges from -35°F to 750°F. Helps cool hot bearings. Does not contain any chlorinated or fluorinated solvents.

BustApart™ Aluminum Aerosol was designed for engine parts, threaded fittings, nuts and bearings. Areas of use include machine shops, industrial plants, construction companies and automotive shops.



DANGER

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

HEALTH AND SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment. As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted into a collection vessel and not allowed to soak into the ground or enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, wipe up or scrape up product and deposit in a sealable container. Thoroughly clean area with detergent solutions and rinse well with water.

⚠️ WARNING!

Prolonged or repeated skin contact may cause irritation. Use protective wear to avoid eye and skin contact. Wash thoroughly after use. For skin contact, wash with soap and water. If swallowed, seek medical attention immediately. For eye contact, flush with water for 15 minutes and contact a physician. For additional information read the Safety Data Sheet for this product. **KEEP OUT OF REACH OF CHILDREN.**

AVAILABLE PACKAGING SIZES



GreaseCo
1101 Cumberland Dr.
Valparaiso, IN 46383
www.GreaseCo.com

PRIMARY INDUSTRIES



TECHNICAL DATA

TEST	BUSTAPART™ ALUMINUM
FORM	SOLVENT-BASED AEROSOL
ODOR	ALIPHATIC SOLVENT
COLOR	THICK SILVER
DETERGENCY	NONE
TOXICITY	500 PPM OSHA TLV
WETTING ABILITY	SATURATES
STORAGE STABILITY	1 YEAR +
COLD STABILITY	0°F
PHOSPHATES	NONE
FLASH POINT	N/A
FLAME EXTENSION	N/A
SOLUBILITY IN WATER	NON-SOLUBLE
SPECIFIC GRAVITY	N/A
% VOLATILE BY VOLUME	N/A
pH	N/A
PROPELLANT	HYDROCARBON
EVAPORATION RATE	>7
BIODEGRADABILITY	NO

CONTAINS (CAS#): Petroleum Distillates, Hydrotreated Heavy Naphthenic (64742-52-5), Propane/ Butane(68476-86-8), Petroleum Distillates, Hydrotreated Light(64742-47-8), Heptane(67-64-1), 2-Propanone(67-64-1)