

BUSTAPART™ COPPER AEROSOL

BustApart™ Copper Aerosol is a copper-based anti-seize lubricant formulated to withstand high temperatures and extreme pressures. Continues ground conductivity better than ordinary lubricants. Seals out moisture, gases and corrosive fluids from threaded connections. Copper-Graphite combination prevents seizing, galling and premature wear. Contains rust and corrosion inhibitors to assure long life of connectors.

BustApart™ Copper Aerosol was intended for use on all threaded fittings, hand and motor operated valves, gaskets, flanges and "O" rings, bushings, bearings, rollers and conveyors, gears, transmission boxes, chains and drives, electric motors, compressors, hoists, turbines and winches, furnaces, burner assemblies, regulators, pumps, valve stems, control chests and headers, man and handhold and inspection doors, cylinder head, manifold and stud assemblies, fuel injectors, pre-combustion chambers, valve cages, turbo-charger fittings, guides and thread tubing, keyways and spark plugs, torque rod pins and tubes, air cylinder assemblies, pneumatic cylinder shafts, air slides and axle shafts.



DANGER

Extremely Flammable Aerosol, Contains aas under pressure; may explode if heated. Causes skin and serious eye irritation. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national

HEALTH AND SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use.

If disposing of used product, take care to protect the environment. As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted into a collection vessel and not allowed to soak into the ground or enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, wipe up or scrape up product and deposit in a sealable container. Thoroughly clean area with detergent solutions and rinse well with water.

∴ WARNING!

Prolonged or repeated skin contact may cause irritation. Use protective wear to avoid eye and skin contact. Wash thoroughly after use. For skin contact, wash with soap and water. If swallowed, seek medical attention immediately. For eye contact, flush with water for 15 minutes and contact a physician. For additional information read the Safety Data Sheet for this product. KEEP OUT OF REACH OF CHILDREN.

AVAILABLE PACKAGING SIZES











GreaseCo 1101 Cumberland Dr. Valparaiso, IN 46383 www.GreaseCo.com

PRIMARY INDUSTRIES











TECHNICAL DATA

TEOTIMOAL DATA	
TEST	BUSTAPART™ COPPER
FORM	SOLVENT-BASED AEROSOL
ODOR	ETHEREAL SOLVENT
COLOR	COPPER
DETERGENCY	NONE
тохісіту	500 PPM OSHA TLV
WETTING ABILITY	N/A
STORAGE STABILITY	1 YEAR +
COLD STABILITY	0°F
PHOSPHATES	NONE
FLASH POINT	N/A
FLAME EXTENSION	18"
SOLUBILITY IN WATER	0%
SPECIFIC GRAVITY	0.91
% VOLATILE BY VOLUME	>40%
рН	N/A
PROPELLANT	HYDROCARBON
EVAPORATION RATE	N/A
BIODEGRADABILITY	NO

AEROSOL FORM CONTAINS (CAS #): NAPHTHENIC OIL (64742-52-5), HEPTANE (142-82-5), COPPER (7440-50-8), ACETONE (67-64-1), PROPANE/N=BUTANE (68476-86-8), GRAPHITE (7782-42-5)