

website: www.HeatAuthority.com phone: Toll FREE (866) 805-HEAT email: info@HeatAuthority.com



FIELD TESTED IN SOME OF THE MOST DEMANDING ENVIRONMENTS PROMAX HEATING UNITS ARE BUILT RUGGED AND DESIGNED TO LAST.

16, 30 & 55 Gallon Drum Heaters

Drum heaters are easily installed, built to fit securely, wrap around the drum and are secured via Velcro closures. Nylon straps and quick-release buckles are optional.

FEATURES

- · Designed to fit securely; suitable for steel or poly drums
- · Durable and weather-resistant
- Temperature accurate
- Mildew and mold resistant
- Fire retardant

WEATHER-PROOF DIGITAL TEMPERATURE CONTROL SYSTEM

- Change Set Point if necessary (lock out is possible)
- · LCD Display to show Process value
- · Display Celsius or Fahrenheit
- · NEMA 4X enclosure for outdoor use

CONSTRUCTION

- · Dupont Cordura exterior Urethane lined for water & tear resistance
- Dupont Nomex heater construction
- · Silicone insulated heating element
- Dupont Nomex felted insulation
- Power Up to 1500 watt models available
- .. Dabond 2000 Thread -UV and abrasion resistant
- 120V & 220V models available

WARRANTY: One Year Parts & Labor

All components UL Listed

Meets NEC 427.23 standards and CE 73/23/EEC





55 GALLON DRUM HEATER	VOLTAGE	WATTAGE
55 Gallon: 33" High	120V	1800
	220V	1800
55 Gallon: 33" High	120V	1500
	220V	1500
55 Gallon: 33" High	120V	1000
	220V	1000
30 Gallon: 24" High	120V	650
	220V	650
#120/16 Gallon: 21" High	120V	500
	220V	500

ADDITIONAL OPTIONS:
WATER-TIGHT DESIGN: For extended periods exposed to the elements

INSULATING LID: Attaches via Velcro closures

CUSTOM SIZES AND HIGHER POWER UNITS AVAILABLE UPON REQUEST