FS-1001MLJ-C 05/06/19 Item # 13211

Modular Head Unit W x D x H 30" x 11" x 26"

Remote Unit Dimension SRC-10J 35^{3/4}" x 23^{1/2}" x 22"

Installation Dimension* SRC-10J 38" x 29" x 37"

*Dimensions include legs

SRC-10J



FS-1001MLJ-C

Remote Air-Cooled












Project: ______

Qty:______
AIA#:_____

Features

- Quiet operation perfect for dining area
- ► Advanced CleanCycle24™ design 🎏



- Up to 851 lbs. of ice production per 24 hours
- · Durable stainless steel exterior
- EverCheck™ alert system
- No heat, less noise
- 2 second flush cycle every hour
- Flush cycle removes sediment for cleaner ice
- Slim depth easier to clean dispenser
- · Front and back serviceability
- 10 ft. power cord with NEMA 5-15P plug
- Compatible with Hoshizaki condenser or central rack system
- · R-404A Refrigerant

Warranty:

3 Year Parts & Labor on entire machine. 5 Year Parts on Compressor; air-cooled condenser coil. Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

FS-1001MLJ-C Shipping: (LxWxH) 34.75" x 15.75" X 32" Volume: 10.14ft3


			ICE PRODUCTION WATER USAGE										
	Condenser	Model	Air / Water Temp Lbs. per 24 hours 70°/ 50°F 90°/ 70°F		Potable Gal. per 100 lbs. 90°/ 70°F	Condenser Gal. per 100 lbs. 90°/ 70°F	kWh Used per 100 lbs. 90°/ 70°F	Min. Circuit Amp - Max. Fuse/Breaker	Amperage	Voltage	Circuit Wires (including ground)	Refrigerant Charge Amount	Net / Ship Weight (lbs.)
	Remote	FS-1001MLJ-C	851	720	12.0	N/A	5.07	15A	3.0A	115V/60/1*	3	0lb. 3.5 oz.	126/166

		LINE SE	ΓS - Brazing	Required	TEMP RANGE		EL	ECTRICA					
Condenser	Model	25' Length	35' Length	55' Length	Ambient (Outdoor Use)	Voltage Range	Min. Circuit Amp - Max. Fuse/Breaker	Amperage	Voltage	Circuit Wires (including ground)	Heat Rejection BTU/hr.	Refrigerant Charge Amount	Net / Ship Weight (lbs.)
Remote	SRC-10J	HS-5299†	HS-5300 [†]	HS-5301 [†]	-20° - 122°	187-253VAC	20A	9.3A	208-230V/60/1	4	9,800	15 lb. 14 oz.	225 /270

Line sets require refrigerant. Refer to instruction manual for installation and electrical requirements. See instruction manual for wiring diagram.

10 ft. power cord included

Cubelet Cube Dimensions*



* approximate size in inches, image not to scale

Operating Limits FS-1001MLJ-C

Ambient Temp Range
Water Temp Range
45 - 100°F
45 - 90°F

Water Pressure
 Voltage Range
 10 - 113 PSIG
 104-127V/187-253V*

Service FS-1001MLJ-C

- Allow 6" (15 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance/service.
- Allow 24" (61 cm) clearance on left side for removal of cube guides
- Panels easily removed and all components accessible for service.


Plumbing FS-1001MLJ-C

- Icemaker Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

Service- src-10J


- Allow 24" (61 cm) clearance in both front and rear for proper air circulation and ease of maintenance/service.
- For best performance the Remote Condenser should not be more than 33 feet above the icemaker or no more than 10 feet below it. These distances are measure from fitting to fitting.


Hoshizaki reserves the right to change specifications without notice




mm[inches] 908 [35-3/4] ELECTRICAL SUPPLY 7/8" DIA. OPENING 558 WIRE HARNESS CONNECTION 7/8" DIA. OPENING (SRK-10J ONLY) 90 211 186 [8-1/4] [7-3/8] 380 SUCTION LINE 5/8" FIELD CONNECTION

REMOTE AIR-COOLED Front





REMOTE AIR-COOLED



 $35^{3/4}$ " x $23^{1/2}$ " x 37" (W x D x H with legs)

For Use with FS-1001MLJ-C

REMOTE AIR-COOLED

5/8" SUCTION LINE FIELD CONNECTION



TOP VIEW

[4] ICE DISCHARGE HOLE Ø134 [5-1/4] MIN. Ø38mm [1-1/2]

Front

(Sold Separately) 25' HS-5299 35' HS-5300 55' HS-5301

348