

TIG 250PAC/DC II & 315PAC/DC

INDUSTRIAL, CLASSICAL, AC/DC, PULSE

- FULL FUNCTION AND EXPERT IN WELDING ALUMINUM.



Processes

- DC TIG
- AC TIG
- Pulse TIG
- MMA
- Remote control

Package Includes

- Inverter power source
- TIG torch, 4m
- Earth clamp, 3m
- Tungsten electrode



Optional Accessories

- Electrode clamp, 3m
- Foot control pedal
- Helmet

Features

- AC/DC selectable.
- Pulse frequency and pulse width adjustable.
- AC balance adjustable.
- 2T/4T.
- Post-gas adjustable.
- Down-slope adjustable.
- Arc-striking current and arc-extinction current adjustable.
- Tri-proof air duct design.

Model	Input Voltage/Phase/Frequency	Output Current/Voltage/Duty Cycle	Amps Input At Rated Output	Output Range/ OCV	Dimension (mm)	Weight (kg)
TIG 250PAC/DC II	220V/1P/50-60Hz	TIG: 210A/18.4V/30%@40°C 150A/16V/100%@40°C MMA: 160A/26.4V/30%@40°C 120A/24.8V/100%@40°C	TIG: 36.5A@210A MMA: 35.4A@160A	TIG: 10-210A/96V(AC)/68V(DC) MMA: 10-160A/60V	476*340*402	20
TIG 315PA/CDC	380V/3P/50-60Hz	TIG: 300A/22V/20%@40°C 230A/19.2V/100%@40°C MMA: 240A/29.6V/60%@40°C 220A/28.8V/100%@40°C	TIG: 17.2A@300A MMA: 15.5A@240A	TIG: 12-300A/62V MMA: 15-240A/62V	609*332*622	38