-OVERLAND

TUFF STUFF® Overland Awning



Overland Awning Owner's Manual

Congratulations on your purchase of our Tuff Stuff Overland Awning. We strive to provide the ultimate camping experience for every Tuff Stuff product.

Tuff Stuff Overland awnings are made with the best materials that stand up to the most extreme conditions. The convenience of being able to have instant shade just about anywhere is true convenience.

Most of your Tuff Stuff Overland awning components have been fully assembled at the factory. Installation is composed of unpacking, attaching brackets and mounting to your rack. Should you have any questions, please email support@tuffstuff4x4.com or call Customer Service at 1-866-220-0171





WARNING

Improper installation or use of your awning may result in serious damage, injury or death. Follow these installation instructions carefully to ensure proper installation on your vehicle and safe use of your Overland Awning.

Getting Started

This installation manual supports the current Tuff Stuff Overland Awning.

Mounting Directly to a Roof Rack





Mounting directly to roof cross bars





1. Slide the small bolts into the mounting rail of the awning, as seen in the picture to the left.

- 2. With help from another person, hold the awning in place and mark the mounting holes for the awning. It is best to have the mounting bolts as far apart as possible.
- 3. Carefully drill the holes into the roof rack.
- 4. Align awning into desired position and tighten the nuts.
- 5. Re-check all nuts and bolts periodically

STEPS

- 1. Ensure that the roof bars are of enough distance apart to provide sufficient support for the awning.
- 2. Align the long side of the "L" shaped brackets on the roof bars as seen to the left, with the brackets in a suitable position to allow easy access to the awning, without it protruding to far from the side of the vehicle.
- 3. Mark the holes and center punch.
- 4. Drill the holes to clear the long bolts.
- 5. Bolt the "L" shaped brackets to the roof bars.
- 6. Slide the head of the small bolts into the mounting rail of the awning.
- With help from another person, position the awning onto the "L" shaped brackets and install the nylon nuts.
- 8. Align awning into desired position and tighten all nuts and bolts.
- 9. Re-check all nuts and bolts periodically.

QUICK SETUP Procedure

1. Undo the zipper on the protective bag and while holding the awning in place, release the captive buckles.

2.Flip the awning over the top of the cover, this will now allow you to easily swing out the horizontal poles past 90°. Once you have pulled the horizontal poles out extend them out as far as possible and twist to lock into place.

3.Holding the awning in your hands, unroll it to its full length, taking care as you get to the end as the 2 Vertical poles may have come loose during travel.

4.Carefully release the legs from inside the channel, and with one hand holding the center of the awning, set each leg to the desired height and twist the bottom half of the leg to lock.

5.While holding the awning end beam with one arm, align the end pin on one of the horizontal legs with the hole in the end beam. Twist the leg to lock in position. Repeat on the other horizontal leg.

6. Fix the awning material to the horizontal arms using the Velcro straps.

7. Using the pegs and guy ropes secure the awning front beam diagonally outwards to secure the legs.

NOTE: The pegs supplied are designed to be used in hard soil. A different peg design and size may be required to secure your awning depending on the type of terrain you are anchoring it to.

8. Pack away is a reverse of steps 1-7. Be sure to roll the awning material underneath itself. Avoid packing away the awning wet, if the awning has been stored wet, open it at a more convenient time to allow it to dry.

WARNING

1.ALWAYS SET UP AWNING WITH SUFFICIENT ANGLE TO ALLOW THE WATER TO RUN OFF AND NOT POOL ON TOP OF THE AWNING.

2. IT IS HIGHLY RECOMMENDED THAT EXTRA MEASURES ARE TO BE USED TO SECURE YOUR TUFF STUFF OVERLAND AWNING TO THE GROUND IN WINDY CONDITIONS. IN EXTREME CIRCUMSTANCES THE AWNING SHOULD BE PACKED AWAY TO PREVENT DAMAGE. TUFF STUFF OVERLAND WILL NOT BE HELD LIABLE FOR AWNINGS THAT ARE DAMAGED DUE TO ADVERSE WEATHER, OR ANY CONSEQUENTIAL DAMAGES.

3. ANY ELEMENTS APPLIED ON THE VEHICLE ROOF CHANGES THE NORMAL VEHICLE HANDLING. THE MANUFACTURER DISCLAIMS ALL RESPONSIBILITY IN CASE OF ACCIDENTS DUE TO IMPROPER USE, WRONG MAINTENANCE, OR NOT CHECKING THE TIGHTNESS OF THE FASTENING HARDWARE/ BRACKETS.



STEP 1

Open Awning by unzipping the cover



STEP 2

Unclip the two straps that hold awning in place



Clips that hold awning in place can be adjusted.



STEP 3

Remove Side Horizontal poles from bracket



STEP 4

Extend Horizontal Poles to the length required



STEP 5

Lock Horizontal poles in place by twisting the rod.



STEP 6 Roll out Awning



STEP 7

Bring awning out to the complete position and adjust Horizontal poles to fit into awning bracket hole



STEP 8

Horizontal poles fits into awning bracket hole



STEP 9

When side Horizontal poles are at full length tighten to maintain awning position



STEP12

Secure Velcro Straps along support poles to secure fabric to awning top



STEP10

Drop Awning legs to the ground



STEP11

Adjust legs by twisting the bottom pole and adjusting to the correct height





STEP13

Secure supplied guy ropes and stakes to awning



STEP14

Secure stakes to the ground and make sure the guy ropes are secure and taut.

Side Mount



Storage and Handling

- 1) Open the Awning shake out the fabric and use a air compressor to clean.
- 2) Clean the fabric as needed using a mild detergent, warm water, and a soft to medium brush. Rinse fabric of all detergent prior to drying.
- 3) Dry awning in the sun with awning open. The awning must be completely dry before storage, or mildew and mold may occur. This is especially necessary after camping in rain or wet conditions.
- 4) Using a small brush you can remove dirt from the zipper. You can use bees wax or a silicon spray to keep the zipper lubricated
- 5) Before you leave always check the nuts and bolts attaching your awning to the rack. Make sure they are tight and secure. Check the cover is zipped and strapped.
- 6) Avoid creases and seams when rolling up the awning.



Limited Manufacturers Warranty

What is covered

Tuff Stuff Overland warrants to the original purchaser that its products are free from manufacturer defects in material and workmanship,1 year described, except as qualified below.

What is not covered

Tuff Stuff Overland is not be responsible for the natural breakdown of materials that occurs with extended use (e.g., Ultra Violet (UV) light damage on tents, extensive use of zippers), or defects caused by accident, abuse, alteration, animal attack, storm damage, misuse or improper care.

THERE ARE NO OTHER EXPRESS WARRANTIES BEYOND THE TERMS OF THIS LIMITED WARRANTY. IN NO EVENT SHALL Tuff Stuff Overland BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

What Tuff Stuff Overland will do.

If after inspection we find that a product failed due to a manufacturing or material defect, we will repair or replace the product, at our option, without charge. Picture may be requested if applicable.

How to obtain warranty service

First call to obtain an RA# and then return the product, freight prepaid, to Tuff Stuff Overland; or, contact Tuff Stuff Overland Customer Care Department for return authorization: toll free 1-866-220-0171 .Warranty shipments without return authorization cannot be accepted and will be returned at the customers expense. Please provide the RA# on all products.

How state law relates to this warranty

This warranty gives you specific legal rights. You may have other rights that vary from state to state.

Warranty term

Limited 12 Month warranty applies to all awning components.

WHAT PEOPLE ARE SAYING ABOUT US



CUSTOMER CARE

Email: Support@tuffstuff4x4.com

Telephone:

1-866-220-0171 Monday - Friday 8:30 - 5:00pm California Time

Tuff Stuff USA Headquarters: 2205 South Wright St, Santa Ana California USA



EN IN



11 🚇 tuffstuffoverland





tl 🕼 emmaterres17



13 💩 tuffstuffoverland naui







t1 🚇 tuffstuffoverland





Contraction of the

53 F. 10

•

tl 🚳 overland_az

tl 🕘 tuffstuffoverland na

tl 🕼 emmaterres17

Tuest

13 🚇 tuffstuffoverland

tl 🦣 readysetgordon