

# SAFETY DATA SHEET

Issue Date 10-July-2023 Revision Date N/A Version 2

## 1. IDENTIFICATION

**Product identifier** 

Product Name Satin Concrete Sealer

Recommended use of the chemical and restrictions on use

Recommended Use Concrete Curing & Sealing

Uses advised against No Data

Details of the supplier of the safety data sheet

**Distributor Address** 

Floor Skinz - 168 Richards Road - Bridgeton, NJ 08302

**Emergency telephone number** 

Company Phone Number 856-455-6777

24 Hour Emergency Phone Number 800-535-5053 (United States & Canada), International Call: 1-352-323-3500

## 2. HAZARDS IDENTIFICATION

## Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 5
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 2
Flammable liquids Category 2, Hazardous to the Aquatic Environment -	Long Term (Chronic) Hazard Category 2

## **Label elements**

## **Emergency Overview**

#### Danger!

## Hazard statements

Highly flammable

Suspected of Causing Cancer

Toxic to Aquatic Life with Long Lasting Effects

Causes Serious Eye Irritation

May Cause Respiratory Irritation

May Cause Drowsiness or Dizziness

May be Harmful if Swallowed

May be Harmful if Swallowed and Enters Airways

Causes Skin Irritation



Appearance Transparent Liquid Physical state liquid Odor Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating / lighting/ equipment

Use only non-sparking tools

Take action to prevent static discharges

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Avoid release to the environment

Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

If skin irritation occurs: Get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CONTROL CENTER/doctor

Do NOT induce vomiting.

Take off contaminated clothing and wash before reuse

In case of fire use, "alcohol resistant" foam, dry chemical, halon or carbon dioxide to extinguish.

Collect spillage

#### **Precautionary Statements - Storage**

Store in well-ventilated place. Keep Cool. Keep container tightly closed. Store locked up.

#### **Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local/regional/national regulations.

## Hazards not otherwise classified (HNOC)

Repeated exposure may cause skin dryness or cracking

#### Other Information

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### **Substance**

Chemical Name	CAS No.	Weight-%	Trade Secret
Dimethyl carbonate	616-38-6	40 - 70	*
Acrylic Co-Polymer	Proprietary	10 - 30	*
Petroleum naphtha, light aromatic	64742-95-6	10 - 30	*

Naphtha (petroleum), heavy aromatic	64742-94-5	1 - 5	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

#### Description of first aid measures

**General advice** Move out of the dangerous area. Consult a physician. Provide this Safety Data Sheet to the

doctor in attendance.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash off immediately with soap and plenty of water. If skin irritation

persists, call a physician.

**Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If breathing is irregular or stopped, administer artificial respiration. If symptoms

persist, call a physician.

Ingestion IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT

induce vomiting. Never give anything by mouth to an unconscious person.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** Eye, Skin, and Respiratory Irritation.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically. For additional information, see Safety Data Sheet.

### 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Dry Chemical, Alcohol Resistant Foam, Halon or Carbon Dioxide.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

In a fire or if heated a pressure increase may occur and the container may burst.

Hazardous combustion products Carbon dioxide (CO2). Carbon monoxide.

#### Explosion data

Sensitivity to Mechanical Impact Not available.

**Sensitivity to Static Discharge** May be ignited by friction, heat, sparks or flames.

### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

## **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. P261 - Avoid breathing

dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation, especially in confined areas.

Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors

**Revision Date** Satin Concrete Sealer N/A

accumulating to form explosive concentrations. Vapors can accumulate in low areas.

**Environmental precautions** 

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not allow product to enter any drains

or waterways.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike to collect large liquid spills.

Methods for cleaning up Use a non-combustible material like vermiculite or sand to soak up the product and place

into a container for later disposal. Use clean non-sparking tools to collect absorbed

material. Dispose according to local regulations.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not handle until all safety precautions have been read and understood. Avoid contact

with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, Ground and bond container and receiving equipment. Take measures to prevent the buildup of electrostatic charge. Use non-sparking tools. Wash hands and skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective

clothing/eye protection/face protection.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Containers which are

opened must be carefully resealed and kept upright to prevent leakage.

Incompatible materials Keep away from strong oxidizing agents, strong alkalis, and strong acids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters** 

**Engineering Controls** 

**Exposure Guidelines** Dimethyl Carbonate - CAS 616-38-6: None Established. Petroleum Naphtha, Light

Aromatic, CAS# 64742-95-6: OSHA 100 ppm TWA. Naphtha (petroleum), heavy aromatic -

CAS# 64742-94-5: None Established. Copolymer of Styrene and 2-Ethylhexylacrylate -

CAS 25153-46-2: None Established. **Appropriate engineering controls** 

General/Local Ventilation Recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact. Wear chemical resistant gloves at minimum. Wash

skin immediately upon contact. Wash hands at mealtime and end of shift.

Respiratory protection Use respiratory protection unless adequate local exhaust ventilation is provided, or

> exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29

CFR 1910.134) and use NIOSH/MSHA approved respirators.

**Revision Date** N/A Satin Concrete Sealer

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice. Wash hands before and after breaks and at the end of the workday.

CC (closed cup)

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state liquid

**Appearance** Transparent Liquid Odor Solvent

Color Transparent Liquid - May have slight Odor threshold No data available

color due to performance additives.

**Property Values** Remarks • Method

pН

Not Relevant Melting point / freezing point Not Available 149 °C Boiling point / boiling range

(65 °F) Flash point 18.3 °C

**Evaporation rate** Not Available Flammability (solid, gas) Not Relevant

Flammability Limit in Air

**Upper flammability limit:** 7.0% Lower flammability limit: 1.0%

Vapor pressure Not Available Vapor density Not Available

1.005 @ 70 Degrees F Relative density Water solubility Insoluble in water Solubility in other solvents Not Available Partition coefficient Not Available **Autoignition temperature** Not Available **Decomposition temperature** Not Available Kinematic viscosity Not Available **Dynamic viscosity** Not Available **Explosive properties** Not Available **Oxidizing properties** Not Available

Other Information

Softening point Not Relevant Molecular weight Not Available **VOC Content (%)** < 350 g/LDensity Not Available **Bulk density** Not Available

### 10. STABILITY AND REACTIVITY

### Reactivity

Not Available

## **Chemical stability**

Stable.

#### **Possibility of Hazardous Reactions**

Hazardous polymerization does not occur.

### **Conditions to avoid**

Heat, flames and sparks.

## Incompatible materials

Keep away from strong oxidizing agents, strong alkalis, and strong acids.

## **Hazardous Decomposition Products**

Hazardous decomposition products formed under fire conditions, carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Direct contact and vapor inhalation.

**Eye contact** Direct contact.

**Skin contact** Direct contact.

**Ingestion** Direct contact.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Dimethyl carbonate	= 13000 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 140 mg/L (Rat) 4 h
616-38-6			
Petroleum naphtha, light aromatic	-	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm
64742-95-6			( Rat ) 4 h
Naphtha (petroleum), heavy	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m <sup>3</sup> (Rat) 4 h
aromatic			
64742-94-5			

#### Information on toxicological effects

**Symptoms** May cause drowsiness or dizziness if inhaled. May cause respiratory irritation. Causes

serious eye irritation. Causes skin irritation.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Causes severe burns. Irritating to skin.

**Serious eye damage/eye irritation**Irritating to eyes. Risk of serious damage to eyes. Irritation
Irritating to eyes, respiratory system and skin.

**Sensitization Germ cell mutagenicity**No data available.
No data available.

Carcinogenicity Naphtha (petroleum), heavy aromatic (CAS#64742-94-5) Contains an ingredient, Cumene

which is classified by IARC as "possibly carcinogenic to humans" (Group 2B).

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
Not Available.
Not Available.
Not Available.

#### **Numerical measures of toxicity - Product Information**

## 12. ECOLOGICAL INFORMATION

Material is expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### **Ecotoxicity**

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Petroleum naphtha, light aromatic	-	9.22: 96 h Oncorhynchus mykiss	6.14: 48 h Daphnia magna mg/L
64742-95-6		mg/L LC50	EC50
Naphtha (petroleum), heavy	2.5: 72 h Skeletonema costatum	19: 96 h Pimephales promelas mg/L	0.95: 48 h Daphnia magna mg/L
aromatic	mg/L EC50	LC50 static 2.34: 96 h	EC50
64742-94-5	_	Oncorhynchus mykiss mg/L LC50	
		1740: 96 h Lepomis macrochirus	
		mg/L LC50 static 45: 96 h	
		Pimephales promelas mg/L LC50	

flow	w-through 41: 96 h Pimephales	
	promelas mg/L LC50	

#### Persistence and degradability

No data available.

#### **Bioaccumulation**

No data available.

Chemical Name	Partition coefficient
Naphtha (petroleum), heavy aromatic	2.9 - 6.1
64742-94-5	

Other adverse effects No data available.

## 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes Under RCRA 40 CFR 261 this material is a hazardous waste. Dispose of in accordance

with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area. Contact a

licensed professional waste disposal service to dispose of this material.

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations.

## 14. TRANSPORT INFORMATION

**DOT** UN1263, PAINT RELATED MATERIAL, 3, II

Marine pollutant Material is expected to be harmful to aquatic organisms. May cause long-term adverse

effects in the aquatic environment.

<u>IATA</u> UN1263, PAINT RELATED MATERIAL, 3, II

IMDG UN1263, PAINT RELATED MATERIAL, 3, II

## 15. REGULATORY INFORMATION

## **International Inventories**

**TSCA** Complies DSL/NDSL Complies **EINECS/ELINCS** Does not comply **ENCS** Complies **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

#### AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

#### **US State Regulations**

#### **California Proposition 65**

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

#### U.S. State Right-to-Know Regulations

#### **U.S. EPA Label Information**

## 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and Chemical

Properties -

Health hazards 2 Flammability 3 Physical hazards 0 Personal protection X

Issue Date 10-July-2023

Revision Date N/A

**Revision Note** 

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**