

AELP Pallet Beams



AELP pallet beams provide an affordable solution to weigh oversized or bulky items. Equipped with rugged built-in wheels and handles, AELP pallet beams are easy to set up and move. The low-profile beams permit easy accessibility to simplify loading, weighing and unloading. AELP comes with a 15-foot/5-meter shielded cable, allowing the indicator and beams to be positioned as needed. Four OIML-approved load cells provide precise, consistent measurements. The AELP pairs well with Adam's GK or AE 403 indicators.

Low-profile beams facilitate safe, secure weighing of loaded pallets



Features

- Low-profile beams allow easy pallet weighing using pallet trucks
- Approximately five-meter/15-foot shielded cable
- Heavy-duty rubber feet ensure stability of unit
- Integrated wheels permit easy movement
- Can be used with any Adam indicators
- Two beams per set

Applications

- Weighing
- Parts counting
- Percentage weighing
- Checkweighing
- Check counting
- Dynamic / animal weighing



AE 403 Indicator



GKa Indicator

About ADAM:

For more than 45 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

Model	AELP 1000	AELP 2000	AELP 3000	AELP 1000 [GKa]	AELP 2000 [GKa]	AELP 3000 [GKa]	AELP 1000 [AE403]	AELP 2000 [AE403]	AELP 3000 [AE403]
Capacity	2200lb / 1000kg	4400lb / 2000kg	6600lb / 3000kg	2200lb / 1000kg	4400lb / 2000kg	6600lb / 3000kg	2200lb / 1000kg	4400lb / 2000kg	6600lb / 3000kg
Readability	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg	0.5lb / 0.2kg	1lb / 0.5kg	2lb / 1kg
Repeatability (S.D.)	1lb / 0.2kg	2lb / 0.5kg	4lb / 1kg	1lb / 0.2kg	2lb / 0.5kg	4lb / 1kg	1lb / 0.2kg	2lb / 0.5kg	4lb / 1kg
Linearity (+/-)	1lb / 0.4kg	2lb / 1kg	2lb / 1kg	1lb / 0.4kg	2lb / 1kg	2lb / 1kg	1lb / 0.4kg	2lb / 1kg	2lb / 1kg
Excitation Voltage	5 - 10 VAC / DC								
Loadcells	4								
Pan Size	4.7"x52.4" / 120x1330mm								
Weighing Units	N/A			kg, lb, lb:oz, oz, N			g, kg, lb, lb:oz, oz, N, custom unit		
Stabilization Time (sec)	2			2					
Interface	N/A			RS-232					
Calibration	External calibration			External calibration					
Display	N/A			Backlit LCD with 0.8"/ 20mm -high digits					
Power Supply	N/A			12VDC 800mA adapter / Internal rechargeable battery					
Operating Temperature	-10° to 40°C / 14° to 104°F								
Housing	Mild steel base								
Cable Length	16' / 5M								
Overall Dim.	4.7"x52.4"x3.3" / 120x1330x85mm (wxdxh)								
Net Weight	74.9lb / 34kg			79.3lb / 36kg			79.3lb / 36kg		

Accessories

Item number	Description
3052010526	In-use wet cover - GKa Indicator only
3074010266	RS-232 cable (null-modem) - GKa Indicator only
700400103	RS-232 cable - AE 403 Indicator only
3074010507	RS-232 to USB adapter (must order corresponding RS-232 cable)
1120014641	AIP impact printer
1120011156	ATP thermal printer
600002028	AdamDU Data Collection Program
2050013351	Indicator stand
700660289	Calibration certificate

Key Accessories



ATP thermal printer
Easy-to-use features combined with quick set-up equals a truly versatile thermal printer. A single push-button feed key and three easy-to-read LED indicators make operation simple.



AdamDU data collection program
Adam DU software connects a balance to the laboratory network, helping to achieve seamless data collection, transfer and analysis. DU features an easy-to-use interface with a main command window, allowing users to quickly collect information from up to eight Adam balances simultaneously using RS-232 or USB connections.

Supplied by

