


CAS RW-S/L
Wheel Weighers



Pair with an
RW-2601P Indicator



CAS RW-X Axle Weighers

Beacon SERIES

Remote Displays

- Super Bright Energy Efficient 2"/4.5"/6.5" LED Display
- Auto-Learn Technology
- Weather Proof Enclosure with Breather Vent
- Optically Isolated Port for Lightning Protection
- Bluetooth Wireless Option
- Optional Stainless Steel Enclosure



Beacon 65 Remote Display ▲



Beacon 45 Remote Display ▲



Beacon 20 Remote Display ▼



Beacon SERIES | Remote Displays

The CAS Beacon Series Remote Displays are designed to work in conjunction with CAS wheel weighers and axle scales. When used with the CAS RW-2601P Indicator/Printer, the Beacon Series displays individual axle weights and vehicle total gross weight. For applications utilizing other scale indicators, the Beacon Series can be easily configured to read indicator data formats and output strings, reducing set up time.

Each Beacon Series Remote Display shares identical features and operate on the same hardware and software platforms. For standard time & date and optional temperature display capabilities, choose from the CAS Beacon 45 and 65 Series Remote Displays.

CAS Beacon 20 LED Display 2" Viewing Range 50ft	CAS Beacon 45 LED Display 4.5" Viewing Range 250ft	CAS Beacon 65 LED Display 6.5" Viewing Range 300ft
--	---	---

CAS Beacon Series Standard Features

- **Easy to See**
 - Super bright high intensity LED's are easy to read even in direct sunlight
 - Viewing range up to 300 ft
 - Energy efficient LED display segments
 - Non-glare lens for optimal clarity
- **Easy to Use**
 - Auto-Learn technology enables every Beacon Series Remote Display to learn indicator data formats and output strings - reducing configuration and set up time
 - Command mode for custom strings
- **Energy Efficient**
 - Power Save Mode reduces brightness and power consumption during inactivity
 - Selectable day/night brightness levels
 - Automatic sensor adjusts to ambient light conditions
- **Durable and Dependable**
 - Weather proof enclosure with breather vent
 - Optically isolated port for lightning protection
 - 2 year Standard Warranty
- **Versatile**
 - Mirrored display mode
 - Multi-drop capabilities
 - 5 standard communication protocols
 - Optional stainless steel enclosure
 - Optional Time & Date/Temperature display modules
 - Bluetooth Wireless options (consult factory)
 - Utility software programs (consult factory)

SPECIFICATIONS

Features	Beacon 20	Beacon 45	Beacon 65
Viewing Range	50 ft	250 ft	300 ft
Display	High Intensity (Ga Al In P) LED Lamps		
	2" Display	4.5" Display	6.5" Display
	6 Digit (7 segments each)		
	1 or 2 Decimal Places		
Communications	4 Annunciator Lights (GR, NT, lb, kg)		
	RS-232 / RS-422 / RS-485 Multi-drop 20mA Current Loop (Active & Passive)		
Data Format	Auto-Learns Data String, Baud Rate, Data Bits, Parity, and Stop Bits Command Mode for Custom Strings		
Power Requirements	100 - 240 VAC 50/60 Hz		
	Consumption 200 mA (15W)	Consumption 1 A (25W)	
Enclosure	Mild Steel with Powder Coated Finish		
	Breather Vent (prevents condensation)		
	Tough, Dependable, & Weatherproof		
Dimensions (inch/mm)	12 7/8" x 6" x 2 1/4" (327 x 152 x 57)	24" x 10" x 5" (610 x 255 x 127)	32" x 12" x 5" (812 x 305 x 127)
Weight	6 lb. (3 kg)	18 lb. (9 kg)	32 lb. (15 kg)
Operating Temperature	-40°F to 120°F (-40°C to 50°C)		
Warranty	2-year Standard Warranty		

OPTIONS

Features	Beacon 20	Beacon 45	Beacon 65
Stainless Steel Enclosure	•	•	
Visor		•	•
Pole Mount Bracket		•	•
Time & Date Module		•	•
Temperature Module		•	•
12/24V Power Adapter Plate	•		
Bluetooth Wireless Capabilities	Consult Factory		



CAS Corporation
 99 Murray Hill Parkway
 East Rutherford, NJ 07073
 (800) 223-4227 • Fax (201) 933-9025
<http://www.cas-usa.com>

Specifications are subject to change for improvement without prior notice.