

Installation of accessory heads on model BenchMixer Vortexers

1. Grasp the Benchmixer™ with one hand and gently rotate the rubber cup head counter clock wise to loosen and remove it.
2. Observe the bottom of the plastic mount on the accessory head and align the slot on the on the bottom with the two flat areas on the mixer's drive shaft and gently press down. The plastic mount should drop down and sit firmly on the mixer's shaft.
3. Insert the screw in the center hole and gently tighten with a Phillips screw driver.
4. On the 3" round FLAT head, remove the protective paper from each of the tape strips to expose the tacky surface. Then press the smooth side of the round sponge disc on to the plastic mount so that the sponge firmly sticks to the plastic mount.
5. Test the newly installed head at slow speed before using it to mix tubes.

Installation of accessory heads on model BenchMixer Vortexers

1. Grasp the Benchmixer™ with one hand and gently rotate the rubber cup head counter clock wise to loosen and remove it.
2. Observe the bottom of the plastic mount on the accessory head and align the slot on the on the bottom with the two flat areas on the mixer's drive shaft and gently press down. The plastic mount should drop down and sit firmly on the mixer's shaft.
3. Insert the screw in the center hole and gently tighten with a Phillips screw driver.
4. On the 3" round FLAT head, remove the protective paper from each of the tape strips to expose the tacky surface. Then press the smooth side of the round sponge disc on to the plastic mount so that the sponge firmly sticks to the plastic mount.
5. Test the newly installed head at slow speed before using it to mix tubes.

Installation of accessory heads on model BenchMixer Vortexers

1. Grasp the Benchmixer™ with one hand and gently rotate the rubber cup head counter clock wise to loosen and remove it.
2. Observe the bottom of the plastic mount on the accessory head and align the slot on the on the bottom with the two flat areas on the mixer's drive shaft and gently press down. The plastic mount should drop down and sit firmly on the mixer's shaft.
3. Insert the screw in the center hole and gently tighten with a Phillips screw driver.
4. On the 3" round FLAT head, remove the protective paper from each of the tape strips to expose the tacky surface. Then press the smooth side of the round sponge disc on to the plastic mount so that the sponge firmly sticks to the plastic mount.
5. Test the newly installed head at slow speed before using it to mix tubes.

Installation of accessory heads on model BenchMixer Vortexers

1. Grasp the Benchmixer™ with one hand and gently rotate the rubber cup head counter clock wise to loosen and remove it.
2. Observe the bottom of the plastic mount on the accessory head and align the slot on the on the bottom with the two flat areas on the mixer's drive shaft and gently press down. The plastic mount should drop down and sit firmly on the mixer's shaft.
3. Insert the screw in the center hole and gently tighten with a Phillips screw driver.
4. On the 3" round FLAT head, remove the protective paper from each of the tape strips to expose the tacky surface. Then press the smooth side of the round sponge disc on to the plastic mount so that the sponge firmly sticks to the plastic mount.
5. Test the newly installed head at slow speed before using it to mix tubes.