## Nimbus® Precision Balances





Nimbus precision balances feature durable construction and easy operation. With readabilities from 0.001g to 0.1g, the Nimbus precision balance provides a streamlined weighing experience. Small pan precision models have a compact footprint, so the balance occupies minimal space but retains a high level of performance. Solid metal construction throughout the balance provides the durability to withstand chemicals and rigorous daily use. Efficient mechanics plus improved electronics provide readings that are consistent and reliable. Nimbus precision balances with 0.001g (1mg) readability have a removable round glass shield to help minimise effects of air movement.

# Innovative design combined with powerful performance in a premier balance









#### **Features**

- Vivid, backlit LCD easily visible in any lighting conditions
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Level indicator and adjustable feet ensure proper balance setup for optimum weighing results
- Removable draught shield on models with 0.001g readability helps to reduce errors caused by air currents
- Robust metal housing protects internal components in harsh environments
- · Sealed keypad protects against dirt and spills
- · USB and RS-232 interfaces provide speedy communication with computers and printers
- Large, grade 304 stainless steel pan allows easy cleaning
- Vivid, backlit LCD easily visible in any lighting conditions
- Lockdown device to secure balance
- · External calibration allows for verification and adjustment with weights
- Printouts include date and time for data tracking within Good Laboratory Practices (GLP) guidelines
- Selectable digital filtering helps minimise effects of vibration and disturbances
- · Zero-tracking feature ensures display returns to zero reading
- · Multilingual display allows use in many different countries
- AC adapter included

#### **Applications**

- Weighing
- · Parts counting
- · Percentage weighing
- Dynamic / animal weighing
- · Density determination

#### **About ADAM:**

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment.

Adam provides the right balance of speed, performance and value.

# Nimbus® Precision Balances



Model - External Calibration	NBL 223e	NBL 423e	NBL 623e	NBL 823e	NBL 1602e	NBL 2602e	NBL 3602e	NBL 4602e	NBL 4201e	NBL 6201e	NBL 8201e	NBL 12001e	NBL 16001e	NBL 22001e	NBL 32001e	
Model - i= Int Cal P=pillar	NBL 223i	NBL 423i	NBL 623i	NBL 823i	NBL 1602i	NBL 2602i	NBL 3602i	NBL 4602i				NBL 12001P	NBL 16001P	NBL 22001P	NBL 32001P	
Capacity	220g	420g	620g	820g	1600g	2600g	3600g	4600g	4200g	6200g	8200g	12000g	16000g	22000g	32000g	
Readability	0.001g	0.001g	0.001g	0.001g	0.01g	0.01g	0.01g	0.01g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g	
Repeatability (S.D.)	0.002g	0.002g	0.002g	0.002g	0.02g	0.02g	0.02g	0.02g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2g	
Linearity (+/-)	0.002g	0.002g	0.002g	0.002g	0.02g	0.02g	0.02g	0.02g	0.2g	0.2g	0.2g	0.4g	0.4g	0.4g	0.4g	
Pan Size	120mm ø				160mm ø							400x300mm				
Weighing Units	g, mg, ct, GN, N, oz, ozt, dwt, T, custom unit															
Stabilisation Time (sec)	3															
Interface	RS-232, USB															
Calibration	External calibration / Internal automatic calibration									External calibration						
Display	Backlit LCD with 20mm -high digits															
Power Supply	18VDC 50/60Hz 830mA adapter															
Operating Temperature	15° to 35°C															
Housing	Extruded aluminum base with a die-cast aluminum case															
Draught Shield	Round 180mm ø x 110mm								N/A							
Overall Dim.	220x310x270mm (wxdxh)				220x310x90mm (wxdxh)						400x480x100mm (wxdxh) 400x480x590mm (wxdxh) Pillar version					
Net Weight	3.1kg								7.6kg							

#### Accessories

lt a mar mar marla a m	Description
Item number	
104008036	
	Density kit for 120mm ø and 160mm ø pan
	Dust cover for 0.01g and 0.001g balances
	In-use wet cover for 120mm ø and 160mm ø pan
1120011156	•
3126011263	ATP thermal printer paper
3126011281	ATP thermal printer paper (pack of 10)
3014011014	RS-232 cable
600002028	Adam DU data collection program
3074010267	USB cable
3021210953	
3014013041	Security cable
700660290	Calibration certificate
700100207	E2 1g - 200g Calibration Weight Set
700100027	F1 1g - 100g Calibration Weight Set
700100070	F1 1g - 2kg Calibration Weight Set
700100022	E2 100g Calibration Weight
700100023	E2 200g Calibration Weight
700100049	F1 1g - 200g Calibration Weight Set
700100042	F1 1g - 500g Calibration Weight Set
700100232	E2 50g Calibration Weight
700100209	F1 2 x 5kg Calibration Weight
700100007	F1 100g Calibration Weight
	F1 5kg Calibration Weight
700100012	F1 200g Calibration Weight
700100008	F1 500g Calibration Weight
700100009	F1 1kg Calibration Weight
700100010	F1 2kg Calibration Weight

#### **Key Accessories**



#### Anti-vibration table

The AVT anti-vibration table offers a solid, stable surface to help decrease vibration during the operation of analytical or precision balances. The AVT can help reduce fluctuations and inconsistency in measurement resulting from environmental affects.



### ATP thermal printer

Easy-to-use features combined with quick set-up equals a truly versatile thermal printer. A single push-button feed key and three easy-to-read LED indicators make operation simple.



### AdamDU data collection program

Adam DU software connects a balance to the laboratory network, helping to achieve seamless data collection, transfer and analysis. DU features an easy-to-use interface with a main command window, allowing users to quickly collect information from up to eight Adam balances simultaneously using RS-232 or USB connections.

### Supplied by