



More information on the website
radwag.com/en/info,w1,GDY

PUE 7.1P (panel) Terminal



Datasheet

Physical parameters	
Display	5,7" resistive colour touchscreen
Device dimensions	215×156×120 mm
Packaging dimensions	300×250×130 mm
Net weight	0,8 kg
Gross weight	1,2 kg
Protection class	front IP 66/67, construction IP 32
Additional weighing platform module	Moduł dodatkowego przetwornika A/C DP4
Number of buttons	8
Communication interface	
Communication interface	2×RS232, 2×USB, Ethernet, 4 IN / 4 OUT (digital)
Metrological parameters	
Maximum increase of signal	19,5 mV
Minimum load cell impedance	50 Ω
Maximum load cell impedance	1200 Ω

Metrological parameters	
Load cell excitation voltage	5V DC
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Relative humidity	10% ÷ 85% RH no condensation
Construction	
Keypad	panel touchscreen
Housing	stainless steel
Components and software	
Operating system	Linux
Processor	quad-core 64-bit Cortex-A53 1,2 GHz
Memory	RAM 1GB LPDDR2
Data memory	16 GB (micro SD)
Features of use	
Max number of platforms	2



Compatible with

Receipt Printer
Barcode scanners
Label Printers
USB Hubs
IN/OUT Cables

Keypad, external switches
RS 232, RS 485 cables
RS 232 – USB Converter
RS 232 cables (scale - EPSON printer)

Software

E2R System
Audit Trail Reader
RADWAG Connect
RADWAG Remote Desktop
RADWAG Development Studio
Scales Editor 2.0

RAD-KEY
LabVIEW Driver
Label Editor R02
R-LAB
R.Barcode

Device dimensions

