



More information on the website
radwag.com/en/info,w1,H8F

5Y.35.PM Precision Balance



The drawings, photos and graphics used are for illustrative purposes only.

Functions

-  Autotest
-  Dosing
-  Percent Weighing
-  Parts counting
-  Peak hold
-  Formulation
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  IR sensors
-  GLP Procedures
-  Animal weighing
-  Pipettes Calibration
-  Air density correction
-  Density determination
-  Differential weighing
-  Ambient conditions monitoring
-  Statistical Quality Control
-  Packaged Goods Control
-  ALIBI Memory
-  Wi-Fi

Datasheet

Metrological parameters

Maximum capacity [Max]	35 kg
Minimum load	5 g

Metrological parameters	
Readability [d]	0.1 g
Verification unit [e]	1 g
Tare range	-35 kg
Minimum weight (USP)	100 g
Minimum weight (U=1%,k=2)	10 g
Repeatability (Max)	0.05 g
Linearity	±0.3 g
Stabilization time	1 s
Adjustment	internal (automatic)
OIML Class	II
Physical parameters	
Leveling system	semi-automatic - LevelSENSING
Display	10" touchscreen
Weighing pan dimensions	350×260 mm
Packaging dimensions	520×520×280 mm
Net weight	12 kg
Gross weight	16 kg
Construction	
Protection class	IP 43
Communication interface	
Communication interface	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2.4A Waga: 12 – 15V DC 1.4A max*
Environmental conditions	
Operating temperature	+10 – +40 °C

* The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



Accessories

MediaBox

- IM02.1 (MediaBox) Communication Module [WX-016-0303]

RFID Tags

- RFID Tag [WX-015-0330]

Antivibration Tables

- SAL/STONE/H Stainless Steel Antivibration Table [WX-001-0079]
- SAL/STONE/C Antivibration Table [WX-001-0078]

Power Adapters

- ZR-04/1 Powerbank [WX-015-0329]

Under-pan weighing

- Under-Pan Weighing Hook (PM, WLC, WLY) [WX-015-0324]

RS 232, RS 485 cables

- Cable to the ZR-03/1 and ZR-04/1 Powerbank [WX-013-0244]
- PT0455 Cable [WX-013-0239]

USB Hubs

- USB 3.0 Hub [WX-015-0286]

RS 232, RS 485 cables

- PT0454 Cable [WX-013-0240]

- ZR-03/1 Powerbank [WX-015-0319]

Additional modules

- RES Radwag Extended SI Module (5Y, CY10) [WX-016-0315]
- 21 CFR Part 11 Compliance Module (4Y, 5Y, CY10) [WX-001-0133]

Professional weighing table

- PSW Professional Single Weighing Workstation [WX-001-0020]

Protective cover for balances

- Hybrid Protective Glass 5Y, CY10 [WX-001-0435]

Barcode scanners

- LS2208 Barcode Scanner [WX-006-0005]
- PM9501-433RBK20 Barcode Scanner [WX-006-0051]
- PD9531-K1 Barcode Scanner [WX-006-0046]
- DS2208 Barcode Scanner [WX-006-0036]
- PM9501-433RBK10 Barcode Scanner [WX-006-0045]
- PD9531-K2 Barcode Scanner [WX-006-0050]

Balance Storage Case

- Transport Case for 5Y.PM [WX-002-0044]

- PT0443 Cable [WX-013-0229]

Stands, wall mounting kits and mounting brackets

- Wall mounting kit for 5Y / PUE CY10 terminals [WX-002-0131]

Receipt Printer

- RTP-UEW80 Radwag Thermal Receipt Printer (USB + Ethernet + WiFi) [WX-007-0118]
- RTP-RU80 Radwag Thermal Receipt Printer (RS232 + USB) [WX-007-0119]

Fingerprint Reader

RS 232 – USB Converter

- Moxa UPort 1110 Converter [WX-015-0278]

Software

- Scale Editor 2.1 [WX-010-0173]

Device dimensions

