

Weighing Technology



50lb x0.01lb 100lb x0.02lb 200lb x0.05lb 500lb x0.1lb



- NTEP Approved Class III
- · Stainless Steel Pillar & Square Base
- Stainless Steel Backlit LCD Indicator
- Specially Protected Load Cell
- Reads in lb, kg, oz only
- Rechargeable Battery

















| Model | TitanH 50-16 | TitanH 100-16 | TitanH 200-16 | TitanH 100-24 | TitanH 200-24 | TitanH 500-24 |
|---------------------------|---|-------------------|-------------------|-------------------|-------------------|------------------|
| Capacity | 50 lb / 25 kg | 100 lb / 50 kg | 200 lb / 100 kg | 100 lb / 50 kg | 200 lb / 100 kg | 500 lb / 250 kg |
| Readability | 0.01 lb / 0.005 kg | 0.02 lb / 0.01 kg | 0.05 lb / 0.02 kg | 0.02 lb / 0.01 kg | 0.05 lb / 0.02 kg | 0.1 lb / 0.05 kg |
| Divisions | 5,000 | | | | | |
| Weighing Units | lb, kg, oz only | | | | | |
| Functions | Accumulation | | | | | |
| Tare Range | Full capacity by subtraction | | | | | |
| Power Source | AC/DC adapter 12 VDC and rechargeable battery | | | | | |
| Construction | Stainless steel indicator, platter and base with stainless steel protection system | | | | | |
| Display | 2" high backlit display | | | | | |
| Platform Size (W x D x H) | 16 x 16 x 4" | 16 x 16 x 4" | 16 x 16 x 4" | 24 x 24 x 6" | 24 x 24 x 6" | 24 x 24 x 6" |
| Dimensions (W x D x H) | 16 x 16 x 35" | 16 x 16 x 35" | 16 x 16 x 35" | 24 x 24 x 35" | 24 x 24 x 35" | 24 x 24 x 35" |
| Operating Environment | 14 ° F to 104 ° F (-10 ° C to 40 ° C) | | | | | |
| Net Weight | 26 lb / 12 kg | | | 49 lb / 23 kg | | |
| Shipping Weight | 34 lb / 16 kg | | | 55 lb / 25 kg | | |
| Options | Stainless Steel Wheel Kit, Bi-Directional RS232 Interface (must be factory installed) | | | | | |
| Approvals | V-FS Indicator: NTEP 17-145, Base NTEP 12-077A1 | | | | | |

| Features | Benefits | | |
|---|---|--|--|
| Stainless steel construction | Easy to clean for food processing or harsh environments | | |
| Heavy duty construction | Will withstand harsh industrial operation | | |
| Sealed electronics | Improved water and dust resistance | | |
| Reads in lb, kg, oz only | Flexibility of operation | | |
| Zero tracking | Ensures you always start weighing at zero | | |
| Reads in kilograms, pounds and ounces | Flexibility of operation | | |
| Built-in rechargeable battery or external power adapter | Portability - battery lasts a minimum of 120 hours (without back light) | | |
| Accumulation function | Allows you to add together consecutive weights to arrive at a total | | |