



Weighing Technology

# TitanH™

Intelligent-Weigh™



50lb x0.01lb  
100lb x0.02lb  
200lb x0.05lb  
500lb x0.1lb



- NTEP Approved Class III
- Stainless Steel Pillar & Square Base
- Stainless Steel Backlit LCD Indicator
- Specially Protected Load Cell
- Reads in lb, kg, oz only
- Rechargeable Battery





Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance



TitanH™

Series

| Model                     | TitanH 50-16   | TitanH 100-16     | TitanH 200-16     | TitanH 100-24     | TitanH 200-24     | TitanH 500-24    |
|---------------------------|--|-------------------|-------------------|-------------------|-------------------|------------------|
| Capacity                  | 50 lb / 25 kg  | 100 lb / 50 kg    | 200 lb / 100 kg   | 100 lb / 50 kg    | 200 lb / 100 kg   | 500 lb / 250 kg  |
| Readability               | 0.01 lb / 0.005 kg   | 0.02 lb / 0.01 kg | 0.05 lb / 0.02 kg | 0.02 lb / 0.01 kg | 0.05 lb / 0.02 kg | 0.1 lb / 0.05 kg |
| Divisions                 | 5,000  |                   |                   |                   |                   |                  |
| Weighing Units            | lb, kg, oz only  |                   |                   |                   |                   |                  |
| Functions                 | Accumulation   |                   |                   |                   |                   |                  |
| Tare Range                | Full capacity by subtraction   |                   |                   |                   |                   |                  |
| Power Source              | AC/DC adapter 12 VDC and rechargeable battery                                      |                   |                   |                   |                   |                  |
| Construction              | Stainless steel indicator, platter and base with stainless steel protection system |                   |                   |                   |                   |                  |
| Display                   | 2" high backlit display  |                   |                   |                   |                   |                  |
| Platform Size (W x D x H) | 16 x 16 x 4"   | 16 x 16 x 4"      | 16 x 16 x 4"      | 24 x 24 x 4"      | 24 x 24 x 4"      | 24 x 24 x 4"     |
| Dimensions (W x D x H)    | 16 x 16 x 35"  | 16 x 16 x 35"     | 16 x 16 x 35"     | 24 x 24 x 35"     | 24 x 24 x 35"     | 24 x 24 x 35"    |
| Operating Environment     | 14 °F to 104 °F (-10 °C to 40 °C)  |                   |                   |                   |                   |                  |
| Net Weight                | 26 lb / 12 kg  |                   |                   | 49 lb / 23 kg     |                   |                  |
| Shipping Weight           | 34 lb / 16 kg  |                   |                   | 55 lb / 25 kg     |                   |                  |
| Options                   | Stainless Steel Wheel Kit, Bi-Directional RS232 Interface                          |                   |                   |                   |                   |                  |
| Approvals                 | V-FS Indicator: NTEP 17-145, Base NTEP 12-077A1                                    |                   |                   |                   |                   |                  |

| Features  | Benefits  |
|---|---|
| Stainless steel construction                            | Easy to clean for food processing or harsh environments                 |
| Heavy duty construction                                 | Will withstand harsh industrial operation                               |
| Sealed electronics                                      | Improved water and dust resistance                                      |
| Reads in lb, kg, oz only                                | Flexibility of operation  |
| Built in rechargeable battery                           | Portability   |
| Zero tracking   | Ensures you always start weighing at zero                               |
| Reads in kilograms, pounds and ounces                   | Flexibility of operation  |
| Built-in rechargeable battery or external power adapter | Portability - battery lasts a minimum of 120 hours (without back light) |
| Accumulation function                                   | Allows you to add together consecutive weights to arrive at a total     |