



- Compatible With Any Base
- Reads in lb, kg, g, oz
- 2" High Backlit LCD Display
- Optional Bi-Directional RS232
- Will Drive 4 x 350  $\Omega$  Load Cells
- Optional Light Tower



Optional



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

# VFS-W Indicator

Model	VFS-W
Divisions	Up to 120,000
Weighing Units	lb, kg, g, oz
Functions	Net/Gross, Checkweighing, Counting
Tare Range	100% Subtractive
Power Source	External AC power adapter (included) , rechargeable battery
Construction	IP 67 Stainless Steel Washdown
Display	2 inch high bright backlit LCD display
Connectivity	Optional Bi-Directional RS232 Interface (must be factory installed)
Net Weight	5.7 lb / 2.6 kg
Shipping Weight	7.5 lb / 3.4 kg
NEMA / IP rating	NEMA 4X / IP 67
Options	Bi-Directional RS232 Interface, Printer, Light Towers

Features	Benefits
Large backlit display	Can be easily read in less than ideal conditions
Adjustable weighing speed filters	Allows you to adjust for operational and environmental conditions
Automatic Zero tracking	Ensures that you always start weighing at zero
Built-in rechargeable battery or external power adapter	Portability (battery lasts approximately 150 hours)
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
RS232 Interface (Optional-Must be factory installed)	Allows for easy maintaining of records



Shown With Optional Light Towers

Manufactured for Intelligent Weighing Technology, Inc. in an ISO 9001 certified facility

• Phone: 1-805-642-3034      www.intelligentwt.com

Rev: VFS 1-20