

Luxury vinyl (PVC) wood plank

- Embossed wood grain
- matt finish; micro bevelled
- nano silver antibacterial finish
- UV resistant

Product Information:

Thickness: 3mm

Wear Layer: 0.3mm (Domestic)

Length: 1219.2mm

Width: 228.6mm

Pack Size: 13 Planks/Pack = 3.62m²/box

General Performance: **EN685**

Reaction to Fire: **EN 13501-1 Class BF1-S1**

Slip Resistance: **Exceeds ADA Requirement**

Abrasion Resistance: **ASTM D 3884**

Indentation –Residual: **EN 433 0.1mm**

Dimensional Stability: **EN 434**

Castor Chair: **Suitable**

Colour fast to Light: **ISO 105-B 02**

Flexibility: **EN 435 Pass**

Resistance to staining: **EN 423 Pass**

General Instruction:

Refer to sams 10070:2007 for *“the installation of resilient thermoplastic and similar flexible floor covering materials”*.

Tools required:

- Vinyl Plank Flooring
- Adhesive (A suitable water-based, low voc acrylic adhesive)
- Sealing primer
- Floor patching compound
- Wood putty
- Measuring tape
- Chalk line or marker pen
- Tools for removing baseboards and thresholds
- Utility knife or vinyl tile cutter
- Small notch trowel
- Putty knife
- Roller

INSTRUCTIONS BEFORE INSTALLATION:

1. Please ensure UV films are installed to glass where flooring will receive direct sunlight
2. The surface of the floor must be completely dried, cleaned and free of dirt, wax, paint and etc. before installation
3. Ensure that the floor is smooth without cracks
4. use only recommended adhesives

INSTRUCTIONS AFTER INSTALLATION:

1. Do not move heavy furniture over newly installed floor within 24 hours after installation
2. Do not wash the newly installed floor within 3 days after installation

General maintenance of Arbour Floor:

Dilute approximately 1 part white vinegar to 15 parts warm water for a normal daily/weekly wash down. For a deeper clean, something a bit stronger can be used. Eg. Bio Wash.

Bio Wash can be used as is for very stubborn dirt or diluted to wash periodically. (Instructions on bottle)

Please note that no bleaches should be used on the product such as "Handy Andy" as they may lead to damage of the product.

Dish washing liquid should not be used either as it tends to leave the floor with a very slippery gloss finish.