



# GO ROGUE

WITH RULE-DEFYING TIG PERFORMANCE.

# BREAK AWAY FROM CONVENTION WITH THE RULE-DEFYING ROGUE.

The days of entry-level mediocrity are over. With unconventional features, unprecedented performance, and an all-new industrial design, Rogue ushers in a new era of welding capability that will force you to rethink everything you expect from a portable GTAW machine at this price point. Are you ready to go rogue?

## ENTRY-LEVEL PERFORMANCE.

Rogue's next-level technology gives you precise, professional and consistent control for a smooth, stable performance every time. High-frequency TIG start keeps you from experiencing failure on ignition. Advanced TIG controls including gas pre-flow, start current, end current and gas post-flow allow full cycle control to match every application. Monitor and easily control ramp up time and down slope time. Pulse up to 500 Hz for perfect control of heat input.



## BASIC POWER.

Throw away your preconceptions about welders in this class = Rogue's power stacks up against machines twice its price. Power Fact Control (PFC) technology allows for a highly efficient and steady arc that is resistant to power fluctuations. With up to 25% duty cycle at 200 A, Rogue has the strength to crush jobs on thicker materials.

## UNDERWHELMING STRENGTH.

No other machine at this price point comes close to matching Miniarc Rogue's strength. Its robust and rigid fiberglass-molded housing is built to withstand impact after impact, in the shop or in the field. And like every ESAB machine, Miniarc Rogue comes with our industry-leading three-year warranty for unbeatable peace of mind. Sayonara, cheaply constructed welders.





## **LIMITED PORTABILITY.**

No other machine at this price point comes close to matching Rogue's strength. Its robust and rigid fiberglass-molded housing is built to withstand impact after impact, in the shop or in the field. Rogue is durable and weather resistant, with an IP23S rating for use in tough outdoor applications.

## **POOR USABILITY.**

Rogue's compact and lightweight design makes it easy to carry from job to job. It weighs in at just 21.2 lbs, and its sturdy handle and included shoulder strap make it more comfortable than ever before to go wherever you need to. Plus, its stable arc performance means you can use long extension cables to work in even the most remote locations without affecting weld quality. It is the definition of a portable workhorse.







**Package includes:** power source with 3 m (10 ft) mains cable and plug, shoulder strap, TIG torch SR-B 26 type with flexible neck and potentiometer 4m (13 ft), a set of wear parts including tungsten electrode, SMAW electrode holder 3 m (10 ft), work lead with clamp 3 m (10 ft), gas regulator, power adapter 115V/230 V.

SPECIFICATIONS	
Model	<b>Rogue ET 200iP PRO</b>
Primary Voltage 1ph	115/230 VAC ± 15%, 1ph, 50/60 Hz
Maximum Output	200 A
Rated KVA	7 kVA
Energy Save Mode	50 W
Open Circuit Voltage	78 V DC
MMA Welding Output	
@ 25% Duty Cycle	200 A / 28.0 V
@ 60% Duty Cycle	129 A / 25.2 V
@ 100% Duty Cycle	100 A / 24.0 V
TIG Welding Output	
@ 25% Duty Cycle	200 A / 18.0 V
@ 60% Duty Cycle	129 A / 15.2 V
@ 100% Duty Cycle	100 A / 14.0 V
Current Range	10 – 200 A
Operating Temperature	-10 to +40 °C (+14 to +104 °F)
Enclosure Class	IP23S
Certification Mark	ETL
Dimensions	403 x 153 x 264 mm (15.7 x 6 x 10.4 in.)
Weight	9.6 kg (21.2 lbs)

ORDERING INFORMATION	
Rogue ET 200iP PRO	0700500073

OPTIONS AND ACCESSORIES	
Description	Part Number
Shoulder strap	0700500086
Power adapter	W4014000
Foot pedal, 4.5 m (15 ft), 8 PIN	W4014450
Electrode Holder 200A and Lead Assembly, 4 m (13 ft), 50 mm Dinse	WS200E13
Tweco Ground Clamp w/Lead, 3 m (10 ft), 50 mm Dinse	WS200G10
GF250-50-580 Regulator Flow meter	0781-9411
TIG Torch SR-B 26 with Flexible Neck and Potentiometer 4 m (13 ft)	0700025557
TIG Torch SR-B 26 with Flexible Neck and Potentiometer 8 m (26 ft)	0700025591

Defy convention. Go rogue. Visit [esab.com/rogue](https://esab.com/rogue) to find a distributor near you.



ESAB / [esab.com](https://esab.com)

