



Spray Enamel

AP7000-11050/11051/11052/11053/11054/11055/11056/11057/11058/11059

AP7000-11060/11061/11062/11063/11064/11065/11066/11067/11068

January, 2000

Description

ALLPRO Spray Enamel is a high performance coating which provides extra hiding on most interior and exterior applications. With a properly prepared surface, this tough coating prevents corrosion. Its fast drying formula is non-toxic when dry. The high gloss finish provides easy care.

Prominent Features

- » Fast drying
- » Interior & exterior use
- » Prevents corrosion
- » Tough coating
- » Tamper-proof matching colored cap
- » Full length draw tube ensures maximum delivery per can
- » Internal heavy-disc mixer for faster, more thorough paint mixing

Uses

Excellent for wood, metal, furniture, wicker, shop, industrial and other uses.

Limitations

Galvanized surfaces should be primed prior to application with a galvanized primer.

Surface Preparation

Clean surface thoroughly, removing all dirt, grease, oil, soapy film, rust, moisture, etc. and cover adjacent areas to protect from spray mist.

Application

Use in well ventilated area. Shake can vigorously for one minute before spraying and occasionally while in use. Hold can 8 - 10 inches from surface to be sprayed. Spray at room temperatures between 70°F - 90°F (21 - 32°C). For best results, apply thin even coats – two thin coats are better than one heavy one. Recoat within 2 hours or after 48 hours. If nozzle clogs during use, turn spray button ¼ turn or remove and clean button slot. Do not stick objects into can opening.

Clean Up

Clean overspray immediately after use with paint thinner. For storage after use, clear nozzle immediately after use by holding can upside down, spraying 2-3 seconds or until paint no longer sprays out of can.

Environmental Concerns

Compliant with all U.S. VOC regulations for aerosol paint. Contains no methylene chloride or any ozone damaging fluorocarbons.

Spray Enamel

AP7000 – 11062

January, 2000

<u>Caution</u>	<u>Technical Information</u>	
<p>VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION.</p> <p>Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C).</p> <p>Notice: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.</p> <p>Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.</p> <p>Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory equipment protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing.</p> <p>First Aid: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.</p> <p style="text-align: center;">KEEP OUT OF REACH OF CHILDREN</p> <p style="text-align: center;">Manufactured For: ALLPRO® Corporation TAMPA, FL 33619</p> <p>Note: The information, ratings and opinions stated above pertain to the material currently offered and represent the results of tests and calculations believed to be reliable.</p>	<p>Packaging: aerosol – 10 oz. by wt. (283 g) Colors: 19 colors</p>	
	Chocolate Brown	Fire Engine Red
	Machinery Gray	Forest Green
	Antique White	Tangerine
	Chrome Aluminum	Gold
	Daisy Yellow	Navy
	Clear Acrylic	
	Red Oxide Primer	Gray Metal Primer
	Gloss Black	Gloss White
	Semi-Gloss Black	Semi-Gloss White
	Flat Black	Flat White
	<p>Weight Per Gallon: n.a. Specific Gravity: Varies by color. Approx. 0.75 Solids by Volume: n.a. % Solids by Weight: varies by color. Average ~19.5%, range of 11.8 - 30.6%. Viscosity: n.a. Spreading Rate: Approx. 12-18 sq. ft. per can @ 1 mil dry film thickness Shelf Life: 2 years Freeze Thaw: n.a. Dry Time – Dry-to-touch: 5 minutes Tack-free: 20 minutes Dry hard: 4 hours Flash Point: 1°F Odor: Strong odor Storage: Indoors. Do not expose to heat or store at temperatures above 120°F. Exposure to heat or prolonged exposure to sun may cause bursting. Do not puncture or incinerate container Vehicle: Vinyl Toluene Alkyd Copolymer Air Quality Data: Contains no methylene chloride or any ozone damaging fluorocarbons. VOCs varies by color. Average is 57.5%, range of 53.1 - 63.6%</p>	