







Equipmen

Operatory Room	p.69 - p.92
Imaging Room	p.93 - p.96
Hygiene & Mechanical Room	p.97 - p.103
Mini Laboratory	p.104 - p.106



Operatory Room

Dental Unit



i-XS4 Brushless **Micromotor**

This also softens the aggressive impact of the instruments to the patient before the operation

Torque up to **70Ncm** and speed from 100 \sim 40,000 rpm

For restorative, endodontic and implant surgery



Automatic Chip Air

Automatically emits air after stop & prevents retrograde contamination



5.7" Touch Screen with Highly **Personalized Setting**

7 programs can be set for each operation mode (Surgery, endodontic and restorative)

and for each operator (max. 3 operators)



ATLAXIS Headrest

Pneumatic headrest with orbital rotation (no levers or mechanical brakes)



Assistant's Table

Double arm with vertical adjustment



VENUS PLUS - L LED (3-Axis)

Flexibly delivers 3,000 to 50,000 Lux light with 5,000K color temperature

No-touch infrared sensor and hermetically sealed front screen for easy cleaning and maintenance

Peristaltic Pump

integrated to eliminate need for additional cart or modules







Automatic sanitization of suction system between one patient and another (ACVS)








Operatory Room





combines mechanical strength and stability, enables S200 chair to lift up to 190 kg



i-XR3 Brushless Micromotor

- Low noise level
- Increase patients comfort
- Speed: 100 -40,000 rpm
- Torque: 3.3 Ncm
- For restorative and prosthetic dentistry

Automatic Chip Air

Automatically emits air after stop & prevents retrograde contamination



Non-Optic

Keypad Control with 3 Digit Display



- Show instruments speed and Power Control - Integrated X-ray Viewer for I/O radiograph



UNIVERSAL

2-axis mechanical headrest



Optional ATLAXIS Pneumatic Headrest





VENUS PLUS (3-axis)

Brightness: 8,000- 50,000 Lux Color temperature: 4,900K

Each



SW-S200


Optional 1) VENUS PLUS-L (LED) 2) Ceiling Mount





Assistant's Module **Instrument Holder** Guide

(removable) for easy retrieving & placing back of suction cannula. Cannula terminals are removable and autoclavable)



Available Colors



Removable **Patient** Chair **Padding**





Distilled Water Container

Large Double Filter on the Cannula






Pressure Foot Control (Joystick activation)

controls chair position, chip air and chip water, motor speed







Dental Unit



i-XS3L Brushes Micromotor

- Low noise level
- Increase patients comfort
- Speed: 100 ~ 40,000 rpm
- Torque: 3.3 Ncm
- For restorative and pros-



UNIVERSAL

2-axis mechanical headrest



VENUS PLUS (3-axis)

- Brightness: 8,000 ~ 50,000 Lux
- Color temperature: 4.900K



Available Colors





Automatic Chip Air

Automatically emits air after stop & prevents retrograde







Keypad Control with LCD Display

- Show instruments speed and Power Control
- Integrated X-ray Viewer for I/O radiograph




Truly Versatile





Operatory Room

Dental Unit



Fully Adjustable Advanced Hydraulic System and Robust Cast Aluminum Back Rest

- Supports patients weighing up to 450 lbs (only < 300lbs for market leaders)







Cantilever Forward™ Design

Delivers an unsurpassed range of travel whether seated or standing



Electronic Rotation System with Foot Control Pedals

- Uniquely cradles the upper

body for exceptional comfort

- Chair to swivel up to 76 degrees















and security

High density foam for inport and long







- 3rd generation Kink Valve Technology provides exceptional reliable handpiece control. Thousands are in use worldwide









Equipment _____









Soft and silent chair movement with adjustable speed

+ Safety Auto System





Rotatable Spitton

with automatic tumbler filling and flushing (with optical sensor) for patient's convenience





bushes for greater positioning flexibility and high hygienic













Doctor table holding 6 instruments with electrostatic touch panel and 7' big size LCD



C8+ Dental Treatment Center

standard

German-made products of superior technology and quality

and Comfort

Headrest







foot switch C





SIROLUX F
Operating Lig

arna a a a a a a a a a a a a a a a a a a
SIROSONIC
Ultrasonic
Handpiece
Handbiece

C8+	Basic	Comfort	Lux	MM Lux
Item no.	SIR-BASIC	SIR-COMFORT	SIR-LUX	SIR-MULTI
Headrest & UPH	Flat & Standard	Flat & Standard	Flat & Standard	MultiMotion
Foot Switch	Standard	footswitch C+	footswitch C+	footswitch C+
Air Turbine Tubing	3	2	2	2
Electric Motor	No	Either One	Yes	Yes
SIROSONIC Scaler	No	Ellilei One	Yes	Yes
Cuspidor Type	Fix	Fix	Extended	Extended
Disinfection System	No	No	No	Yes
Syringe Assistant	3-Way Syringe	Sprayvit	Sprayvit	Sprayvit
Operating Light	SIROLUX E	SIROLUX E	SIROLUX E	LED View Operating Light



Equipment _____



Operatory Room

Dental Stool



The ONLY Chair That Solves Your Back, Shoulder, Lower Limb And Hips Problems!




Conventional Problematic Seat

- Shoulder tension
- Lower back pain
- Knee and hip problem
- Pressure on buttock and thigh muscle
- Early retirement
- **Trouble-Free** Salli Seat
- Re-establish vertebrae position
- Improve blood circulation
- Reduce lower back pain - Ease shoulder tension
- Reduce knee and hip problem
- Reduce sitting fatigue
- Improve working efficiency

Places weight on bones, not the sensitive tissue







pressure safety on the ischial bones, minimal pressure on sensi-tive tissue when moving around and leaning over



Available Colors



Chair Parts

Each

Chrome Gas Spring

Packing Item no.



SAL-CHIN-

salli **SWAY**

	User neight (cm)				
	<165 165-185 >185				
Spring	Short	Medium	Long		



2	User height (cm)		
	<160	>180	
Spring	Short	Medium	Long



Elbow Rest (SAL-ELBOWREST)

- · Adjustable height for
- · Curve length: 63cm
- Width: 7cm



All Around (SAL-ALLAROUND)

- 360° rotating elbow support
- Support arch: length 61cm, width: 8.5cm
- · Requires a large base



Foot Supporting Ring (SAL-FOOTRING)

- · For workstation with changing height re-quirements
- · Diameter 46cm



Stretching Support (SAL-SSUPPORT)

- Backrest for momentary stretching during long working hours
 • Only available on Chin, requires a large base







Operatory Room

Scaling and Prophy Equipment





Air-Flow Master Piezon®

Combines AIR-FLOW® and Piezon® technologies in one for professional removal of calculus & sub-gingival biofilm

Restore biocompatibility of implant surfaces, removal of biofilm

Journal of Biomedical Materials Research Part B (July 2008)

Packing	Item no.
Each	EMS-FT-200








The new perio nozzle and the new Air-Flow Perio Powder combine to deliver greater efficacy and much more patient comfort









More gentle action and intelligent feedback control compared to conventional hand instrumentation



Ultrafine grain (grain size: 25µm) specially developed for use in deep periodontal





Air-Flow® S2

Combines AIR-FLOW® and Piezon® technologies in one for professional removal of calculus & stain



Controlled Piezon oscillations pattern

ranging from 27,500 to 32,000/s for maximum cleaning efficiency Efficient and patient



Powerful air/ powder jet for complete removal of plaque and



3 integrated self-cleaning filters prevent clogging of powder, air and water lines

Automatically purges and cleans itself each time it is switched off





Contents:

2 x Air-Flow Handpieces

1 x Piezon Handpiece 3 x Scaling Tips (A, P, PS)

1 x Steribox

12cm 1 x Cleaning Instrument 1 x Spare "o" Rings

x Air-Flow Powder

Packing Item no. Each EMS-FT-169



To avoid scratching of the tooth surface during prophylaxis.. Turn the airflow control up

and water control down



To avoid tooth staining after prophylaxis... avoid smoking & other colored beverages 2-3 hours after prophylaxis



- To increase Adherence in restoration... ☑ Cleaning enamel surface before etching
- ☑ Cleaning fissures before applying sealant





Equipment _____

Operatory Room

Scaling and Prophy Equipment



K Varios Combi Pro

ULTRASONIC

POWDER

i7iezo engine°

- The iPiezo engine easily and comfortably removes both soft and hard calculus by powering the tip according to the applied pressure
- The ultrasonic engine features state-of-the-art software to maximize performance while minimizing patient discomfort

■ Feedback Function **■** Auto Tuning Function - Powder Therapy to Clean Supragingival Areas Efficiently and Quickly





And Nozzle



■ A Wide Choice Of Tips

And Accuracy Competitor A1



■ Slim Handpiece Ensures Safety

NSK Varios 2 Lux

■ Fast And Effective Therapy





■ Varios Combi Pro Basic Set

Dimension (W x D x H): 225mm x 290mm x 162mm

NSK-

Y1003042

Content




- 1 x PROPHY-Handpiece with 60° Nozzle

- 1 x PROPHY-Hose
- 1 x PROPHY-CHAMBER
- FLASHpearl (5pcs x 15g sachets)
- 1 x Maintenance Kit
- 1 x VA2LUX-Handpiece
- 1 x VA2LUX-Hose
- 3 x Scaling Tips
- 1 x Sterilization Case
- 1 x Irrigation Bottle (400mL)
- 1 x Foot Control



NSK-Y1002843

Item no.





Henry Schein Hong Kong Ltd. Tel: (852) 2541-2290 Fax: (852) 2882-4383

- 1 x Perio-Mate Nozzle Tip

- 1 x Perio-Mate Nozzle Tip Remover - 1 x Perio-Mate Powder



Operatory Room

Prophylaxis Equipment










Effective removal of Biofilm in deep pockets (up to 10mm)



Air-Flow Master

Perfect for supra-gingival and sub-gingival prophylaxis









Item no.

Biofilm on root surface is removed following treatment combine to deliver greater efficacy and much more patient comfort

More gentle action and intelligent feedback control compared to conventional hand instrumentation


Content

Air-Flow[®] Handy 3.0 Perio

For Sub- & Supra-gingival Treatments







AIR-FLOW" PLUS





Safe and conser-

Type



Biofilm on root surface is removed following treatment with the Original Air-Flow® Method



Photos by Prof. Dr. A. Mombelli University of Geneva, Switzerland







- 2 Optimized Nozzle Design Based On Fluid Analysis Ensures Flawless Powder Flow In The Pocket
- 3 Smooth 360-Degree Rotation For Safe And Accurate Operation
- Powder Control Ring

Perio-Mate BioFilm Eraser Used in the Treatment of Periodontal Pockets & Peri-Implantitis







Operatory Room

Prophylaxis Equipment



Air-Flow® S1 Classic Prophyaxis Unit







Removes dental plaque, soft deposits and surface stains from pits, grooves, interproximal spaces and smooth surfaces of the teeth

Air-Flow® handy 2+ Outstanding Designer Prophylaxis Handpiece











- Ergo-Comfort Design: lightweight, compact design and well-considered weight balance enable easy handling
- Smooth, Easy 360° Swivel: twin joints rotate smoothly 360° for easy operability, responding flexibly to minute
- Simple One-Touch Connection: one-touch attachment directly to NSK couplings and major brands' air turbine handpiece couplings
- Easy Detachable Nozzles With $60^{\circ}\,\text{And}\,80^{\circ}\,\text{Tips}$




















Piezon® Master 700 Multi-functional Piezon® Unit





Intelligent NO PAIN TECHNOLOGY with automatic feedback control minimizes damage to the tooth substance







Equipment _____

Operatory Room

Piezon Equipment



miniMaster®

Stand-alone Multi-purpose Piezon Unit with Own Liquid Supply

Product	Packing	Item no.
miniMaster LED	Each	EMS-FT-201
miniMaster	Each	EMS-FT-155



Optimum

Clinical

Versatility

NSK Varios 970 i?iezo engine®

■ Features

- Easily changeable solution bottles
- Designed for easy on-site maintenance
- Eye-friendly icons for Endo, Perio and General modes
- Clear display for 10 power and irrigation flow settings
- Simple to use memory function to store individual settings
- Touch control irrigation status selection for dry, bottled water and external water
- Dual water adjustment controls for bottled or external water



■ Large LED **Display**



■ Auto Cleaning Mode



■ Sterilization Case



■ 360° Foot Control

Dimension (mm)	(W)160 x (D)270 x (H)190 (mm) (include bottle)
Power Supply	AC 230V 50/60 Hz
Frequency	28-32 KHz
Max. Ouput	11 W (G mode)
Unit Weight	2.1 kg
Bottle Volume	400 mL (x 2 bottles)

■ Varios 970 Complete Sets

Туре	Model no.	Content	(NSK-)
Optic	VA970 LUX (230V)	- 1 x Control Unit - 1 x Handpiece (Optic: VA2-LUX-HP / Non-Optic: VA2-HP)	Y1001168
Non- Optic	VA970 (230V)	- 1 x Handpiece Cord - 2 x Irrigation Bottles - 3 x Scaling Tips (G4, G6, G8) - 1 x Sterilization Case - 1 X Foot Control (FC-70) - 1 AC Power Cord - 3 x Tip Wrench with Torque Limiter	Y1001175

NSK Varios 570 i?iezo engine®



Dimension (mm)	(W)160 x (D)135 x (H)65 (mm)
Power Supply	AC 100V-240V 50/60 Hz
Frequency	28-32 KHz
Max. Ouput	11 W (G mode)
Unit Weight	0.43 kg
Unit Weight	0.43 kg



■ NSK's new technology, iPiezo engine® ensures stable frequency by automatically adjusting to the optimum frequency of tips for an excellent, tactile feel




■ NSK LED delivers natural daylight-quality

■ Varios 570 Complete Sets

Туре	Model no.	Content	Item no. (NSK-)
Optic	VA570 LUX (230V)	- 1 x Control Unit with Handpiece Cord - 1 x Handpiece (Optic: VA2-LUX-HP / Non-Optic: VA2-HP) - 1 x Water Supply Connector - 3 x Scaling Tips (G4, G6, G8)	Y1001273
Non-Optic	VA570 (230V)	- 3 x Scaling Tips (G4, G6, G8) - 1 x Tip Wrench with Torque Limiter - 1 x AC Adaptor - 1 x Water Filter Set - 1 X Foot Control (FC-70)	Y1001269





NSK Varios 370 i?iezo engine®









NSK		
■ Scaling	Model no.	Item no.
a 9 oi	G1	Z217 101
0 0	G4	Z217 104
	G6	Z217 106

■ Perio	Model no.	Item no.
• •	P20	Z217 420
	P21R	Z217 422
. 6	P21L	Z217 421
	P25R	Z217 424
. 9	P25L	Z217 425

■ Spare Parts	Model no.	Item no.
with Vorios2Lux	VA2-LUX-HP	E351050
MSW Virios2	VA2-HP	E350050
	VA970LUX -SC	E351055
	VA970-SC	E350055
■ Perio-Control	Model no.	Item no.
1) (36 #	Kit Perio-Control	Y1002606





Operatory Room

Curing Light


















It is important to choose a right curing light!

"More than 37% of composite restoration are clinically insufficiently cured"

Inside Dentistry, March 2012, Vol.8, Issue 3

Product	Packing	Item no.
VALO Cordless	Each	UL-5941
VALO	Each	UL-5919

Boardband LED with 4 LED chips emitting light of a wide range of wavelength to cure everything



Easy access to all area in a mouth No light guide, slim wand (only 12mm) and 5° head angle






Ensure successful curing

Highly focused, collimated beam with only 40% power lost in 10mm distance





Superior output enables 3s curing time

Extremely durable Made from a single piece of high-grade aircraft aluminum



Curing Light Accessories Various curing tips for different clinical applications Packing 2 lens/pack **PointCure TransLume** Lens Lens UL-5937 UL-5934 Endo Guide **ProxiCure Ball Lens** Tip

UL-5938

Elipar[™] S10

LED Curing Light

3M ESPE


Elipar<u>™</u> **LED Curing Light**







Optimized to deliver a more focused light output



UL-5936

Easy charging

Uniform Intensity Distribution

- Maintain high intensity (44%) even at

- a distance of 7 mm - 10mm light guide cover large curing surface
- Timer offers 5, 10, 15, 20, 120s and tack-cure mode
- High-performance Li-ion battery (60mins cure)
- Built-in Li-ion **Power Supply** Battery Wavelength Range 430-480 nm **Light Intensity** 1,200 mW/cm² Charging Time (Empty Battery) 11 W (G mode) Total Exposure Time 2.1 kg Diameter 28 mm Length 27 mm 180 g
- One-piece stainless steel casing is extraordinarily robust and easy to disinfect
- Unique, ergonomic V-shape provides a comfortable grip from any angle
- Simple two-button operation with one cure mode for all indications



Long-Life, high-performance Li-ion battery technology

Wavelength 430-480 nm Range Diameter (HxWxD) 170 x 95 x 50mm Time to discharge 90 minutes Weight 250 g (with battery)



3M-76954

Each



Henry Schein Hong Kong Ltd.

Tel: (852) 2541-2290 Fax: (852) 2882-4383







BA Optima 10 LED Curing Light

- Light & Compact (2.5 x 25.2cm; 178g)
- Light intensity: 1,000mw/cm²
- 3 curing modes: Full power, Progressive, Pulse
- Digital display and simple use
- 5 metalic colors available: black, blue, red, green & grey
- Wave-length: 420 ~ 480nm











Packing

Item no.





Item no.


Each





Operatory Room

Dental Digital Camera





Shooting Modes



Standard Mode For standard intraoral photography.

Surgery Mode



For intraoral photography from a dis-

Mirror Mode
• For intraoral photography using a mirror.
• The image taken

can be reversed



Low-glare Mode

For photographing details of anterior teeth, working models and indirect restorations.



Tele-macro Mode

For photographing anterior teeth, indirect restorations and working models in higher magnification.

* Attach provided Close-up lens when taking pictures in this mode



Isolate shade Mode

You can isolate the shade for optimal shade matching.



Combine the conventional ring flash and side flash into one sleek, compact design

 Sleek, compact body design, Only 465g (Accessories not included)



- Easy to hold One hand holds, one hand touches
- Anti-shake capabilities





Operatory Room

Surgical Equipment



Luxator® LX Mechanical Periotome

Advantages



- Cutting Sharpey's fibers in a patient friendly way
- Durable titanium coated tip



- Press firmly and follow the surface of the root
- Self-directing Periotome Tip follows the root surface to cut the periodontal fibers



Great access to molar, lingual or distal area

■ Luxator LX Mechanical **Periotome Starter Kit**

Content	Item no.
- 1 x Handpiece - 2 x Periotome Tips Short (2mm & 3mm) - 2 x Periotome Tips Long (2mm & 3mm) - Tip Holder & Plunger	DIR- 5064-43

■ Luxator LX Mechanical Periotome with...

(DIR-)	Short Tip	Long Tip
Size	Item no.	Item no.
3mm	5064-41	5064-42
2mm	5064-44	5064-45



NSK

iSD900 Cordless Prostheodontic Screwdriver

Advantages & Features

- Torque Calibration System (TCS) for prosthodontic screw fixing procedures
- Help to save time and allow precise risk-free lightening of screws

Torque	10-40Ncm in 1 or 5 Ncm increments	
Speed	15, 20, 25 min ⁻¹	
Programs	148 g (iSD900 Motor + iSD-HP)	
Charging Time	Around 90 min*	
Continuous Operation Time Max 72 min*		
* these may change according to the usage environment		

- Guarantee precise torque control due to the unique NSK TCS which is extremely easy to use

Model no.	Packing	Item no.
iSD900 (230V)	 1 x iSD900 Motor 1 x iSD-HP 1 x Quick Charger for iSD900 1 x Torque Calibrator 1 x On/Off Switch Lever 	NSK- Y1001358

NSK Surgic XT Plus

- Wide speed range of 200-40,000 min⁻¹
- Powerful torque: 5-50 Ncm
- High power 210W
- Low noise, low vibration with minimal heat durability
- High torque accuracy

Model	Packing	Item no.
Surgic XT Plus Non-Optic (230V)	Each	NSK-Y1001-207



Surgic XT Plus

Advanced Handpiece Calibration (AHC)

Automatically calibrates micromotor and handpiece to the rotational resistance of each individual handpiece prior to operation. Offers high torque accuracy and maximum safety



Simple, intuitive control panel

The display shows all settings and status at the same time



8 programs can be set individually

You can independently set speed, torque, cool-ant flow, gear ration and rotation direction







Gear Ratio 20:1 Reduction Body Stainless Steel Body Torque Max. 80 Ncm Max. 2.000 min-1 Speed External and Internal Cooling (Kirschner and Meyer) Others - Double Sealing System

3 User-Friendly Foot Control Control Program Control Reverse







Operatory Room

- Excellent durability

Surgical Equipment





design

Surgic Pro+

■ Surgic Pro+ Complete Set with X-DSG20L

Model no.	Content	Item no.
Surgic Pro+ OPT-D (230V)	 1 x Control Unit with Data Storage Facility 1 x LED Micromotor (SGL70M) 1 x Foot Control (FC-78) 1 x Optic Handpiece (20:1 Reduction) (X-DSG20L) 5pcs x Irrigation Tubes Other Accessories 	NSK- Y1002096

230V 50/60 Hz	Dimensions	268 x 220 x 100 (mm)	
75 mL/min	·		
8 Programs/	USB I/F	1 port (Surgic Pro ⁺ Only)	
Implant systems	Built in Memory	100 min (Surgic Pro+ Only)	
	75 mL/min 8 Programs/	75 mL/min (W x D x H) 8 Programs/ USB I/F	

OPTIONAL

Link Set



Model no.	Packing	Item no.
VarioSurg3	Set	NSK- Y1002729

Handle Set (Optional for Surgic Pro)

Easy to attach foot control handle

Hanger can easily be moved with th foot control

> Model no. Handle Set

Πŧ		
	Packing	Item no.
	Each	NSK- Z1027001

VarioSurg3	Compl	ete	Set
with Foot C	ontrol		

Model no.	Packing	Item no.
VarioSurg3 (230V) Non FT	Same as VarioSurg3 Complete Set without Foot Control	NSK- Y1002248

NSK VarioSurg3

■ VarioSurg3 Complete Set

	0			
Model no.			Content	Item no.
VarioSurg3 (230V)	- 1 x F - 1 x B (H-SC	ontrol Unit oot Control (FC-78) asic H-S Kit G1, SG3, SG5, SG6D, O, SG11 and Tip Holder	- 1 x LED Handpiece with 2m Cord - 1 x Sterilization Cassette - 1 x Handpiece Stand - 5pcs x Irrigation Tubes) - Other Accessories	NSK- Y1002726

Frequency	cy 28-32 kHz Programs	SURG x 5, ENDO x 2,	
Power Supply	230V 50/60 Hz	Programs	PERIO x 2
Irrigation Flow Rate	10~75 mL/min	Dimensions (W x D x H)	265 x 220 x 100 mm










Operatory Room

Surgical Equipment





Touch Screen

- Easy to clean
- Irrigation and power rate chosen by the touch of a finger



Sterile Protection Foils

- Invisible shields
- No dirt, scratches or fingerprints and glass keyboard



Piezosurgery[®] Insert Kits

Item	Packing	Item no.
Basic Kit	Each	MC-01520001
Sinus Lift Kit		MC-01520002




Piezon Master Surgery® Good For Sinus Lift & Extraction Of Autogenous Bone





PerFect® TCS II







Operatory Room

Endodontic Equipment




iPexII (Advanced Apex Locator)



"Auto-detects the apex accurately in any condition, dry or wet"

- · High-precision root canal measurement generated by using SmartLogic
- · Multi-frequency measuring technology







- 6000			
For 1.5VAAA (LR03 or R03 Batteries			
Approx. 60 hours			
60 x 86 x 60 (mm)			
Unit 76g (without batteries)			

■ iPexII Complete Set

- 1 x Control Unit
- 1 x iPexII Probe (1.8m) 3pcs x iPexII File Clips
- 3pcs x Lip Hooks
- 1 x iPexII Tester 3pcs x AAA Manganese Dry Cell Batteries

Packing	Item no.
Set	NSK-Y1002208



Root Apex Locator

- Guaranteed accuracy in any root canal conditions (dry bleeding, wet, saline, EDTA, NaOCI, Chlorhexidine and etc.)

- Ultra-light weight and compact design -Exceptional portability





	4.5V DC (1.5V	Content	Item no.
Rated Voltage	Alkaline Battery AAA x 3)	- 1 x Rootor - 1 x Probe Cord	
Dimension (W x D x H)	7 x 2.5 x 10 (cm)	- 1 x Probe Cord - 5 x Lip Clips - 1 x File Holder A - 2 x File Holders B - 1 x USB Cable - 1 Driver & Software CD	META-EM -ROOTOR
Continuous Operation Time	62 Hours (at 1,250mAh Battery x 3)		

E & Q Obturation System



- Slim design provides a nice feeling of grip and easy handling
- Simple operation enables efficient workflow
- Thermo-plasticized filling makes treatment speedy, accurate and predictable
- Excellent treatment outcome event in anatomically complicated canals

	Pen	Gun
Charger Output	DC 9V, 1.8A	
Charging Time	Within 3 Hours	
Heating Time	1 Second 2 Minutes	
Operating Time	Continuous for 1.5 Hours	
Battery	Li-ion (3.8V, 2,400mA)	

3-Dimensional Filling Technique








Equipment _____



Endodontic Equipment







✓ Portable Endodontic Rotary System





Model no.	Content	Item no.
ENDO- MATE DT (230V)	- Control Unit - Motor and Cord - AC Adaptor - Handpiece Stand - MPAS-F20R Head (20:1)	NSK- Y141121





Endo-Mate AT

✓ Economical yet Evolved Version of the Legendary DT

- Same endo function as ENDO-MATE DT
- Featuring new FX Head
- Compatible with DT Heads as optional
- Operative with AC Adaptor only
- No rechargeable battery, no recharging function

Model no.	Content	Item no.
ENDO-MATE AT (230V)	- Control Unit - Handpiece Stand - Motor and Cord - iFX75 Head (16:1) - AC Adaptor	NSK-Y1002190









Scaler & Curette

Makes routines maintenance sharpening fast, easy and consistent

Item no.

HF-SDKKIT

For Sickle & Universal

Curette

Sharpening

Movement of Stone

For Gracey Curette

Sharpener


Hu-Friedy

FIRST BECAUSE WE LAST.

sidekick

Terminal Shank Guide









Imaging Room

X-Ray



Carestream CS 81003D

Specially Designed For GP's Daily Practice

100+ Years Industry Experience / Multi-Function 2D, Cone Beam CT & CAD/CAM Scanning Unit




4 Fields of View Programs (4x4cm to 8x9cm



Endodontic Applications (Endo HD program)

- Pre-surgical assessment
- Uncover unusual canal anatomy and morphology
- Discover presence of disease
- Implant planning





CAD/CAM Compatible



Comprehensive 3D Imaging Software

- Customizable for beginner or advanced users
- Sophisticated implant planning with implant library
- Compatible with other imaging software (NobelGuide™, Simplant® and SureSmile)




CS 8100 Digital Panoramic System (KD-CS8100)

Supreme quality images with just 1 click CMOS sensor, vibration-free motion system and artifact-free image filters ensure supreme quality images with just one click



Unique 3D-like technology

"2D+" technology": create 3D-like visuals to explore buccolingual impaction, apical lesion and root relationship to ID nerve





✓ Ultra-Compact Design ✓ Sleek & Simple √ High-Quality Images
√ Quiet & Fast

Optimized Positioning

Precise and effortless patient positioning with faceto-face open design



More Forgiving to Patient Positioning

Enhanced Focal Trough

provides greater tolerance for imperfect positioning to reduce retakes



Simple & Quick Operation Intuitive user interface with preset programs and step-by-step instructions













DENTAL Experience



CS9000 & CS9300 **3D Imaging Systems**

✓ A Low-Dose, 3-In-1 Designed For Both ENT And Dental Imaging

3-In-1 Solution **Cone Beam CT (CBCT)**

Optional One-Shot Cephalometric

Intuitive, easy-to-use imaging software for easy case review, sharing and planning



Streamlined user interface, preset programs and face-to-face positioning makes exams faster and more precise than ever





10 cm x 10 cm

3 simple steps to a 3D model





Fields of View

CS 9000 3D System



5 cm x 3.75 cm 7.5 cm x 3.75 cm Extended Mode

CS 9300 Select



Space Requirement $(W \times D \times H)$

For CS9000, CS9000 3D & CS9300

1,500 mm x 2,000 mm x 2,400 mm

For CS9000C, CS9000C 3D & CS9300 with Ceph


2,230 mm x 2,000 mm x 2,400 mm

CS 8100SC

- **☑** Scanning in record time: faster ceph scanning in the world
- **☑** Exclusive automatic tracing software: full tracing within 90 seconds
- **☑** CS Adapt module:

for impressive image clarity and customizable look and feel

- **☑** Ultra-compact unit: fits any practice
- **☑** Versatile programs and image formats (26 x 24cm, 18 x 24cm and 18 x 18cm



- CS Adapt module delivers impressive image clarity and even allows you to customize the look and feel of your images

The Fastest Scanning Cephalometric System In The World

- Scan an 18 x 24 cm image in as little as three seconds when using the auick mode

Exclusive Automatic Tracing


- Tracings in just 90 seconds
- The software covers the most common analysis needs, such as Ricketts, McNamara, Steiner and Tweed

Dual-Sensor Systems

- Two sensors are better than one
- One for panoramic and cephalometric
- No need to change the sensor between exam inations, there's little need for manipulation and less risk of damage to the unit

	CS 8100SC		
Tube Voltage	60 - 90 kV		
Tube Current	2 - 15 mA		
Frequency	140 kHz		
Minimum Required Space	With ceph (L x D x H) 2,000 x 1,400 x 2,400 (mm)		







Imaging Room





cs2100 & cs2200 **IntraOral X-Ray System**

	CS2100	CS2200
X-Ray Generator	Very high frequency - DC (300kHz)	Very high frequency - DC (300kHz)
Tube Voltage	60 kV	60 kV, 70 kV
Tube Current	7mA	7mA
Tube Focal Spot	0.7 mm IEC	0.7 mm IEC
Focal Spot/Skin Distance	200 mm (8")	200 mm (8")

cs7600 & cs7200







	CS7600	CS7200
Image Plate Scanning Resolution	Super High Resolution: 18 lp/mm High Resolution: 14 lp/mm High Speed: 8 lp/mm	True Resolution: 17 lp/mm
Plate Size	Size: 0, 1, 2, 3 & 4	Size: 0, 1, 2
Display	7.5cm Color LCD Display	*
Unit Dimensions	266 (H) x 237 (W) x 259 (D) mm	120 (H) x 270 (W) x 300 (D) mm
Weight	6 kg	3.5 kg
Scan & Go	✓	×
Connectivity	Ethernet	USB

RVG Series

Digital IntraOral Imaging System









	CS5100	CS5200	CS6100	CS6200	CS6500
Connectivity	USB2	USB2	USB2	USB2	Wireless
True Resolution	14 lp/mm	16 lp/mm	>20 lp/mm	>24 lp/mm	>20 lp/mm
Sensor Size	1-2	1-2	0-1-2	1-2	0-1-2
iPad Aquisition	×	×	*	×	✓
Sensor Water- proofness	✓	✓	✓	✓	✓





Precise

CAD/CAM

Equipment




cs3500

2D/3D Intraoral Scanner

		Portable
	CS3500	Portable
Accuracy	30μm (average precision)	
Illumination	LED: Amber, Blue, Green	Fle
Field of View	16 x 12 mm with Normal Tip 12 x 9 mm with Additional Smaller	Tip
Depth of Field	-2 to +13 mm within 45 Degree Ar	igle

CS Model for Orthodontics









USB cable

Flexible



Autoclavable tips









Comfort collar Split screen viewing



Zfx provides dentists and dental laboratories a high end CAD/CAM solution for the entire dental process chain: From intraoral and desktop scanners via digital impressions and CAD software to complete milling solution

Abutments





Inlays & Onlays



Powder-free



IMPLANT MANUFACTURER	IMPLANT SYSTEMS			
CAMLOG	Screw Line®	VARIO SR®		
DENTSPLY IMPLANTS (ASTRATECH)	OsseoSpeed®	UniAbutment®		
DENTSPLY IMPLANTS	Multi- Purpose®	Frialit-Xive®		
NOBEL BIOCARE	Active®	Brånemark®	Multi-unit®	Replace®

Crowns &

Bridges

IMPLANT MANUFACTURER	IMPLANT SYSTEMS			
OSSTEM	GS & TS System®			
STRAUMANN INSTITUT	Bone Level®	Mutli-Base®	SynOcta®	
ZIMMER	Tapered Screw Vent®	Shoulder Abutment®	SwissPlus®	Tapered Abutment®
BioHorizon	Taper Internal (Excluded 3.0)			





Hygiene & Mechanical Room

Handpiece Maintanence Unit



iCare



■ Dual Standard Ports + **Dual Rotation Ports** Model no. Packing Item no. iCare C2 Type(230V) NSK-Y1002787

■ Single Standard Ports + **Triple Rotation Ports**



Model no.	Packing	item no.
iCare C3 Type(230V)	Set	NSK-Y1002788



Preset Proper Solution Volume Based On Handpiece Type

The proper solution volume is preset based on high speed and low speed handpieces, ensuring precise and thorough lubrication at the touch of



Low- & High-Speed Handpieces

The NSK rotation system guarantees optimum oil delivery to the internal com-ponents of all low-speed handpieces

iCare meticulously cleans the components of high-speed handpieces











- Purging Select Mode
- Chuck Cleaning Function
- B Easy To Clean
- Solution Tank
- **5** HP Head Filter Prevents Mist Leaks (Optional)

Power Supply	AC 100-240V, 50/60Hz
Air Pressure	0.5 - 0.6 MPa (5.0 - 6.0 kgf/cm²)
Weight	6.5 kg (C2 type/C3 type)
Dimension (mm)	(W)280 x (D)240 x (H)350
Solution Tank Capacity	1,200 mL


Contents

- iCare unit - Power cord
- Mist filter set Air tube
- Oil absorber sheet
- Maintenance oil for iCare (1L)
- Chuck Cleaning Nozzle



iCare Adaptors / NSK

Model no.	Usage	Item no.
PTL Adaptor	For NSK High Speed Handpieces for PTL-CL-LED Coupling	NSK-Z257010
KV Adaptor	For KaVo® High Speed Handpiece for MULTIflex® LUX Coupling	NSK-Z257020
SR Adaptor	For Sirona® High Speed Handpiece for Quick Coupling	NSK-Z257023
WH Adaptor	For W&H® High Speed Handpiece for Roto Quick Coupling	NSK-Z257021
F-Type Adaptor	For ENDO-MATE TC2, DT/ TASKAL Wizard Heads	NSK-Z280042







Hygiene & Mechanical Room

Handpiece Maintanence Unit



TTcare 100+ Lubrication Unit

Easy to Use • Done in a Simple Way

■ Benefits & Features

1) Exclusive Chuck Care System

Place chuck into



Simply disassemble the

front door for further

cleaning


2 Press program button



3 Clean and care handpiece's chuck









4) Easy Spray Insert and replace spray can easily





Dimension (W x D x H) (mm) Sound Level < 60 (65) dB (A) Air Consumption 40 NL/min Compressed Air Quality 0.1 mg/m³	
Air Consump- 40 NL/min Compressed max.	
Compressed max.	
Compressed	
Air Quality (Residual oil content)	

Model no.	Packing	Item no.
TTcare	- 2 x High-Speed Ports	TTB-
100+	- 1 x E-Type Adaptor	08090012TB1



DAC Universal Fully Automatic Handpiece Maintenance Unit

2) Simply Disassemble 3) Stay Clean Easily

■ Why DAC Universal?



1 DAC Universal gives you a healthy and safe clinic environment

The viruses and bacteria, such as HIV virus, Hep C virus, Hep B virus and Tuberculosis can hide inside your handpiece through blood, saliva and secreations

3 DAC Universal cleans and sterilizes not only external surfaces but also internal channels of handpieces





2 DAC Universal also keeps longer life of your expensive handpieces





Certifications:

- ISO 15883: 5 Annex J European standard EN 13060 for class S small sterilizers
- HKSAR Exemption Cert.

Packing Item no. BA-6258342 Each

Accessories



Henry Schein Hong Kong Ltd. Tel: (852) 2541-2290 Fax: (852) 2882-4383





98







M3 UltraFast® **Automatic Sterilizer**



Sterilize Unwrapped Instruments in only 6 minutes & Pouched Instruments in just over 10 minutes

Model no.	М3
Item no.	MM-M3-002
No. of Trays	1
Overall Dimension	W559 x H190 x D610 (mm)
Dimension of Chamber	W193 x H41 x D307 (mm)
Volume of	1.8L




Midmark UltraClave® **Automatic Sterilizers**



4 Pre-programmed sterilizing cycles

+ 2 Custom programs



Model no.	M9	M11
Item no.	MM-M9	MM-M11-021
No. of Trays	4	4
Overall Dimension	W389 x H454 x D540 (mm)	W452 x H533 x D452 (mm)
Dimension of Chamber	229Ø x D381	280Ø x D457
Volume of Chamber	13.4L	24.6L

Midmark Speed-Clean

22L

/ Midmark

Volume of Chamber

000000



- Ultra Cleave Steam sterilizers for autoclave
- Dilute 2 oz. of Speed-Clean to 32 oz. water

Packing	Item no.
16 oz./ bottle	MM-002-0396-05



Hygiene & Mechanical Room





AUTOMATIC

CLASS B

Mechanical Kwiklave

Fully Automatic Kwiklave One Touch Sterilization Closed Door System

Elare 11D Class B Built-In Steam Generator





- Semi-automatic (automatic shut off)
- Drying stage
- Double safety locking device
- Complies with the highest international standards

	Tuttnauer	A 3 3 3 5
1		3 000 E
(2)		
(100 mm)		
Charles		

- One touch button
- Fast cycle, 9 minutes (unwrapped cycle time)
- Fully automatic autoclaves
- Reduces total cycle time by 50%
- Optional printer
- High efficiency air pump circulates hot air during the dry cycle for fast drying

Model no.	2340EKA	2540EKA
Item no.	TUTT-2340EKA	TUTT-2540EKA
No. of Trays	3	4
Overall Dimension	W508 x H362 x D550 (mm)	
Dimension of Chamber	23Ø x D47	
Volume of	19L	23L



- High speed Class B performance with powerful built-in steam generator
- Advanced control system with multi-color
- Download cycle data your USB memory device
- Self-locking door with double safety locking mechanisam

Model no.	Elara11
Item no.	TUTT-Elara11
No. of Trays	5
Overall Dimension	W530 x H444 x D645 (mm)
Dimension of Chamber	28Ø x D43
Volume of Chamber	28L

Model no. 2340MK 2540MK TUTT-2340MK TUTT-2540MK Item no. No. of Trays 3 W508 x H362 x D550 (mm) 23Ø x D47 19L 23L

coltène /// whaledent[®]

<u>BioSonic</u> **Ultrasonic Cleaning System**



Overall Dimension (L x W x H) (mm)

Tank Dimension (L x W x H) (mm)

Tank Capacity (L)

Use Capacity (L)

273 x 219

x 350

197 x 146

3.2L

2.0L

419 x 249

x 350

286 x 143

4.8L

3.8L













14.4L

11.4L

Hygiene & Mechanical Room

Compressor & Suction System




Germany

Power Tower Silence (PTS) Wet (VS) and/Or Dry (V) Suction Systems

- **☑** Limited space requirement
- ☑ Quiet (53-56 dB(A)) depends on different model
- \square Low in maintenance and easy
- **☑** Combining compressed air & suction in a single unit

PTS 120





PTS 200

Model no.	PTS200
Item no.	DURR-PTS200
Power Supply	400 V
Overall Dimension (H x W x D) (cm)	200 x 64 x 61
Treatment Room	3 - 6
Simultaneous Operators	3 - 4







Hygiene & Mechanical Room

Compressor & Suction System



Tornado Compressors Designed For Long-Lasting Continuous Operation



Tornado 2

Tornado 2 with Dryer



reddot design award winner 2011











Item no.	DURR-5180-03	DURR-5182-03	DURR-5280-03	DURR-5282-03
Overall Dimension (H x W x D) (mm)	660 x 480 x 370	660 x 490 x 430	640 x 480 x 370	640 x 490 x 430
Treatment Chairs	2		3	
Simultaneous Operators	1		2	

Patented Membrane-drying unit





Central intake filter prevents dirt particles entering the compressor unit





Nanotechnology antibacterial inner tank coating ensures the highest level of safety and protects against corrosion

Optional



Automatic condense drain Automatic draining of water in the tank, maximise the tank space.

Manual draining is no longer needed.

MIDMARK

ClassSeries™ Wet-Ring Single Pump Vacuums

- Powerful: 1.25 HP (CV3), 2 HP (CV5)
- High output, proven performance
- Water recycling by-pass
- Stainless steel motor shaft
- Durable aluminum bronze construction NFPA 99C level-3 compliant
- Exclusive internal water recycling

Model no.	CV3	CV5
Item no.	MM-CV3	MM-CV5
Overall Dimension (H x W x D) (mm)	381 x 305 x 330	432 x 305 x 330
Treatment Chairs	2	3
Simultaneous Operators	1	2









Hygiene & Mechanical Room

Compressor & Suction System



The Radial Tyscor V/VS Suction Machine











- **☑** Quiet
- **☑** Lightweight
- **☑** Energy-saving
- **☑** Network-capable

Model no.	Tyscor V 2	Tyscor VS 2
Item no.	DURR-TYSCORV2	DURR-TYSCORVS2
Power Supply	230V	230V
Overall Dimension (H x W x D) (mm)	350 x 320 x 430	350 x 320 x 430
Weight (kg)	10	11
Number of Dentists	2	2
Numbr of Rooms at 60% Simultaneous	3	3
Noise Level [db(A)]	58	58



VS Series Dry / Wet Suction System Compact, Quiet, Extraordinary Long Service Lives



☑ Long Service Lives

housing components and runners are made from galvanic coated aluminium or highly corrosion-resistant plastic

☑ Compact Size

Aspiration & separation are combined centrally on one drive shaft

☑ Exceptionally Quiet

Aerodynamic turbine wheels and integrated sound suppressors ensure low-noise operation

☑ Regulation & Cooling

Integrated auxiliary air valve regulates suction power and ensures sufficient internal cooling

VS 300S

VS 600

VS 900 S

VS 1200 S

Extra **Powerful** 300 l/min delivers full suction power at all times







Item no. (DURR-)	7122-02/002	7128-02/002	7134-02/002	7138-03/002
Power Supply	230V	230V/400V	230V/400V	400V
Treatment Chairs	1-2	2-3	3-5	4-6
Simultaneous Operators	1	2	3	4





Hygiene & Mechanical Room

Compressor & Suction System



The Radial Tyscor V/VS Suction Machine











- **☑** Quiet
- **☑** Lightweight
- **☑** Energy-saving
- **☑** Network-capable

Model no.	Tyscor V 2	Tyscor VS 2
Item no.	DURR-TYSCORV2	DURR-TYSCORVS2
Power Supply	230V	230V
Overall Dimension (H x W x D) (mm)	350 x 320 x 430	350 x 320 x 430
Weight (kg)	10	11
Number of Dentists	2	2
Numbr of Rooms at 60% Simultaneous	3	3
Noise Level [db(A)]	58	58



VS Series Dry / Wet Suction System Compact, Quiet, Extraordinary Long Service Lives



☑ Long Service Lives

housing components and runners are made from galvanic coated aluminium or highly corrosion-resistant plastic

☑ Compact Size

Aspiration & separation are combined centrally on one drive shaft

☑ Exceptionally Quiet

Aerodynamic turbine wheels and integrated sound suppressors ensure low-noise operation

☑ Regulation & Cooling

Integrated auxiliary air valve regulates suction power and ensures sufficient internal cooling

VS 300S

VS 600

VS 900 S

VS 1200 S

Extra **Powerful** 300 l/min delivers full suction power at all times








Item no. (DURR-)	7122-02/002	7128-02/002	7134-02/002	7138-03/002
Power Supply	230V	230V/400V	230V/400V	400V
Treatment Chairs	1-2	2-3	3-5	4-6
Simultaneous Operators	1	2	3	4



Mini Lab Equipment



/ Henry Schein





Handy Articulator IIA

- The upper jaw maintains a horizontal position even when the Incisor Rod is
- 2 easily removable, heat resistant plastic mounting plates to permit working with more than one model



Packing	Item no.
Each	SF-5041

Renfert

MT3 Wet Trimmers

The Appropriate Trimmer For Any Requirement

Extremely Compact Very High Torque

100% Corrosion Free **Robust & Durable**





Adjustable Trimmer Table

Trimmer table can be easily tilted betwen 90° and 98°





Easy & Fast Cleaning

Tool-free removable front door, spray tube & trimmer table can also be removed easily for cleaning

Items	Packing	Item no.
MT3 Trimmer 230V (incl. Klettfix)	Fach	RF-1808-0000
MT3 Trimmer 230V (incl. Marathon)	Each	RF-1808-0500

Renfert

Trimmer Discs



■ Klettfix Silicon carbide

Packing	Item no.
Each	RF-1803-1100



■ Marathon

Partially diamond coated

Packing	Item no.	
Each	RF-1803-2001	



Equipment _____

Mini Laboratory

Mini Lab Equipment



Twister Vacuum Mixing Machine For All Conventional Casting And Modelling Materials





High performance motor and high quality vacuum pump guarantee homogenous and buttle-free mixing

- The large, well illuminated and simple display provides a high degree of user comfort

- Offering all standard functions for easy operation




Speed	100~450 1/min
Power Consumption	180 VA
Dimension (W x D x H)	105 x 243 x 285 (mm)
Weight	5.2 kg
Filter Protection System	3-Step Filter System

Packing	Item no.
Each	RF-1826-0000

Alginate Mixing Bowl With Paddle





✓ HENRY SCHEIN® Clinical

Sandblaster

Henry Schein

clavable

- Increase bond strength



- 1 x Unit With Abrasive Reservoir

- 1 x Additional Abrasive Reservoir With
- Abrasive Sample - 1 x Air Supply Line With In-Line Stopcock - 1 x Air Supply "T" Connections

- 1 x Set Of Instructions

Mixing Bowl With Paddle



Volume	Packing	Item no.
65 mL		RF-1820-6500
200 mL		RF-1820-0200
500 mL	Set	RF-1820-0500
700 mL		RF-1820-0700
1000 mL		RF-1820-1001

Mixing Spatula

	Tomas
Packing	Item no.
i acking	item no.
Each	RF-1821-0200

Vibrax 230V





- **☑** Two-Wave Unit **☑** Four Intensity Levels For **Fine Adjustment**
- Basic Fine Sandlasting Unit

Basic eco 25-70 μ /70-250 μ (230V)

- **☑** Special Mixing Chamber Technology
- **☑** Tank Selector Switch
- **☑** Clean Working Environment
- **☑** Tank Extension
- **☑** Blasting Chamber Volume
- **☑** Tool-Free Exchangeable Panel

Packing	Item no.
Each	RF-2949-2025



Vortex Compact 3L (220 - 240V)



Silent TS (220 - 240V) Powerful Workstation Extraction





Henry Schein Hong Kong Ltd. Tel: (852) 2541-2290 Fax: (852) 2882-4383

HS-101-7004

Mini Lab Equipment



✓ HENRY SCHEIN® Micro-Torch

/ Henry Schein

Instant electronic Ignition Removable base for freestanding or hand-held use

Packing	Item no.
Each	HS-100-2136



PRODUCTS, INC.



UltraVac™ Vacuum Former

The lightweight UltraVac uses a single, three-position toggle switch that activates the unit's heating element, vacuum pump,

The indicator light in the UltraVac's base alerts the operator when the heating element is activated and ready for operation

Power Supply	Packing	Item no.
220V	Each	UL-1080



Waxing Technology High Precision And Time Savings

■ Waxprofi Electronically Regulated Heating Pot







Separate and repeated heating of the instrument is no longer required



Waxlectric Light I Electronically Regulated Wax Knife

Packing	Item no.
Set	RF-2150-0000

■ Waxlectric Tips



Type	Item no.
Probe Large	RF-2150-0103
Blade Narrow	RF-2150-0104
Blade Wide	RF-2150-0105
Blade Chamfer	RF-2150-0106
Wax Knife Large	RF-2150-0112

SYMPRO

Compact, High-Performance Cleaning Device

Quick Cleaning in 15 mins



- Remove plaque, tartar, stains by coffee, tea & red wine
- For dentures, orthodontic appliances and splint

3-Year Warranty

Packing	Item no.
Each	RF-6500-0000

■ SYMPROfluid Universal





Item no. RF-6500-0600



■ SYMPROfluid



Item no. RF-6500-0610

NSK

PRESTO AOUA II

Lubrication Free Laboratory Air Turbine Handpiece With Water Spray



Packing	Item no.
- 1 x PRESTO AQUA II Unit - 1 x PRESTO AQUA Handpiece - 1 x QD-J B3 Coupling - 1 x Hose for PRESTO AQUA II - 1 x Foot Control (AFC-40) - 1 x Secondary Hose for PRESTO	NSK- Y150-023

ULTIMATE XL System (Compact) Bench Top System



Dimension (W x D x H)	167 x 247 x 77(mm)
Speed	1,000~50,000 min ⁻¹
Power Supply	AC 230V 50/60 Hz
Weight	2.8 kg

Packing	Item no.
- 1 x Control Unit - 1 x Micromotor Handpiece - 1 x Foot Control - 1 x Handpiece Stand	NSK- Y141-470

ULTIMATE XL-F System (Compact)



Dimension (W x D x H)	230 x 292 x 113(mm)
Speed	1,000~40,000 min ⁻¹
Power Supply	AC 230V 50/60 Hz
Weight	3.8 kg

Packing	Item no.
- 1 x Control Unit - 1 x Micromotor Handpiece - 1 x Handpiece Stand	NSK- Y141-514







