Pro-Drive FASTENERS

Pro-Driven Industrial Products and Solutions™



SUPERIOR
QUALITY
AT THE
RIGHT

PRICE



Pro-Driven
Industrial Products
and Solutions

Pro-DriveFasteners.com





SUPERIOR QUALITY AT THE RIGHT PRICE

About Pro-Drive Fasteners:

Pro-Drive Fasteners is a premier provider of top-quality products for the flooring industry.

From a one stop line of staples and nails and ever-expanding line of pneumatic tools to our new line of Orbital and Jitterbug sanders. Pro-Drive Fasteners™ is a premier provider of top-quality products for the Wholesale wood distribution channels as well as meeting the requirements with the OEM cabinet/furniture industries.

Product development is a company specialty, as is exceptional quality. In providing products to meet the demands of the industrial environment, Team Pro-Drive Fasteners traces the origins of each process--all the way back to the steel.

Just as we are involved with all aspects of our product, we're similarly committed to all aspects of the customer experience. This includes shipping policies to meet your professional needs. Pro-Drive Fasteners™ offers same-day shipping for orders received by 11am, as well as bulk or full truckload and private label pricing options.

At Pro-Drive Fasteners[™], we continue to innovate the fastening market so we can be your one-stop vendor for premium fasteners and assembly solutions!



Learn more at Pro-DriveFasteners.com

TABLE OF CONTENTS

pg. 4-6

pg. 32

15 GA 1/2" Crown Flooring Staples 15 GA (Q Wire) 7/16" Crown Staples 16 GA (GS Wire) "Paslode" 1/2" Crown Wire Staples 16 GA (N Wire) 1/2" Crown Staples	pg. 4 pg. 5 pg. 6 pg. 6
STAPLES Wide Crown	pg. 7
16 GA 16 GAUGE (S2 SERIES) Bostitch" 1" Wide Crown Staples 16 GA (P Wire) 1" Crown Wire Staples	pg. 7 pg. 7
STAPLES 18 GA	pg. 8
18 GA (M Wire) 3/8" Crown Staples 18 GA (L Wire) Duo-Fast 1800 series	
BRADS-FINISH-MICRO Pins	pg. 9-14
15 GA FN 25° Angle Collated strip FINISH Nails 15 GA DA 34° Angle Collated strip FINISH Nails 16 GA 0° No Angle Collated strip BRAD Nails 16 GA 20° Paslode Angle Collated strip BRAD Nails 18 GA 0° Angle Collated strip BRAD nails "Medium HEAD" 23 GA Micro Pins	pg. 10 pg. 11 pg. 12 pg. 12 pg. 13 pg. 14
DIVERGENT STAPLES Manual & Electric	pg. 15
20 GA "PAD/Carpet Staples 19 GA "PAD" Staples 20 GA Stair Tread Carpet Staples	pg. 15 pg. 15 pg. 15
UPHOLSTER- ASSEMBLY Staples	pg. 16
20 GA Staples (80/10 C & 80/12 C) 20 GA Fine Wire Staples (BEA-97/12 & BEA-97/16 22 GA Staples (BEA7106 & BEA7110)	pg. 16 pg. 16 pg. 17
PNEUMATIC STAPLERS - FINISH TOOLS	pg. 18-19
Brad-Finish - Micro Pin Nailers Fine Wire - Narrow Crown - Medium Crown - Wide Crown Staplers	pg. 18 pg. 19
MALLETS AND CAPS	pg. 25-32
Urethane Striking Faces Poly Dead Blow Hammer Mallet Caps Mallets Split Head Hammer Faces EZ-Connect™ Tapping Block Hammer Tackers	pg. 25 pg. 26 pg. 27 pg. 28 pg. 29 pg. 30 pg. 31

STAPLES Medium Crown

Tipper-De-Tipper™



15.5 GA HARDWOOD FLOORING STAPLES

FLOORING STAPLES

Guaranteed to fit all standard 15.5 gauge flooring tools.



DESCRIPTION:

- · Sold in Contractor Bulk Packs and 1,000 count Project Packs.
- Packed in heavy-duty, FOUR-way, reinforced, resealable boxes.
- Chisel point staple angle reduces splitting during installation.
- Excellent for all types of hardwood flooring installations.







2"

1-3/4"

13/4"

FS-200-5000

FS-175-5000

FS-175-9000



Chisel Point 5,000

Chisel Point 5.000

Chisel Point 9.000



23.8 lbs

20.4 lbs

36.9 lbs

LENICTII	A II	/FO \	
LENGTH	: 2"	(50mm))

E-G Galvanized	Chisel Point	7,720	35.1 lbs
	E o odivanized	2 o carvarrized critiser r critic	2 d dalvariized diiseri diite 7,720

E-G Galvanized

E-G Galvanized

E-G Galvanized

LENGTH: 1-3/4" (44mm)

	, .				
FS-150-5000	1-1/2"	E-G Galvanized	Chisel Point	5,000	18.2 lbs
FS-10300-150	11/2"	E-G Galvanized	Chisel Point	10.300	36.9 lbs

LENGTH: 1-1/2" (38mm)









15 GA STAPLES

7/16" CROWN (Q WIRE) STAPLES

Senco Style Staples




DESCRIPTION:

Collation: Straight Strip

Crown: 7/16"Gauge: 15

Meets or Exceeds ASTM A641

Verify Compatibility by Consulting Owner Manual





Q17	11/2"	E-G Galvanized	Chisel Point	5,000	18.7 lbs
Q21	2"	E-G Galvanized	Chisel Point	5,000	23.1 lbs
Q25	2 1/2"	E-G Galvanized	Chisel Point	5,000	29.7 lbs

Guaranteed to work with:

Senco SQS55, FASCO F45C SQ-55 SS(CT), F5 SQ-65 CT, SQS55XP; Spotnails: MS6564;

Duo-Fast: MS-1580D

Precision engineered to interchange:

BeA 180, Duo Fast 1500, Senco Q Wire, Spotnail

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

WARNING: This product can expose you to chemicals including Nickel and Lead which are known to the State of California to cause cancer.

For more information visit: www.P65Warnings.ca.gov



16 GA STAPLES

1/2" CROWN GS (PASLODE WIRE)
7/16" CROWN SENCO STAPLE (N WIRE) STAPLES



DESCRIPTION:

- Furniture Frames
- · Cabinet Sub-Assembly
- · Millwork Door Jambs etc.
- Heavy Duty Pallet Manufacturing and Repair
- Heavy Duty Crate Framing
- Meets or Exceeds ASTM A641

Verify Compatibility by Consulting Owner Manual


16 GA 1/2" CROWN GS (PASLODE WIRE) STAPLES

GS16112 11/2" E-G Galvanized Chisel Point	10,000	26.2 lbs	k	E-G Galvanized	11/2"	GS16112
---	--------	----------	---	----------------	-------	---------



16 GA 7/16" CROWN SENCO STAPLE (N WIRE) STAPLES

MC750-N11	3/4"	E-G Galvanized	Chisel Point	15,000	21.0 lbs
MC875-N12	7/8"	E-G Galvanized	Chisel Point	15,000	21.5 lbs
MC100-N13	1"	E-G Galvanized	Chisel Point	12,000	21.3 lbs
MC125-N15	11/4"	E-G Galvanized	Chisel Point	10,000	22.0 lbs
MC150-N17	11/2"	E-G Galvanized	Chisel Point	10,000	25.3 lbs
MC200-N21	2"	E-G Galvanized	Chisel Point	10,000	34.0 lbs



Guaranteed to work with:

DeWalt D51431; Fasco R3C HD-40 VIL-SID, F45C GC/16-SS Paslode IM200-S16, S200-S16, MA-S16L, 3200-S16, 3200-S16P, 3150-S16, PA-200; Spotnails X1S1640, MS76-8650i

Precision engineered to interchange:

Paslode GS-16, and Prebena GX series staples.

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

WARNING: This product can expose you to chemicals including Nickel and Lead which are known to the State of California to cause cancer.

For more information visit: www.P65Warnings.ca.gov



WIDE CROWN STAPLES

16 GA S2 SERIES "BOSTITCH" WIDE CROWN 16 GA 1" CROWN (P WIRE DURO-FAST 1700 SERIES)



DESCRIPTION:

- Excellent For Lathing, Sheathing, Foam Insulation Board, Attaching Corrugated to Skids, Furniture and Cabinet Frames, and Butt Joints.
- Steel Chisel

Verify Compatibility by Consulting Owner Manual

16 GA S2 SERIES BOSTITCH" WIDE CROWN

P-16S2-16G 5/8"	E-G Galvanized	Chisel Point	10,000	23.3 lbs

Guaranteed to work with:

Bostitch: T40S2-CT, T50S2-1, T35-8, T35-32, 438S2 ,438S2R, 450S2R; Fasco: F3C ATW-38 ROOF, F3C ATW-38 :Omer: WS.38: :Spotnails: X1S1640 1-1/2", X1S1640RFH, X1S1650 2", X1S1664 2- 1/2"

16 GA 1" CROWN (P WIRE DUO-FAST 1700 SERIES)

P08	1/2"	E-G Galvanized	Chisel Point	10,000	17.0 lbs
P10	3/4"	E-G Galvanized	Chisel Point	10,000	20.3 lbs
P11	5/8"	E-G Galvanized	Chisel Point	10,000	17.6 lbs
P13	1"	E-G Galvanized	Chisel Point	10,000	24.0 lbs

Guaranteed to work with:

BeA 145, Duo-Fast 1700, Fasco ES6, Senco P, Hitachi N3824A, Prebena WS & W, Spotnails 3600 series staples.

Precision engineered to interchange:

Craftsman®: 18307, 18307: Duo-Fast®: RS-1748, KW-1748, SW-1748, RNS-1748I;: Fasco®: R3C SNW 38TL, F3C SNW-38R; Grex®: 2638;: Hitatchi®: N5024A, N3824A; Grip-Rite®: GRTS1200;: Makita®: AT2550A; Omer®: WP.38; Prebena WS & W ,:Spotnails®: X1S3640(LM) 1-1/2", X1S3650 2", X1S3640RFH; Senco®: MW, MWXP-1, PW, PW-2", PW-R, PW200, SPS, SPS-RFR, PW150/R; WC150XP, WC200XP



This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

WARNING: This product can expose you to chemicals including Nickel

and Lead which are known to the State of California to cause cancer.

For more information visit: www.P65Warnings.ca.gov



18 GA STAPLES 3/8" CROWN (M WIRE) **DUO-FAST 1800 SERIES**




DESCRIPTION:

- Made from Extra Hard Wire
- Meets or Exceeds ASTM A641

Verify Compatibility by Consulting Owner Manual

18 GA 3/8" CROWN (M WIRE & DUO-FAST 1700 SERIES)

M10BAB58	5/8"	E-G Galvanized	Chisel Point	5,000 x 10 50,000	36.5 lbs
M11BAB34	3/4"	E-G Galvanized	Chisel Point	5,000 x 10 50,000	43.7 lbs
M12BAB78	7/8"	E-G Galvanized	Chisel Point	5,000 x 10 50,000	23.1 lbs
M13BAB100	1"	E-G Galvanized	Chisel Point	5,000 x 10 50,000	56.4 lbs
M15BAB125	11/4"	E-G Galvanized	Chisel Point	5,000 x 8 40,000	55.3 lbs




Applications:

Cabinet assembly insulation, plastic sheeting, Tyvek, roofing paper, house wrap and more

Precision engineered to interchange:

DUO-FAST®W-1800, , JOSEF KIHLBERG® G4450 , PREBENA® G , SENCO® M, SPOTNAILS® 6800, AND OTHER 3/8" CROWN M WIRE TOOLS. Not compatible with Arrow T50 series 3/8" crown staplers. May not operate in an automated setup.

18 GA 1/4" CROWN (L WIRE - DUO-FAST 1800 SERIES) 5,000 x 8 1824-L11 3/4" E-G Galvanized Chisel Point 37.8 lbs 40,000 5,000 x 8 1828-L12 7/8" F-G Galvanized Chisel Point 42.0 lbs 40,000 5,000 x 8 1832-L13 1" E-G Galvanized Chisel Point 46.8 lbs 40,000 5,000 x 8 1 1/8" 1836-L14 E-G Galvanized Chisel Point 46.8 lbs 40,000 5,000 x 8 1840-L15 11/4" E-G Galvanized Chisel Point 53.2 lbs 40,000 5.000 x 8 1848-L17 1-1/2" E-G Galvanized Chisel Point 62.7 lbs



Applications:

Finish and trim staples are ideal for cabinets, drawers, case backs, upholstery, soffits, underlayment, lattice, insulation sheathing, Engineering flooring and much more

40,000

Precision engineered to interchange:

ATRO 90, BeA 90, DUO-FAST 1800, PREBENA EB, HAUBOLD KL 6000 ,HITACHI N3804, PORTER CABLE NS 100 & NS150A, SENCO L, SPOTNAILS 4800, JK 781

Learn more at Pro-DriveFasteners.com

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.

Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode, Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.




WE HAVE THE RIGHT BRAD/FINISH NAIL FOR ANY JOB!



15 GAUGE **FINISH NAILS**

Commonly used for all types of trim.



16 GAUGE **FINISH NAILS**

Commonly used for all types of trim. Fits all brands.





18 GAUGE **FINISH NAILS**

Used for finer, thinner wood trim. Less putty needed. Fits all brands.



23 GAUGE **FINISH NAILS**

Micro Pins fasten with a nearly invisible hole. Excellent for face nailing wide

plank engineered flooring.







Learn more at Pro-DriveFasteners.com

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.


> Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode. Not recommended for exterior application or ACO Treated Lumber.



15 GA "FN" FINISH NAILS

25° ANGLE BRAD

Our brad finish nails are professional grade quality, contractor-tested and approved.



DESCRIPTION:

- · Chisel Point Smooth Shank.
- Electro Galvanized Steel Meets ASTM F1667.
- Contractor Packed 3,655 per box.
- Made with Premium Grade Steel to Provide Exceptional Performance.
- Guaranteed to Deliver Worry-free Performance.
- Excellent for Interior Finish, Trim Work, Hardwood Flooring, Baseboards, and More!

Verify Compatibility by Consulting Owner Manual









Learn more at Pro-DriveFasteners.com






15 GA "DA" FINISH NAILS

34° ANGLE BRAD

Our brad finish nails are professional grade quality, contractor-tested and approved.



DESCRIPTION:

- · Chisel Point Smooth Shank.
- Electro Galvanized Steel Meets ASTM F1667.
- · Available in Stainless Steel.
- Contractor Packed 4,000 per Box.
- Made with Premium Grade Steel to Provide Exceptional Performance.
- Guaranteed to Deliver Worry-free Performance.
- Excellent for Interior Finish, Trim Work, Hardwood Flooring, Baseboards, and More!


Verify Compatibility by Consulting Owner Manual




DA13-100	1" (25mm)	E-G Galvanized	Chisel Point	4,000 x 4 16,000	24.2 lbs
DA15-125	11/4" (32mm)	E-G Galvanized	Chisel Point	4,000 x 4 16,000	23.7 lbs
DA17-150	11/2" (38mm)	E-G Galvanized	Chisel Point	4,000 x 4 16,000	24.4 lbs
DA19-175	13/4" (45mm)	E-G Galvanized	Chisel Point	4,000 x 4 16,000	33.0 lbs
DA21-200	2" (50mm)	E-G Galvanized	Chisel Point	4,000 x 4 16,000	36.7 lbs
DA21-200SS	2" (50mm)	Stainless Steel	Chisel Point	4,000 x 4 16,000	36.7 lbs
DA25-250	2 1/2" (64mm)	E-G Galvanized	Chisel Point	4,000 x 4 16,000	45.8 lbs
DA25-250SS	2 1/2" (64mm)	Stainless Steel	Chisel Point	4,000 x 4 16,000	45.3 lbs

For more information visit: www.P65Warnings.ca.gov







16 GA FINISH NAILS

0° ANGLE "STRAIGHT" COLLATED STRIP 20° ANGLE COLLATED STRIP

Fits most straight, no angle 16-gauge finish tools.



DESCRIPTION:

- · Blunt Chisel Point Smooth Shank.
- Electro Galvanized Steel Available in Stainless Steel
- Contractor Packed 2,500 per box.
- Meets ASTM F1667
- Made with Premium Steel Guaranteed not to Jam Your Tool
- Excellent for Interior finish, Trim Work, Hardwood Flooring, Baseboards, and More!

Verify Compatibility by Consulting Owner Manual

16GA 0° ANGLE "STRAIGHT" COLLATED STRIP FINISH NAILS

C25-100	1" (25 mm)	E-G Galvanized	Chisel Point	2,500 x 10 25,000	21.8 lbs
C32-125	11/4" (32mm)	E-G Galvanized	Chisel Point	2,500 x 12 30,000	32.8 lbs
C38-150	11/2" (38mm)	E-G Galvanized	Chisel Point	2,500 x 12 30,000	38.4 lbs
C45-175	1 3/4" (44mm)	E-G Galvanized	Chisel Point	2,500 x 12 30,000	45.1 lbs
C50-200	2" (50mm)	E-G Galvanized	Chisel Point	2,500 x 12 30,000	49.8 lbs
C50-200SS	2" (50mm)	Stainless Steel	Chisel Point	2,500 x 12 30,000	49.8 lbs
C64-250	2 1/2" (64mm)	E-G Galvanized	Chisel Point	2,500 x 8 20,000	42.2 lbs
C64-250SS	2 1/2" (64mm)	Stainless Steel	Chisel Point	2,500 x 12 30,000	42.2 lbs

16GA 20° PASLODE® ANGLE COLLATED STRIP FINISH NAILS

AFN50-200	2"	(50mm)	E-G Galvanized	Chisel Point	2,000 x 10 20,000	43 lbs	
-----------	----	--------	----------------	--------------	----------------------	--------	--

Precision engineered to interchange:

Dewalt DCN660D1, Metabo HPT NT65M2SM, MAX NF565A/16, Omer 14.50, Paslode IM250S-Li, T250S-F16, Senco 16XP, Stanley Bostitch FN1664K. Designed to be Universal fit for most straight no angle 16 gauge finish nailers.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



18 GA FINISH NAILS

0° ANGLE "STRAIGHT" COLLATED STRIP

Our brad finish nails are professional grade quality, contractor-tested and approved.



DESCRIPTION:

- · Chisel Point Smooth shank.
- · Electro Galvanized Steel Meets ASTM F1667.
- Contractor Packed 5,000 per box.
- Made with Premium Grade Steel to Provide Exceptional Performance.
- Guaranteed to Deliver Worry-free Performance.
- Excellent for Interior Finish, Trim Work, Hardwood Flooring, Baseboards, and More!

Verify Compatibility by Consulting Owner Manual


18GA 0° ANGLE "STRAIGHT" COLLATED STRIP BRAD NAILS "SLIGHT HEAD"



AXX08EAA-500	1/2"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	10 lbs
AXX10EAA-625	5/8"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	10 lbs
AXX11EAA-750	3/4"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	10 lbs
AXX13EAA-100	1"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	12 lbs
AXX15EAA-125	1-1/4"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	12 lbs
AXX17EAA-150	1-1/2"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	12 lbs
AXX21EAA-200	2"	E-G Galvanized	Chisel Point	5,000 x 12 60,000	12 lbs
AXX11EAA-750SS	3/4"	Stainless Steel	Chisel Point	1,000 x 8 8,000	8 lbs

Precision engineered to interchange:

Duo-Fast 4450, 4450ST, Dewalt DC608K, DCN680D1, DCN680B, DWFP12233, Grip-Rite GRTBN200, Grex 1850GB, Paslode T200 F18, IM200-Li, Senco Finish-Pro FP25XP, FinishPro 18MG, SLP20XP, FinishPro 2N1, FP18MG, FN55AX, Metabo HPT NT50AE2M, Stanley Bostitch BT1855K, SB-2IN1, and designed to be Universal fit for most straight no angle 18ga "Medium HEAD" finish nailers.





Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.



23 GA HEADLESS PIN NAILS

MICRO PINS

Micro Pins fasten the smallest of trim securely, leaving a nearly invisible hole.



DESCRIPTION:

- · Chisel point · Smooth shank Electro Galvanized Steel
- Convenient 4,500 ct Project Pack and 10,000 ct Job Pack
- Directional Arrows are Painted on Strips to Eliminate Loading Error.
- Micro Pins Fasten with a Nearly Invisible Hole
- Our Brad Finish Nails are Contractor Tested and Proven
- Meets ASTM F1667

Verify Compatibility by Consulting Owner Manual

23GA PINS NAILS

CZ10-58	5/8" (16mm)	E-G Galvanized	Chisel Point	4,500 x 24 108,000	10.1 lbs
CZ11-34	3/4" (19mm)	E-G Galvanized	Chisel Point	4,500 x 24 108,000	11.3 lbs
CZ13-100	1" (25mm)	E-G Galvanized	Chisel Point	4,500 x 24 108,000	16.0 lbs
CZ16-138	13/8" (35mm)	E-G Galvanized	Chisel Point	4,500 x 24 108,000	20.8 lbs

CZ08-500-10	1/2" (13mm)	E-G Galvanized	Chisel Point	10,000 x 48 480,000	35.0 lbs
CZ10-58-10	5/8" (16mm)	E-G Galvanized	Chisel Point	10,000 x 48 480,000	43.0 lbs
CZ-11-34-10	3/4" (19mm)	E-G Galvanized	Chisel Point	10,000 x 48 480,000	48.1 lbs
CZ13-100-10	1" (25mm)	E-G Galvanized	Chisel Point	10,000 x 48 480,000	69.0 lbs
CZ16-138-10	13/8" (35mm)	E-G Galvanized	Chisel Point	10,000 x 24 240,000	45.5 lbs



Eliminate loading errors with direction arrows

Precision engineered to interchange:

Cadex 23/15-10M, Duo-Fast 2320, Fasco ES2316P, Grex P6/15L, Grip-Rite GR58PIN, Grizzly H5044, Hitachi 23000, Interchange MP23-58-I (23225), Metabo HPT (23000), ,Porter-Cable PPN23063, Prebena AL16CRF, Senco A100629 (CZ10EAAN), Spotnails 23010, Unicatch CZ16 (87946) and many other 23ga Mirco Pin capable tools

Application Including and Not Limited To:

- Interior finish and trim
- Carving and ornamentals
- Rattan furniture production, picture and mirror frames, window beading
- Molding
- Decorative trim
- Cabinets
- Picture and mirror frames
- Ornamentals
- And many more applications requiring Headless pin nail

Compatible Tools:

Cadex 23/15-10M, Duo-Fast 2320, Fasco ES2316P, Grex P6/15L, Grip-Rite GR58PIN, Grizzly H5044, Hitachi 23000, Interchange MP23-58-I (23225), Metabo HPT (23000), Porter-Cable PPN23063, Prebena AL16CRF, Senco A100629 (CZ10EAAN), Spotnails 23010, Unicatch CZ16 (87946), and many other 23ga Mirco Pin capable tools

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.



20 GA STAPLES

20GA "PAD" STAPLES 20GA "STAIR TREAD PAD" STAPLES TAN CROWN

Similar to Rapid 19 Arrow T-50



DESCRIPTION:

- Made from Extra Hard Wire
- Resin Coated and Galvanized

Verify Compatibility by Consulting Owner Manual

DIVERGENT STAPLES

Applications: Bedding Carpet Pad, Insulation, Roofing, House Wrap, light wood assembly, Poly Sheeting, roof paper, upholstery



20GA "PAD" STAPLES

A11-10D 3/8" Leg	13/32" Crown	20 GA	E-G Galvanized	Chisel Point	5,000 x 20 100,000
-------------------------	--------------	-------	----------------	--------------	-----------------------

Arrow T50, Duo-Fast A-11, Arrow T-55, Senco H, Senco A-11, Rapid 11, JK671 staples, and other A11-10- series staplers

5010-D	3/8" Leg	1/2" Crown	20 GA	E-G Galvanized	Chisel Point	5,000 x 20 100,000	
--------	----------	------------	-------	----------------	--------------	-----------------------	--

Compatible Fasteners: BeA 95, Haubold 900, JK64, Prebena AD, Spotnails 35, Fasco ED-50. and other 5000 series staples

7512D	3/8" Leg	15/32" Crown	19 GA	E-G Galvanized	Chisel Point	5,000 x 20 100,000
-------	----------	--------------	-------	----------------	--------------	-----------------------

Carpet pad staples for use in in hammer tackers using 7500 series staples (Duo-Fast HT-755, HT-755M & others).



20GA "STAIR TREAD PAD" STAPLES TAN CROWN

5418D	9/16" Leg	3/16" Crown	19 GA	E-G Galvanized	Chisel Point	5,000 x 20 100,000	
-------	-----------	-------------	-------	----------------	--------------	-----------------------	--

Applications: For use with electric tacker staples are used to fasten carpet treads on stairs, upholstery, bedding.

Compatible Tools: For use in electric and pneumatic tools-Bostitch: CR1000E; , Cran 625 Pro Stapler , Duo-Fast DNS-5424, ENC-5418A, BN-5424, SShot 5424; Duo-Fast DNS-5424, ENC-5418A, BN-5424, SShot 5424; Fasco: F1A 54DF-18, F1B 54DF-18

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.


WARNING: This product can expose you to chemicals including Nickel

and Lead which are known to the State of California to cause cancer.



20 & 22 GA STAPLES

1 /2" CROWN X 20 GA STAPLES 3/16" CROWN X 20 GA STAPLES






DESCRIPTION:

- Made from Extra Hard Wire
- Highest Quality for Industrial and Commercial use
- Meets or Exceeds ASTM A641
- Guarantee performance will no jamming

Verify Compatibility by Consulting Owner Manual

1/2" CROWN X 20 GA STAPLES

80/10 C	3/8" Leg x 1/2" Crown	E-G Galvanized	Chisel Point	10,000 x 10 100,000	29.2 lbs
80/12 C	1/2" Leg x 1/2" Crown	E-G Galvanized	Chisel Point	10,000 x 10 100,000	42.6 lbs





Applications:

Upholstery staple, bedding, dust covers, arts and crafts, picture framing, corner blocks, packaging, carpeting and many more light assembly applications.

Precision engineered to interchange:


BEA 80/380, Bostitch AZ33, Atro 8, JK680, Spotnails 80, Haubold 800, Empire 8, Rainco 8, Fasco EB80XX.

Guaranteed to work with:

BeA: 80, 380/16; "Fasco F1B 80-16, S80-16, F1A 80-16, F1B 80-16 LN 50MM, F1A 80-16 LN50MM, F1A 80-16 AUTO LM, F1B 80-16 AUTO LM; Bostitch: 21680B, 21680BLN, 21680B-ALM, BA-T400; Josef Kihlberg JK20-680, JK20A-680 Auto, JK20A-680L Auto Long magazine, Haubold: N814; Spotnails BS8016AF, JS8016(LN), PS8016, BS8016AF, DS8016, TES8118;

3/16" CROWN X 20 GA STAPLES

BEA-97/16 5/8" Leg x 3/16" Crown E-G Galvanized Chisel Point 10,000 × 10 100,000 30.2 lbs	BEA-97/12	1/2" Leg x 3/16" Crown	E-G Galvanized	Chisel Point	20,800 x 6 124,800	31.6 lbs
	BEA-97/16	5/8" Leg x 3/16" Crown	E-G Galvanized	Chisel Point	10,000 x 10 100,000	30.2 lbs





Applications:

Auto Industry, Case Backs, Cabinetry, Chairs, Drawer Runners, Picture Framing, Lattice Panels, TV and Stereo Cabinets, Upholstered Furniture , Wicker and Rattan Furniture

Precision engineered to interchange:

Spotnails 97, Bea 97, Atro 97, Prebena O, JK 690 staples.

Guaranteed to work with:

S3297-LHF-2, LHF97125, Duo-Fast ENC-5418A, Fasco F1A 97B-25, F1B 97B-25, F21P 97B-25, F21P 97B-25A staplers.

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.





22 GA STAPLES

3/8" CROWN X 22GA STAPLES (BEA 71 SERIES & SENCO C SERIES)




Designed for high-speed Air Powered (Pneumatic) Staple Guns

DESCRIPTION:

- Made from Extra Hard Wire
- · Highest Quality for Industrial and Commercial use
- Meets or Exceeds ASTM A641
- Guaranteed performance- will not jam

Verify Compatibility by Consulting Owner Manual

3/8" CROWN X 22GA STAPLES (BEA 71 SERIES & SENCO C SERIES)



BA7106	1/4" Leg x 3/8" Crown	E-G Galvanized	Chisel Point	20,000 x 10 200,000	26.1 lbs
BA7110	3/8" Leg x 3/8" Crown	E-G Galvanized	Chisel Point	20,000 x 10 200,000	34.53 lbs
BA71-12	1/2" Leg x 3/8" Crown	E-G Galvanized	Chisel Point	20,000 x 10 200,000	???
BA71-14	9/16" Leg x 3/8" Crown	E-G Galvanized	Chisel Point	20,000 x 10 200,000	???
BA7106SS	1/4" Leg x 3/8" Crown	Stainless Steel	Chisel Point	20,000 x 10 200,000	24.2 lbs
BA7110SS	3/8" Leg x 3/8" Crown	Stainless Steel	Chisel Point	20,000 x 10 200,000	28.3 lbs
BA7112SS	1/2" Leg x 3/8" Crown	Stainless Steel	Chisel Point	20,000 x 10 200,000	???



Applications:

Upholstery staple, bedding, dust covers, arts and crafts, picture framing, corner blocks, packaging, carpeting, molding and many more light assembly applications.

Precision engineered to interchange:

ATRO 90, BEA 90, DUO FAST 1800, PREBENA EB, HAUBOLD KL 6000, HITACHI N3804, PORTER CABLE NS 100 & NS150A , SENCO L, SPOTNAILS 4800, JK 781

Guaranteed to work with:

BeA:71/15-421, FASCO: F1A 7C-16,FIA S3G-16, FIB 7C-16, F1B S3G-16, F1B SR3-16, Porter Cable US58; ,Spotnails JS7116, JS7116LN, IS7116, BS7116AF, PS7116, Senco STF1O-C, SFW09-C, SFW10XP-C, SFW08C, SFT1O-C, SJ10-C, Fasco F1A 7C-16, F1B 7C-16 AUTO, F1B 7C-16 LN50, F1B 7C-16 ALM air staple guns; Fasco Maestri ME-3G electric staple guns

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



AIR TOOLS

18GA BRAD NAILER 16GA BRAD NAILER 23 GA MICRO PINNER



AIR TOOLS

BRAD18	18 GA Brad Nailer
BRAD16	16 GA Brad Nailer
MICRO-23	23 GA Micro Pin Nailer

BRAD18



360° exhaust deflector E-Z tool-free depth-adjustment device EZ front access for removing jam Easy open magazine latch No-mar pad

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
3.06 lbs	9.7"x2.4"x9.9"	70 - 110 psi	110 Brads	5/8" - 2"

Precision engineered to work with most straight (no angle) 18-gauge finish nails

BRAD16



Accept 15 / 16GA Finish Nails 360° Adjustable Air Deflector Quick Release Nose Cover Well Balanced

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
4.19 lbs	10.7" x 2.8" x 11.1"	70 - 110 psi	100 Nails	5/8" - 2 1/2"

Precision engineered to work with most straight no angle 16-gauge finish nails No-Mar Rubber Pad Available (#21903602)

MICRO23



Can be used with Both Headless and Mini Head Pins Belt hook Rear Exhaust to Avoid Oil Stains on working surface One hand Side Loading Magazine Removable No-Mar Rubber Pad Nail Lockout to Avoid Empty Shots User friendly full Wrap-Around Rubber Grip Slim Tapered Nose for Precise Nail Placement

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
2.01 lbs	8.07 x 1.69" x 6.85"	70 - 100 psi	120 Pins	1/2" - 1 3/8"

Precision engineered to work with: Cadex 23/15-10M, Duo-Fast 2320, Fasco ES2316P, Grex P6/15L, Grip-Rite GR58PIN, Grizzly H5044, Hitachi 23000, Interchange MP23-58-I (23225), Metabo HPT (23000), Porter-Cable PPN23063, Prebena AL16CRF, Senco A100629 (CZ10EAAN), Spotnails 23010, Unicatch CZ16 (87946), and many other 23ga Mirco Pin capable tools

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



AIR TOOLS

16 GA WIDE CROWN STAPLER 16 GA MEDIUM CROWN STAPLER 97 SERIES FINE WIRE STAPLER



L WIRE STAPLER #L18-NC



18 Ga. 1/4" Narrow Staples

360° exhaust deflector Switchable trigger E-Z tool free depth-adjustment EZ front de-jamming Narrow nose piece No-mar pad Capacity: 110pcs TOP LOADING

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
2.97 lbs	10.9"x2.4"x10"	70 - 110 psi	110 Staples	3/4" - 1 5/8"

Precision engineered to work with most 1/4" narrow crown 18-gauge staples

N WIRE STAPLER #M18-38



Quick-Release Nose Jam Clearance feature no tool required High-speed firing up to 13 staples second Dedicated Bump Fire (Orange) or Full Sequential Trigger (Black) Available Quick Loading Open Magazine Magazine has E-Z viewing fastener capacity

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
4.8 lbs	14 7/8" x 2 7/8" x 10 7/8"	70 - 110 psi	140 staples	1" - 2"

Precision engineered to work with: BeA16® (155), Duo-Fast® 7600 , Haubold ®KG 700, Senco® N, and many more standard 7/16" crown staples 17 GA-Compatible with Senco® O Series

M WIRE STAPLER



360° exhaust deflector Switchable trigger E-Z tool free depth-adjustment EZ front de-jamming Narrow nose piece No-mar pad Capacity: 110pcs TOP LOADING

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
4.6 lbs	11.9"x3.2"x10.4"	70 - 110 psi	130 Staples	3/4" - 1 5/8"

Precision engineered to work with most 3/8" crown 18-gauge staples

L WIRE STAPLER #78150L



8GA Underlayment Stapler
Extra Long Magazine
Crown: 1/4" L WIRE
Designed for 3/8" to 5/8" (10 mm to 16 mm) engineered flooring

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
???????	14" x 2.5" x 9.5"	75 - 100 psi	???????	7/8" - 1-9/16"

Precision engineered to work with most 3/8" crown 18-gauge staples

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



AIR TOOLS

P WIRE STAPLER M WIRE STAPLER



W AND 97 SERIES STAPLER 22 GA #N16-MC



Standard Double trigger for increased safety Bottom Load, Jam Free Magazine Rear Exhaust to Avoid Oil Stains on working surface Slim Long Nose for Easy, Precise Staple Placement Extended Trigger design for Rapid Stapling User friendly full Wrap-Around Rubber Grip

Weight	Dimensions (L*W*H)	Operated Pressure	Load Capacity	Range
1.95 lbs	8.6" x 1.7" x 5.7"	60 - 100 psi	125 Staples	1/4" - 5/8"

Precision engineered to work with: BeA@97, Haubold@4000 Omer@4097, Senco@W Series and many more standard 97 (3/16" Crown) series staples

P WIRE STAPLER #P16-WC



E-Z Quick Release Nose Cover 360° Adjustable Air Deflector Heavy Duty, Well Balanced Sequential Fire Trigger Available

Weight	(L*W*H)	Operated Pressure	Load Capacity	Range
5.6lbs	14.7" x 2.75" x 10.23"	85 - 110 psi	160 Staples	3/4 - 11/2"

Precision engineered to work with: BeA® 145 ,Duo-Fast ®1700, Fasco® ES6 ,Hitachi® N3824A, Senco® P, , Spotnails® 3600, Prebena® WS & W, series staples.and many more standard 1" crown staples

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



AIR SANDERS

JB-3-4

3" X 4" Jitterbug Air Sander with Square pad



JB-3-4

PAD SIZE:	3" × 4"
ORBIT DIAMETER OFFERED:	1/8"
FREE SPEED:	12,000 RPM
AVG. AIR CONS:	10.5 CFM
AIR PRESSURE:	90 PSI (6.2 bar)
NET WEIGHT:	1.63 Lbs/0.74 kgs
AIR INLET:	1/4"
AIR HOSE I.D. :	2.5 m/52
SOUND PRESSURE:	79 dB/AJ
PACKING:	10pvs/ctn GW" 16.30Lbs/7.4kgs



PADS

AS-3-4 PAD-HL <> 3" X 4" SANDING PAD (HOOK & LOOP)



AAS-JB 3-4 REPAIR KIT MAINTANCE REPAIR KIT INCLUDES ALL OF THE BELOW ITEMS

Ball Bearing # 2 (2314), • Rotor #6 (309N-14F) • Rotor Blade #7 (305N-13) has 5 rotors • Ball Bearing #10 (00-2314) • Rotor Key #8 (3701A) Silencer • Assembly #48 (A3090N-37) • Valve Washer #49 2080N-49 • Valve #50 (2080N-50) • Valve Spring #51 92080N-51

> This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode. Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



AIR SANDERS

AS-500

5" Orbital Industrial Level Dual Action Sander with Hook & Loop pad



AS-500

PAD SIZE:	5"
ORBIT DIAMETER OFFERED:	3/16" or 3/32"
FREE SPEED:	12,000 RPM
AVG. AIR CONS:	1.6 CFM
AIR PRESSURE:	90 PSI (6.2 bar)
NET WEIGHT:	1.98 Lbs/0.9 kgs
AIR INLET:	1/4"
AIR HOSE I.D. :	3/8' (10mm)
SOUND PRESSURE:	80 dB(A)
PACKING:	10pvs/ctn GW" 26.5Lbs/12kgs



PADS

AS-500V <> 5" PAD (VINYL, 5/16"

AS-500HL <> 5" PAD (HOOK & LOOP, 5/16")





AS-500 REPAIR KIT MAINTANCE REPAIR KIT INCLUDES ALL OF THE BELOW ITEMS

Sleeve Set #7 A11XAS • Valve set #5 OBS08AS • Bearing #12 70048A • Rotor #15 STOB-21 • Rotor Blade #14 OB-20-3 (has 5 STEEL rotors)

Ball Bearing #19 OB-26A • Rotor Key #22 ST70407

This product is made and sold by Pro-Drive Fasteners® and has no relationship with any of the other companies whose trademarks or item numbers are mentioned above.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



E-Z CONNECTTM

BRAIDED AIR HOSE

E-Z CONNECT air hoses eliminate the need for whip hoses with straight sections.



DESCRIPTION:

- Maximum Working Pressure: 200psi.
- Wall Thickness: .075 +/- .005.
- · Hose Inner Diameter: 1/4" Hose Outer Diameter: 3/8".
- Field Repairable All Units have Reusable Fittings that Allow In-field Repairs if Necessary.
- Industrial Grade 6 Ball Couplers Reusable Fitting.
- Excellent Cold Weather Flexibility, Temp 40°f to 140°f (-40°c to 60°c).
- · High Abrasion-resistance Smooth Finish will not Mar Surfaces .
- Extremely Kink-resistant Oil Resistant.
- 40% To 50% Lighter than Traditional Air Hoses.







BLUE-AIR250-100	PU BRAID TU 1/4*0.375*100FT	12 per ctn	42.3 lbs
BLUE-AIR250-50	PU BRAID TU 1/4*0.375*50FT	20 per ctn	???
RED-AIR250-50R	PU BRAID TU 1/4*0.375*50FT	20 per ctn	3.7 lbs?



E-Z CONNECT™

FITTINGS, COUPLERS & SPLICERS

AIR-MP20M	INDUSTRIAL SIX BALL 1/4"NPT MALE	10 per bag	0.43 lbs
AIR-MIC20F	MIC series Quick Coupler INDUSTRIAL NIPPLE,BRASS,1/4" NPT FEMALE	10 per bag	2.36 lbs
AIR-UCB1414	BRASS FITTING, REUSABLE SPLICER FOR 3/8*1/4 HOSE	10 per bag	1.6 lbs
AIR-SW-MP20M	360 degree MP Swivel nipple x 1/4" NPT male	10 per bag	1.9 lbs









AIR-SW-MP20M

· Eliminates air hose tangles

Improves workflow with

more effective tool

placement

- 360° swivel connector
- AIR-MP20F Male connector · Professional grade nipple
 - Brass plated steel

AIR-UCB1414

- Splicer for 3/8" Hose
- · Requires minimal tools
- Reuseable and durable
- Quick & easy field repair
- · Quality brass hex stock
- · Quick coupler
- · Knurled Body enhances grip
- Industrial 6 ball design

AIR-MIC20F



Learn more at **Pro-DriveFasteners.com** Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode. Not recommended for exterior application or ACO Treated Lumber.



SUPERFLEX HYBRID REINFORCED PVC HOSE



Premium version of our EASY-CONNECT™ air hoses

DESCRIPTION: 1/4"x 0.375" X 50' NPT Male Brass Fitting, and Quick Coupler

· Includes Plastic Guard











AIR PVC-YELLOW-50	FLEXIBLE PVC BRAID HOSE	12	39.1 lbs
YELLOW-CH1414	1/4" NPT HOSE BARB FITTING	10 per bag	12.4 lbs
YELLOW-FE14	1/4" FERRULE	10 per bag	7.2 lbs

Maximum Working Pressure 300 psi • Industrial Grade 6 Ball Couplers
High Abrasion-resistance - Smooth Finish will not Mar Surfaces
Extremely Kink-resistant • Oil Resistant • UV Resistant
35% Lighter than Traditional Rubber Hose • Temp -25°C +60°C
ROHS Compliant

All our fittings and couplers are industrial grade for heavy duty use.

Designed for use in the DIY market as well meeting the demands of the professional tradesman.

You can count on our E-Z Connect line to provide reliable performance for many tool applications and uses.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.



URETHANE STRIKING FACES

Guaranteed to fit leading brands of flooring urethane cap mallets or your money back.



DESCRIPTION:

- Guaranteed to all fit the major brands with 3/8" x 16 standard thread.
- Ideal replacement for 2" Poly Faces.
- · Five different colors denoting hardness and densities.
- Unaffected by liquids, solvents and lubricants.
- Will not damage, mar, dent, or deface, while providing a solid, high-impact and resilient striking face.
- Free counter display with purchase of 16 Poly Striking Faces.





2" Poly Cap - SOFT ITEM# POLY01-ORG	16 per case
2" Poly Cap - SOFT/Med ITEM# POLY01-BRO	16 per case
2" Poly Cap - MEDIUM ITEM# POLY01-GRE	16 per case
2" Poly Cap - TOUGH ITEM# POLY01-RED	16 per case
2" Poly Cap - HARD ITEM# POLY01-BLK	16 per case



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



POLY **DEAD BLOW HAMMER**





KEY FEATURES:

- Head cavity partially filled with iron shot, to provide greater striking force
- Face absorbs portion of blow's energy.
- Force of blow transmitted solidly to strike surface.

POLY Dead Blow Hammer - 2" Poly Face* | ITEM# 200L-POLY | 2.4 lbs



Head Design Provides Greater Service Life (Patent Pending)

100% Premium Hickory Handle

ITEM #'S:

200L-OB
with Orange & Brown Poly caps
200L-OG
with Orange & Green Poly caps
200L-POLY-O-BL
with Orange & Black Poly caps
200L-POLY-BR-BR
with Brown & Brown Poly caps



200L-2000 - Replace Inserts



200L-1000 - Steel Replacement Shot



MALLET CAPS (Rubber)

Guaranteed to fit leading brands of flooring rubber cap mallets or your money back



DESCRIPTION:

- Easy to Install.
- · Heavy-duty chrome-plated retention ring.



GREY MALLET CAP ITEM# CAP602G

24 Per Case

• Great for Pre-Finished and Unfinished wood!



24 Per Case

• Great for Pre-Finished and Unfinished wood!



NEW! PRO-ANGLE* MALLET CAP ITEM# CAP600PA 24 Per Case

- This Cap offers an improved edge clearance for racking flooring strips.
- Great for Pre-Finished and Unfinished wood!



BLACK MALLET CAP ITEM# CAP600B

24 Per Case

• Great for Unfinished wood!



VCAP RUBBER MALLET CAP ITEM# 23004-200

24 Per Case

- 2" Diameter Soft White
- Compatible with Grainger Part Number 1TMB9
- Compatible with MSC Part Number 01893767



- Patented E-Z 2CAP™ design allows for easier and faster cap installation.
- Pro-Drive Fasteners™ caps will fit all major brands, guaranteed.

E-Z 2CAP™







Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.



MALLETS

Six-ring, easy-grip pattern along with flared handle provides slip resistance and ensures firm grip.



DESCRIPTION:

- 100% American Hickory handle.
- Replacement caps and striking faces available in various colors.
- Patent pending head design to secure handle in head.



Steel Head/White Cap ITEM# M1W	15"	3.2 LBS.
Steel Head/White Cap ITEM# M3W	15"	3.6 LBS.
Steel Head/White Cap ITEM# M5W	15"	3.7 LBS.
Round Head/White Cap ITEM# R5W	15"	2.2 LBS.
Double Headed/White Cap ITEM# DHW	15"	3.4 LBS.



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.



SPLIT HEAD HAMMER FACES (Rubber)

Our split-head, rubber, hammer faces are designed for the professional flooring installer.



DESCRIPTION:

- Easy to install.
- Durable for pre-finished and unfinished wood.
- Packed 12 to a case.
- · NON-MARRING.







Premium Mallet caps fit Garland® split head mallets

1 1/2" White Hammer Face ITEM# 23002-150 12 per case

2" White Hammer Face ITEM# 23004-200 12 per case



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.



E-Z CONNECT™

XTRA LARGE PRO-TAPPING BLOCK

Durable, plastic tapping block - made from 1" solid, high-quality material.



DESCRIPTION:

- Ideal tapping block for Vinyl Plank, Engineered or Solid Hardwood Flooring.
- Designed to eliminate use of a mallet. Use only one hand along with the E-Z CONNECT™ Pro-Tapping Block to set your flooring.
- · Makes for faster board placements Ideal for longer planks.
- Extra-long wooden D-Grip will virtually eliminate crushed fingers.
- Balanced 46oz weight will provide enough heft to set planks with one or two strikes.
- Both faces are smooth, providing excellent wear capability.
- Measures 15 ½" x 3 1/8".



E-Z CONNECT™ Extra Large Pro-Tapping Block 6 CT

ITEM# TB-PRO-312



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.

WARNING: This product can expose you to chemicals including Nickel and Lead which are known to the State of California to cause cancer.

For more information visit: www.P65Warnings.ca.gov



HAMMER TACKERS





Hammer Tacker for A-11 or T-50	Staples 1/4" - 3/8" (6-10mm) Capacity 168 pcs, (2 STRIPS)	ITEM# HT A-11-10 Blue handle
Hammer Tacker for DUO-FAST 5000 series	Staples 1/4" - 3/8" (6-10mm) Capacity 168 pcs, (2 STRIPS)	ITEM# HT-5010 Blue handle



Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.



TIPPER-DE-TIPPER™

NEW DEVICE - Patent pending

The safest & fastest method to replace mallet caps!



DESCRIPTION:

- ELIMINATES RISK OF INJURY.
- Replaces mallet caps in 30 seconds.
- Robust construction virtually no maintenance.
- 5 STATION DESIGN fits all major brands of Round or Angle rubber caps.

PATENT # xxxxxxxxxxxxxx







Learn more at Pro-DriveFasteners.com Electro Galvanized steel provides a very thin layer of coating with a measure of protection against the elements. Over time these nails may corrode.

Not recommended for exterior application or ACO Treated Lumber.

To ensure maximum protection, use Stainless Steel type 316 staples.

WARNING: This product can expose you to chemicals including Nickel and Lead which are known to the State of California to cause cancer.

For more information visit: www.P65Warnings.ca.gov

