





PNEUMATIC BELT SANDERS 360-313 & 360-418



MATERIAL REMOVAL MADE EASY

360-313 and 360-418

Introducing the 360-313 and 360-418 Pneumatic Belt Sanders—engineered to make quick work of material removal and deliver smooth finishes. Whether removing spot welds, rust, deposits, or burrs; or fine-tuning a finished surface, these tools get the job done fast with a 0.6HP motor - 20% more than the leading competitor. Increase your productivity with tool-free belt changes (either 3/8" x 13", or 1/2" x 18") that make switching from one abrasive to the next quick and convenient, as well as a tool-free articulating arm that ensures every nook and cranny is easily reached. Additional belts can be purchased in the following kits – 360-313-KIT-BELT (for the 360-313 includes 1 of each belt – 100, 80, and 60 grit) and 360-418-KIT-BELT (for the 360-418 includes 1 of each belt – 100, 80, and 60 grit)



360-313 3/8" & 360-418 1/2" Pneumatic Belt Sanders							
Model	Arbor Speed (rpm)	Belt Speed (sfpm)	Belt Size in (mm)	Sound Level Presure dB(a)	Sound Level Power dB(a)	Weight Ib (kg)	Length in (mm)
360-313	20,000	4,700	%" x 13 (10 x 330)	90	101	2.29 (1.04)	12.4 (316)
360-418	20,000	4,700	½" x 18 (13 x 457)	92	103	2.40 (1.09)	15.1 (383)



Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency.