



259

3/4" Impactool™



Combining performance and value

Ingersoll Rand has long provided professionals with tools that deliver the power, durability, reliability, and value needed to get the job done right. Our 259 3/4" Impactool™ is yet another example of this legacy — offering impressive performance, value, and convenience not found in competitive models.

The 259 is smaller and up to 2 pounds lighter than other 3/4" impacts in its class. Together with its improved weight distribution, this makes the tool easier to handle. And, unlike most other 3/4" impacts, the 259 doesn't require an upgrade to a 1/2" air line. This means lower shop costs and greater convenience of use ... all without sacrificing tool performance.



SPECIFICATIONS	
259 Impactool — 3/4" Drive	
Max Torque – ft-lb (Nm)	1,050 (1424)
Working Torque Range – ft-lb (Nm)	200 – 800 (271 – 1085)
Net Weight – lb (kg)	8.8 (4.0)
Overall Length – in (mm)	8.6 (218)
Average Free Speed – rpm	6,000
Impacting Sound Level – dbA	91.6
Average Air Consumption – cfm (L/min)	8 (227)
Air Consumption @ Load – cfm (L/min)	30 (850)
Air Inlet NPT – in	3/8
Min Hose Size – in (mm)	3/8 (10)



Distributed by:

