

BIO CLEAR

Biological Grease-Trap and Drain Maintainer

DESCRIPTION

Bio Clear is a stable liquid containing selected micro-organisms and enzymes, that efficiently reduce the wastes typically evacuated into the drainage systems of kitchens and other catering and food processing units. Bio Clear is suitable for use in all types of drains, sinks and small-bore pipes, as well as for maintaining septic tanks, grease traps and complete sewerage systems.

Bio Clear has a two-stage operation. When activated with water, the 'free' enzymes quickly break down the waste into smaller pieces, which are more accessible to the micro-organisms. This initial degradation immediately improves drain flow-rates and reduces odours. It also enables the various strains of micro-organisms in Bio Clear to quickly continue the degrading process, further reducing the smaller particles of solid waste (such as fat, paper and vegetable trimmings) into liquids and gasses.

FEATURES AND BENEFITS

- § Degrades grease and solid waste
- § Neutral PH of 6.5 – 7.5
- § Effective on all types of drains and small-bore pipes
- § Maintains septic tanks, grease traps and complete sewerage systems
- § Reduces odours
- § Improves drain flow-rates
- § No Harmful properties

TECHNICAL INFORMATION

Bio Clear contains many strains of non-harmful micro-organisms, typically 50,000,000 units per millilitre. Bio Clear is a tan liquid with a very slight yeast fragrance

PACKAGING

<i>code</i>		
BC 5	BIO CLEAR	4 X 5L
BC 20	BIO CLEAR	20L

STORAGE

Bio Clear is stable for a minimum of 12 months if stored in it's original, sealed container, in cool dry conditions, away from direct sunlight. Bio Clear is not harmful or irritant under CHIP or COSHH.

DIRECTIONS *Shake well before use*

GREASE TRAP MAINTENANCE An initial dose of 500ml should be poured into any sink outlet flowing into the trap & flushed with a little water. To maintain the grease-trap apply 1ml per meal (per day) into waste outlets to the trap ie 50 meals/day = 50 ml/day. For best results use an automatic dosing system.

DRAIN MAINTENANCE For free-flowing odourless drains pour 50 ml into sinks or drain outlets during quiet periods, once each week.

Disinfectants, bleach caustic and acid products will adversely effect the biological action of Bio-Clear. Drainage systems cannot be damaged or overdosed by this product.

