PRÓCHEM。

Product Specification Sheet

R602 PROSEAL

LABEL INSTRUCTIONS

Product Description & Directions for Use:

A water-based seal for use on vinyl, linoleum, thermoplastic, rubber, asphalt, terrazzo and other semi-porous or impoverished internal floor surfaces. Proseal provides a base-coat quality seal with a satin finish which can then be top-coated with Proshine if required.

For professional and industrial use only.

Proseal is ready-to-use. Do not dilute with water.

Coverage is approximately 150 to 200m² per 5 litres, depending upon porosity of floor. Floor should be thoroughly cleaned with Prostrip and rinsed with Prorinse to ensure removal of all traces of old polish, seals and detergent residues. Apply two or three thin even coats with a slightly damp mop or polish applicator allowing 30 to 60 minutes drying between coats. **Do not over apply.** Allow final coat to dry completely before the floor is re-used. A top coat of Proshine can be applied if a gloss finish is required. The floor can be maintained with Protreat.



- Water-based acrylic floor seal
- Suitable for vinyl, linoleum, thermoplastic, rubber, asphalt, terrazzo and semi-porous floor surfaces.
- Provides base-coat seal with satin finish which can be top-coated with Proshine if required.
- White emulsion with acrylic odour.

pH Concentrate: 8.5 pH Diluted: Not applicable

Contains 2,4,7,9-Tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Wear protective gloves. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice / attention.

Safety data sheet available on request.

Please consult the Safety Data Sheet before using this product.

This product is intended for professional use only. The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.