
KDE DIRECT 102XX SERIES BEARING SCHEMATIC KDE10218XF-105 (HE) ANGULAR CONTACT EDITION









 ϕ 15MM x ϕ 21MM x 1MM **BRASS ROUND-HOLE SHIM**





ARROW POINTS UP TOWARDS RADIAL BALL BEARING





-7902C (Ø15MM x Ø28MM x 7MM) ANGULAR-CONTACT BALL BEARING NSK-BRAND, HPS SERIES DOWNWARD FORCE ORIENTATION







ARROW POINTS DOWN TOWARDS SHAFT RETAINING COLLAR





-7202C (Ø 15MM x Ø 35MM x 11MM) ANGULAR-CONTACT BALL BEARING NSK-BRAND, HPS SERIES UPWARD FORCE ORIENTATION




- Φ15MM x Φ21MM x 1MM BRASS ROUND-HOLE SHIM









1. ALL DIMENSIONS APPLY BEFORE PLATING OR COATING 2. REMOVE ALL BURRS, BREAK SHARP EDGES .020 IN MAX

IMPERIAL

THIRD ANGLE PROJECTION

X. X.X X.XX X.XXX TOLERANCES.

± 0.040" ± 0.020" ± 0.010" ± 0.005" ± 1° ANGULAR

DESIGNED KDE DIRECT KDE DIRECT RAWN XX/XX/XXXX

TITLE. KDE DIRECT 102XX BEARING SCHEMATIC

KDE102XX SERIES