



Bright Plus Concrete Sealer/Densifier

Description:

Bright Plus is a unique blend of silicates & surfactants providing superior results that penetrate concrete surfaces that chemically react to increase surface density, durability & abrasion resistance.

Intended Use:

Interior & Exterior
Extend the useful life of Concrete
Low Cost Concrete Treatment
Reduce Permeability & Increase Hardness
Abrasion & Scuff Resistance
Optimizes Gloss

Product Features:

Improves Chemical Resistance
Penetrates to provide long term performance
Once dry insoluble
Forms a stable <High Ratio>, <Low Viscosity> solution
Improved Coefficient of Friction

Physical Properties:

•FlashPoint..... None
•Viscosity..... 34 CP
•Color..... Clear
•Type of Solids..... Silicates Proprietary

Limitations of Use:

Commercial Use Only

Customer Service:

Call or Visit ResinTek
Toll Free: 1-833-693-7699
E-mail: info@resinteksystems.com

ResinTek
1817 S. Horne Suite 13 Mesa, AZ 85204
833-693-7699

Chemtrec 1-800-424-9300

TECHNICAL DATA SHEET

Surface Preparation:

Should not be applied to any surface that has already been treated with compounds that might prevent penetration of the silicate <e.g. paint, oil, > or that interfere with the conversion of free lime. Before any concrete is treated the surface must be cleaned.

Remove all loose soil and debris with a broom or dust mop. Apply 150 degreaser at 8oz to gallon scrub thoroughly & rinse with clear water. It is recommended to repeat these steps to insure all contaminants are removed from the surface. For best penetration it is recommended to wait 24 hours for the surface to dry.

Mixing Instructions:

Ready to use

Application Instructions:

For diamond polishing after 200 grit apply Diamond Bright Plus with pump sprayer or pour directly on the surface and spread evenly with a flat microfiber pad. Apply at the rate 250 Gallon per sq ft when dry proceed to polish with 400 grit diamonds and repeat the application of Diamond Bright Plus when dry polish with 800 grit diamonds. You may choose to continue polishing to 3000 grit however it is not necessary.

Storage:

Containers must be sealed. Store in cool dry place above 40 F away from water, heat & open flames. Provide adequate ventilation. Disposal according to local regulations

Compliances:

voc Less than 25gm/L

Chemical Resistance:

N/A

Precautions:

Please refer to the appropriate safety data sheet prior to using this product.

For technical assistance call customer service at 833-693-7699

Other Notes: Keep containers closed when not in use and upright to prevent leaking DO NOT take internally. Wash hands after using and before eating. Keep Out of Reach of Children