



RTE-CT

High Performance Epoxy Coating

TECHNOLOGY DESCRIPTION

ResinTek coatings represent the next generation of epoxy flooring technology. Many of these high performance coatings utilize domestically produced soy bean oil and environmentally friendly packaging.

PRODUCT DESCRIPTION

ResinTek is a two-component, 100% solids, high performance epoxy floor coating that provides a high gloss, seamless, hygienic surface that is hard and durable. Mixed with color packs, this durable material cures to a smooth, glossy surface or, with the addition of aggregate, a non-skid texture. Color quartz or color flakes can also be used as a broadcast to produce a seamless, decorative finish.

TYPICAL PROPERTIES AT 70 °F

Compressive Strength (ASTMC-579).....	8,200 psi
Tensile Strength (ASTM D-638).....	1,650 psi
Flexural Strength (ASTM C-580).....	3,600 psi
Hardness, Shore D (ASTM D-2240).....	85 – 90
Bond Strength (ASTM D-4541).....	425 psi
Abrasion Resistance (ASTM D-4060).....	80 mg
Volume Solids.....	100%

The data shown above reflects typical results based on laboratory testing under controlled conditions. Variations from the data shown may result. Test methods are modified where applicable.

INSTALLATION DATA

Storage Environment.....	Dry area, 65–80°F
Application Temperature, ambient.....	50–95°F
Application Temperature, substrate.....	Minimum 5°F above dew point
Shelf Life.....	1 year
Pot Life, @ 77°F.....	25 minutes
Foot Traffic, @ 77°F.....	12–24 hours
Service, @ 77°F.....	Light: 24 hours / Full: 48–72 hours
Recoat Window.....	within 24 hours at 70F

IMPORTANT INFORMATION

1. Like all epoxies, not 100% color stable without use of UV stable topcoat.
2. Not designed for exterior use or constant immersion applications.
3. Floors should be sloped to drain to prevent standing water or chemicals.
4. Confirm product performance in specific chemical environment prior to use.
5. Prepare substrate according to “Surface Preparation” portion of this document.
6. Do not apply to slabs on grade unless a heavy unruptured vapor barrier has been installed under the slab or where moisture or MVT is present.
7. Always use protective clothing consistent with OSHA regulations during use.
8. Refer to Material Safety Data Sheet for detailed safety precautions.
9. For industrial/commercial use. Installation by trained personnel only.

TECHNICAL DATA SHEET

BENEFITS

- Multiple system possibilities with one product
 - Full gloss finish
 - Multi-color quartz and flake finishes
 - Various surface finishes available
 - Can be used as a primer, base, topcoat
- Seamless, monolithic application
- Durable finish, chemical resistant
- Available in clear and a wide array of colors
- Zero VOC, very low odor

RECOMMENDED USES

- Warehousing & manufacturing facilities
- Chemical processing plants
- Laboratories, hospitals, healthcare facilities
- Stadiums & other entertainment venues
- Educational & institutional facilities
- Cafeterias, kitchens, storefronts, aisles
- Bathrooms, showers
- Topcoat over VerdeFloor floor systems

GENERIC DESCRIPTION

Multi-Purpose Epoxy Coating

TYPICAL APPLICATION

Floor Coating (primer plus 2 coats)
Aggregate, Color Quartz or Flake broadcast
Top Coat over VerdeFloor systems

STANDARD COLORS

Clear. Variety of color pack options available

PACKAGING & COVERAGE

3 Gallon, 15 Gallon, 150 Gallon units
2 to 1 Mix Ratio A:B
2 Part A Resin : 1 Part B Hardener

100 sqft / gallon @ 16 mils

SURFACE PREPARATION

Concrete: Apply only to clean, dry and sound concrete substrates that are free of all coatings, sealers, curing compounds, oils, greases or any other contaminants.

- *New concrete should be cured a minimum of 28 days.*
- *Concrete that has been contaminated with chemicals or other foreign matter must be neutralized or removed.*
- *Remove any laitance or weak surface layers.*
- *Concrete should have a minimum surface tensile strength of at least 300 PSI per ASTM D-4541.*
- *Surface profile shall be CSP-3 to CSP-5 meeting ICRI (International Concrete Repair Institute) standard guideline #03732 for coating concrete, producing a profile equal to 60-grit sandpaper or coarser. Prepare surface by mechanical means to achieve this desired profile.*
- *Moisture vapor transmission should be 3 pounds or less per 1,000 square feet over a 24 hour time period, as confirmed through a calcium chloride test, as per ASTM E-1907. Quantitative relative humidity (RH) testing, ASTM F-2170, should confirm concrete RH results <75%.*
- *All surface irregularities, cracks, expansion joints and control joints should be properly addressed prior to application.*
- *Outgassing may occur due to the porosity of some concrete surfaces. To reduce the effect of outgassing, the primer and coating should be applied when the temperature of the concrete substrate is dropping. This usually occurs in the evening; however, the concrete substrate temperature should be measured with a surface thermometer for verification. Double priming will greatly reduce the effects of outgassing by additionally filling the pores in the concrete.*

INSTALLATION STEPS

1. Mix Ratio 2:1 Resin to Hardener
2. Prime concrete surface with ResinTek Primer @ 175-250 sqft / gallon. Primer coat of advised primer may be thinned with up to 5% Xylene or IsoPropyl Alcohol. Or prime with ResinTek Advised product for green concrete applications.
3. Part A should be premixed prior to use
4. If pigmented color is to be used, add pre-mixed color pack to Part A. Add one color pack per 3 mixed gallons. NOTE: For white, light gray, tan and safety colors, use 2 color packs per 3 mixed gallons for increased hiding.
5. Pour Part B into the Part A pail and mix for a minimum of two minutes, using a mechanical jiffy-type mixer operated at low speed. Scrape the side of the pail to ensure the entire product has been properly mixed; any unmixed material left on the side of the pail will not cure.
6. Apply mixed material by roller or squeegee and back-roll. Move quickly and empty epoxy coating out of the pail and onto concrete surface as quickly as possible to provide maximum working time. Material left in the pail will generate heat and have a reduced pot life.
NOTE: Back-roll lightly if necessary. DO NOT OVER ROLL. Too much rolling may introduce small air bubbles into system.
7. When applied as a non-skid coating, broadcast clean, dry silica sand or aluminum oxide aggregate into wet resin. Allow to dry. A full broadcast to refusal will produce the best looking and most durable system. Remove all excess grit and scrape floor before applying second coat.
8. After the first coat has become tack free (within approximately 10 hours of cure @70°F and before exceeding 24 hour recoat window), apply a second coat.
9. ResinTek offers a complete line of topcoats for increased resistance to UV exposure, chemicals and high traffic.

© Copyright 2015 ResinTek. All rights reserved. Published technical data and instructions are subject to change without notice. Please contact ResinTek for the most current technical data and instructions.

Rev 9/15

ResinTek, warrants its products to be free from defects in material and workmanship. Verdia's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Verdia's option, to either replacement of products not conforming to this warranty or credit to Buyer's account in the invoiced amount of the nonconforming products. Any claim under this Warranty must be made by Buyer to ResinTek in writing within five days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify ResinTek of such nonconformance as required herein shall bar Buyer from recovery under this warranty.

ResinTek makes no other warranties concerning this product. No other warranties, either expressed or implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply. In no event shall ResinTek be liable for consequential or incidental damages.

Any recommendation or suggestion relating to the use of the products made by ResinTek, whether in its technical literature, or in response to specific inquiry, or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use, and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment changes in procedures of use, or extrapolation of data may cause unsatisfactory results. ResinTek cannot guarantee that color will conform to sample, if provided.