



## GUARD URETHANE FORTIFIED

### Description:

Superior to conventional Guard products all new technology providing improved surface wear performance with exceptional gloss and safety standards for polish hard surfaces including granite stone & concrete

### Intended Use:

New advanced chemical technology to protect polish concrete from chemical stains superior gloss and resistance to abrasion from heavy traffic conditions

### Product Features:

- Gloss..... Excellent
- Durability..... Exceptional
- Water/Detergent Resistance..... Excellent
- Leveling..... Superior

### Physical Properties:

- Solids..... 12%
- PH..... 8.56-9.5
- Viscosity ,cps..... N/A
- Specific Gravity..... 1.02
- Weight/Gallon(LBS)..... 8.95
- Appearance..... Off-White Emulsion
- Freeze/Thaw Stability.... Do Not Freeze

### Limitations of Use:

Commercial Use Only

### Customer Service:

Call or Visit ResinTek  
Toll Free: 1-833-693-7699  
E-mail: [info@resinteksystems.com](mailto:info@resinteksystems.com)

ResinTek  
1817 S. Horne Suite 13 Mesa, AZ 85204  
833-693-7699

Chemtrec 1-800-424-9300

### Surface Preparation:

Prior to applying this product remove all previous materials and surface soil rinse thoroughly with clear water and allow the surface to dry

### Mixing Instructions:

No mixing is required

### Application Instructions:

Apply with a clean microfiber pad pour the guard on the surface and apply a thin even coat allow for adequate time for the coat to dry. a second coat is recommended for optimal performance, it is also recommended to burnish after the second coat is dry

### Note:

Guard coverage is approximately 3500 SQFT per gallon on polish concrete surface

### Storage:

Do not store above 100F also protect from freezing

### Compliances:

Carb compliant less than 1% VOC

### Chemical Resistance:

Results after one hour dry time of the following chemicals

- Coffee..... 10
- Red Wine..... 10
- Pickle Brine..... 10
- Vinegar..... 10
- Phosphoric Acid..... 10

Scale Rating = 1-10 Worse - 10 Best

### Precautions:

Please refer to the appropriate material safety data sheet (MSDS) prior to using this product.

For technical assistance, please call 833-693-7699

FOR INDUSTRIAL / PROFESSIONAL USE ONLY

KEEP OUT OF REACH OF CHILDREN